



MILITARY DATA SHEET

MN54F244-X REV 1A0

Original Creation Date: 04/15/96
Last Update Date: 07/30/96
Last Major Revision Date: 04/15/96

OCTAL BUFFER/LINE DRIVER WITH TRI-STATE OUTPUTS

General Description

The F244 is an octal buffer and line driver designed to be employed as a memory and address driver, clock driver and bus-oriented transmitter/receiver which provides improved PC and board density.

Industry Part Number

54F244

NS Part Numbers

54F244DMQB
54F244FMQB
54F244LMQB

Prime Die

M244

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

Features

- 3-State Outputs Drive Bus Lines or Buffer Memory Address Registers
- Outputs Sink 48 mA
- 12mA Source Current
- Input Clamp Diodes Limit High-Speed Termination Effects

(Absolute Maximum Ratings)

(Note 1)

Storage Temperature	-65 C to +150 C
Ambient Temperature under Bias	-55 C to +125 C
Junction Temperature under Bias	-55 C to +175 C
Vcc Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30mA to +5.0mA
Voltage Applied to Output in HIGH State (with Vcc=0V)	
Standard Output	-0.5V to Vcc
TRI-STATE Output	-0.5V to +5.5V
Current Applied to Output in LOW State (Max)	twice the rated Iol(mA)
ESD Last Passing Voltage (Min)	4000V

Note 1: Absolute maximum ratings are those values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature	
Commercial	0 C to +70 C
Military	-55 C to +125 C
Supply Voltage	
Military	+4.5V to +5.5V
Commercial	+4.5V to +5.5V

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
DC: VCC 4.5V to 5.5V, Temp range:-55C to 125C

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	Input High Current	VCC=5.5V, VM=2.7V, VINL=0.0V	1, 3	INPUTS		20	uA	1, 2, 3
IBVI	Input High Current	VCC=5.5V, VM=7.0V, VINL=5.5V	1, 3	INPUTS		100	uA	1, 2, 3
IIL	Input LOW Current	VCC=5.5V, VM=0.5V, VINH=5.5V	1, 3	Dn		-1.6	mA	1, 2, 3
IIL2	Input LOW Current	VCC=5.5V, VM=0.5V, VINH=5.5V	1, 3	OE1, OE2		-1.0	mA	1, 2, 3
VOLB	Output LOW Voltage	VCC=4.5V, VIL=0.8V, VIH=2.0V, IOL=48mA, VINH=5.5V	1, 3	OUTPUTS		.55	V	1, 2, 3
VOHB	Output HIGH Voltage	VCC=4.5V, VIL=0.8V, IOHB=-12mA, VINH=5.5V, VIH=2.0V	1, 3	OUTPUTS	2.0		V	1, 2, 3
VOH3	Output HIGH Voltage	VCC=4.5V, VIL=0.8V, IOH3=-3.0mA, VINH=5.5V, VIH=2.0V	1, 3	OUTPUTS	2.4		V	1, 2, 3
IOS	Short Circuit Current	VCC=5.5V, VINL=0.0V, VM=0.0V, VINH=5.5V	1, 3	OUTPUTS	-100	-225	mA	1, 2, 3
VCD	Input Clamp Diode Voltage	VCC=4.5V, IM=-18mA, VINH=5.5V	1, 3	INPUTS		-1.2	V	1, 2, 3
ICCH	Supply Current	VCC=5.5V, VINL=0.0V, VINH=5.5V	1, 3	VCC		60	mA	1, 2, 3
ICCL	Supply Current	VCC=5.5V, VINL=0.0V	1, 3	VCC		90	mA	1, 2, 3
ICCZ	Supply Current	VCC=5.5V, VINH=5.5V	1, 3	VCC		90	mA	1, 2, 3
ICEX	Output HIGH Leakage Current	VCC=5.5V, VINH=5.5V, VINL=0.0V, VM=5.5V	1, 3	OUTPUTS		250	uA	1, 2, 3
IOZH	Output Leakage Current	VCC=5.5V, VM=2.7V, VIH=2.0V, VINL=0.0V	1, 3	OUTPUTS		50	uA	1, 2, 3
IOZL	Output Leakage Current	VCC=5.5V, VM=0.5V, VIH=2.0V, VINH=5.5V	1, 3	OUTPUTS		-50	uA	1, 2, 3

Electrical Characteristics

AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
 AC: RL=500 OHMS, CL=50pf TR=2.5ns, TF=2.5ns SEE AC FIGS

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpLH	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	In to On	2.5	5.2	ns	9
			2, 4	In to On	2.0	6.5	ns	10, 11
tpHL	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	In to On	2.5	5.2	ns	9
			2, 4	In to On	2.0	7.0	ns	10, 11
tpZH	Output Enable Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	\overline{OE} to On	2.0	5.7	ns	9
			2, 4	\overline{OE} to On	2.0	7.0	ns	10, 11
tpZL	Output Enable Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	\overline{OE} to On	2.0	7.0	ns	9
			2, 4	\overline{OE} to On	2.0	8.5	ns	10, 11
tpHZ	Output Disable Time	VCC=5.0V @25C VCC=4.5V & 5.5V @-55/125C	2, 4	\overline{OE} to On	2.0	6.0	ns	9
			2, 4	\overline{OE} to On	2.0	7.0	ns	10, 11
tpLZ	Output Disable Time	VCC=5.0V @25C VCC=4.5V & 5.5V @-55/125C	2, 4	\overline{OE} to On	2.0	6.0	ns	9
			2, 4	\overline{OE} to On	2.0	7.5	ns	10, 11

Note 1: Screen tested 100% on each device at +25C, +125C & -55C temperature, subgroups A1, 2, 3, 7 & 8.

Note 2: Screen tested 100% on each device at +25C temperature only, subgroup A9.

Note 3: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C, +125C & -55C temperature, subgroups A1, 2, 3, 7 & 8.

Note 4: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C subgroup A9, and periodically at +125C & -55C temperature, subgroups 10 & 11.

National Semiconductor was acquired by Texas Instruments.

http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html

This file is the datasheet for the following electronic components:

JM38510/33203SSA - <http://www.ti.com/product/jm38510/33203ssa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F244FMQB - <http://www.ti.com/product/54f244fmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F244DMQB - <http://www.ti.com/product/54f244dmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/33203BSA - <http://www.ti.com/product/jm38510/33203bsa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F244LMQB - <http://www.ti.com/product/54f244lmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/33203SRA - <http://www.ti.com/product/jm38510/33203sra?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/33203B2A - <http://www.ti.com/product/jm38510/33203b2a?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/33203BRA - <http://www.ti.com/product/jm38510/33203bra?HQS=TI-null-null-dscatalog-df-pf-null-wwe>



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.