



MILITARY DATA SHEET

MN54F245-X REV 1A0

Original Creation Date: 04/18/96
 Last Update Date: 07/30/96
 Last Major Revision Date: 04/18/96

OCTAL BIDIRECTIONAL TRANSCEIVER WITH 3-STATE INPUTS/OUTPUTS

General Description

The F245 contains eight non-Inverting bidirectional buffers with 3-state outputs and is intended for bus-oriented applications. Current sinking capability is 20mA at the A ports and 48 mA at the B ports. The Transmit/Receiver(T/R) input determines the direction of data flow through the bidirectional transceiver. Transmit (active HIGH) enables data from A ports to B ports; Receiver (active LOW) enables data from B ports to A ports. The Output Enable input, when HIGH, disables both A and B ports by placing them in a HIGH Z condition.

Industry Part Number

54F245

NS Part Numbers

54F245DMQB
 54F245FMQB
 54F245LMQB

Prime Die

M245

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

Features

- Non-Inverting Buffers
- Bidirectional Data Path
- B Outputs Sink 48 mA

(Absolute Maximum Ratings)

(Note 1)

Storage Temperature	-65 C to +150 C
Ambient Temperature under Bias	-55 C to +125 C
Junction Temperature under Bias	-55 C to +175 C
Vcc Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30mA to +5.0mA
Voltage Applied to Output in HIGH State (with Vcc=0V)	
Standard Output	-0.5V to Vcc
TRI-STATE Output	-0.5V to +5.5V
Current Applied to Output in LOW State (Max)	twice the rated Iol(mA)
ESD Last Passing Voltage (Min)	4000V

Note 1: Absolute Maximum ratings are those values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature	
Commercial	0 C to +70 C
Military	-55 C to +125 C
Supply Voltage	
Military	+4.5V to +5.5V
Commercial	+4.5V to +5.5V

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
DC: VCC 4.5V to 5.5V, Temp range: -55C to 125C

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	Input High Current	VCC=5.5V, VM=2.7V, VINH=5.5V	1, 3	INPUTS		20	uA	1, 2, 3
IBVI	Input High Current	VCC=5.5V, VM=7.0V, VINH=5.5V (\overline{OE} , T/ \overline{R})	1, 3	INPUTS		100	uA	1, 2, 3
IBVIT	Input High Current	VCC=5.5V, VM=5.5V, VINH=5.5V, VINL=0.0V (An, Bn)	1, 3	INPUTS		1.0	mA	1, 2, 3
IIL2	Input LOW Current	VCC=5.5V, VM=0.5V, VINH=5.5V (T/ \overline{R} , \overline{OE})	1, 3	INPUTS		-1.2	mA	1, 2, 3
VOL	Output LOW Voltage	VCC=4.5V, VIL=0.8V, IOL=20mA (An)	1, 3	OUTPUTS		0.5	V	1, 2, 3
VOLB	Output LOW Voltage	VCC=4.5V, VIL=0.8V, VIH=2.0V, IOLB=48mA (Bn)	1, 3	OUTPUTS		.55	V	1, 2, 3
VOH	Output HIGH Voltage	VCC=4.5V, VIL=0.8V, IOH=-1.0mA, VIH=2.0V	1, 3	OUTPUTS	2.5		V	1, 2, 3
VOH3	Output HIGH Voltage	VCC=4.5V, VIL=0.8V, IOH3=-3.0mA, VIH=2.0V (An)	1, 3	OUTPUTS	2.4		V	1, 2, 3
VOHB	Output HIGH Voltage	VCC=4.5V, VIL=0.8V, IOHB=-12mA, VIH=2.0V (Bn)	1, 3	OUTPUTS	2.0		V	1, 2, 3
IOS	Short Circuit Current	VCC=5.5V, VINL=0.0V, VOUT=0.0V, VINH=5.5V (An)	1, 3	OUTPUTS	-60	-150	mA	1, 2, 3
IOSB	Short Circuit Current	VCC=5.5V, VINL=0.0V, VOUT=0.0V, VINH=5.5V (Bn)	1, 3	OUTPUTS	-100	-225	mA	1, 2, 3
VCD	Input Clamp Diode Voltage	VCC=4.5V, IM=-18mA, VINH=5.5V	1, 3	INPUTS		-1.2	V	1, 2, 3
ICCH	Supply Current	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 3	VCC		90	mA	1, 2, 3
ICCL	Supply Current	VCC=5.5V, VINL=0.0V, VINH=5.5V	1, 3	VCC		120	mA	1, 2, 3
ICCZ	Supply Current	VCC=5.5V, VINL=0.0V, VINH=5.5V	1, 3	VCC		110	mA	1, 2, 3
ICEX	Output HIGH Leakage Current	VCC=5.5V, VINL=0.0V, VINH=5.5V, VM=5.5V (An, Bn)	1, 3	OUTPUTS		250	uA	1, 2, 3
IOZHT	Output Leakage Current	VCC=5.5V, VM=2.7V, VIH=2.0V, VINH=5.5V, VINL=0.0V (An, Bn)	1, 3	OUTPUTS		70	uA	1, 2, 3
IOZLT	Output Leakage Current	VCC=5.5V, VM=0.5V, VIH=2.0V, VINH=5.5V, VINL=0.0V (An, Bn)	1, 3	OUTPUTS		-650	uA	1, 2, 3

Electrical Characteristics

AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
 AC: CL=50pf, RL=500 OHMS, TR=2.5ns, TF=2.5ns SEE AC FIGS

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpLH	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	An/Bn or Bn/An	2.5	6.0	ns	9
			2, 4	An/Bn or Bn/An	2.0	7.5	ns	10, 11
tpHL	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	An/Bn or Bn/An	2.5	6.0	ns	9
			2, 4	An/Bn or Bn/An	2.0	7.5	ns	10, 11
tpZH	Output Enable Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	OUTPUT ENABLE	3.0	7.0	ns	9
			2, 4	OUTPUT ENABLE	2.5	9.0	ns	10, 11
tpZL	Output Enable Time	VCC=5.0V @25C VCC=4.5V & 5.5V @-55/125C	2, 4	OUTPUT ENABLE	3.5	8.0	ns	9
			2, 4	OUTPUT ENABLE	3.0	10.0	ns	10, 11
tpHZ	Output Disable Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	OUTPUT DISABLE	2.0	6.5	ns	9
			2, 4	OUTPUT DISABLE	2.0	9.0	ns	10, 11
tpLZ	Output Disable Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	OUTPUT DISABLE	2.0	6.5	ns	9
			2, 4	OUTPUT DISABLE	2.0	10.0	ns	10, 11

- Note 1: Screen tested 100% on each device at +25C, +125C, & -55C temperature, subgroups A1, 2, 3, 7 & 8.
- Note 2: Screen tested 100% on each device at +25C temperature only, subgroup A9.
- Note 3: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C, +125C & -55C temperature, subgroups A1, 2, 3, 7 & 8.
- Note 4: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C subgroup A9, and periodically at +125C & -55C temperature, subgroups 10 & 11.

National Semiconductor was acquired by Texas Instruments.

http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html

This file is the datasheet for the following electronic components:

54F245DMQB - <http://www.ti.com/product/54f245dmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34803BSA - <http://www.ti.com/product/jm38510/34803bsa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34803SSA - <http://www.ti.com/product/jm38510/34803ssa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34803BRA - <http://www.ti.com/product/jm38510/34803bra?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34803B2A - <http://www.ti.com/product/jm38510/34803b2a?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/34803SRA - <http://www.ti.com/product/jm38510/34803sra?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F245LMQB - <http://www.ti.com/product/54f245lmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F245FMQB - <http://www.ti.com/product/54f245fmqb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.