

SOT23 NPN SILICON PLANAR DARLINGTON TRANSISTORS

BCV27 BCV47


ISSUE 3 – SEPTEMBER 1995

FEATURES

- * High V_{CE0}
- * Low saturation voltage

COMPLEMENTARY TYPES – BCV27 – BCV28
BCV47 – BCV48

PARTMARKING DETAILS – BCV27 – ZFF
BCV47 – ZFG



SOT23

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	BCV27	BCV47	UNIT
Collector-Base Voltage	V_{CBO}	40	80	V
Collector-Emitter Voltage	V_{CEO}	30	60	V
Emitter-Base Voltage	V_{EBO}	10		V
Peak Pulse Current	I_{CM}	800		mA
Continuous Collector Current	I_C	500		mA
Base Current	I_B	100		mA
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{tot}	330		mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150		$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$ unless otherwise stated).

PARAMETER	SYMBOL	BCV27		BCV47		UNIT	CONDITIONS.
		MIN.	MAX.	MIN.	MAX.		
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	40		80		V	$I_C=100\mu\text{A}$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	30		60		V	$I_C=10\text{mA}^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	10		10		V	$I_E=10\mu\text{A}$
Collector Cut-Off Current	I_{CBO}		100		100	nA nA μA μA	$V_{CB}=30\text{V}$ $V_{CB}=60\text{V}$ $V_{CB}=30\text{V}, T_{amb}=150^\circ\text{C}$ $V_{CB}=60\text{V}, T_{amb}=150^\circ\text{C}$
Emitter Base Cut-Off Current	I_{EBO}		100		100	nA	$V_{EB}=4\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		1.0		1.0	V	$I_C=100\text{mA}, I_B=0.1\text{mA}^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$		1.5		1.5	V	$I_C=100\text{mA}, I_B=0.1\text{mA}^*$
Static Forward Current Transfer Ratio	h_{FE}	4K 10K 20K 4K		2K 4K 10K 2K			$I_C=100\mu\text{A}, V_{CE}=1\text{V}^\dagger$ $I_C=10\text{mA}, V_{CE}=5\text{V}^*$ $I_C=100\text{mA}, V_{CE}=5\text{V}^*$ $I_C=500\text{mA}, V_{CE}=5\text{V}^*$
Transition Frequency	f_T	170 Typical		170 Typical		MHz	$I_C=50\text{mA}, V_{CE}=5\text{V}$ $f = 20\text{MHz}$
Output Capacitance	C_{obo}	3.5 Typical		3.5 Typical		pF	$V_{CB}=10\text{V}, f=1\text{MHz}$

*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$

† Periodic Sample Test Only. For typical graphs see FMMT38A datasheet



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.