


NPN

Surface mount Si-Epitaxial Planar Transistors
Si-Epitaxial Planar Transistoren für die Oberflächenmontage

NPN



Power dissipation – Verlustleistung 250 mW

Plastic case SOT-23
 Kunststoffgehäuse (TO-236)

Weight approx. – Gewicht ca. 0.01 g

Plastic material has UL classification 94V-0
 Gehäusematerial UL94V-0 klassifiziert

Standard packaging taped and reeled
 Standard Lieferform gegurtet auf Rolle

Maximum ratings ($T_A = 25^\circ\text{C}$)**Grenzwerte ($T_A = 25^\circ\text{C}$)**

			BF 554
Collector-Emitter-voltage	B open	V_{CE0}	20 V
Collector-Base-voltage	E open	V_{CB0}	30 V
Emitter-Base-voltage	C open	V_{EB0}	5 V
Power dissipation – Verlustleistung		P_{tot}	250 mW ¹⁾
Collector current – Kollektorstrom (dc)		I_C	30 mA
Peak Collector current – Kollektor-Spitzenstrom		I_{CM}	30 mA
Junction temperature – Sperrschichttemperatur		T_j	150 °C
Storage temperature – Lagerungstemperatur		T_S	- 65...+ 150 °C

Characteristics ($T_j = 25^\circ\text{C}$)**Kennwerte ($T_j = 25^\circ\text{C}$)**

		Min.	Typ.	Max.
Collector-Base cutoff current – Kollektorreststrom				
$I_E = 0, V_{CB} = 20\text{ V}$	I_{CB0}	–	–	100 nA
$I_E = 0, V_{CB} = 20\text{ V}, T_j = 100^\circ\text{C}$	I_{CB0}	–	–	10 μA
DC current gain – Kollektor-Basis-Stromverhältnis ²⁾				
$V_{CE} = 10\text{ V}, I_C = 1\text{ mA}$	h_{FE}	60	–	250

¹⁾ Mounted on P.C. board with 3 mm² copper pad at each terminal
 Montage auf Leiterplatte mit 3 mm² Kupferbelag (Löt-pad) an jedem Anschluß

²⁾ Tested with pulses $t_p = 300\ \mu\text{s}$, duty cycle $\leq 2\%$ – Gemessen mit Impulsen $t_p = 300\ \mu\text{s}$, Schaltverhältnis $\leq 2\%$

Characteristics ($T_j = 25^\circ\text{C}$)Kennwerte ($T_j = 25^\circ\text{C}$)

	Min.	Typ.	Max.
Base-Emitter voltage – Basis-Emitter-Spannung ¹⁾ $V_{CE} = 10\text{ V}, I_C = 1\text{ mA}$ V_{BEon}	–	700 mV	–
Gain-Bandwidth Product – Transitfrequenz $V_{CE} = 5\text{ V}, I_C = 10\text{ mA}, f = 100\text{ MHz}$ f_T	–	250 MHz	–
Collector-Base Capacitance – Kollektor-Basis-Kapazität $V_{CB} = 10\text{ V}, I_E = i_e = 0, f = 1\text{ MHz}$ C_{CB0}	–	0.6 pF	–
Noise figure – Rauschzahl at / bei $V_{CE} = 10\text{ V}, I_C = 1\text{ mA}$ $f = 200\text{ kHz}$ F	–	1.5 dB	–
$f = 1\text{ MHz}$ F	–	1.2 dB	–
$f = 100\text{ MHz}$ F	–	3 dB	–
Output admittance – Ausgangs-Leitwert $V_{CE} = 10\text{ V}, I_C = 1\text{ mA}, f = 0.5...10\text{ MHz}$ h_{oe}	–	4 μS	
Thermal resistance junction to ambient air Wärmewiderstand Sperrschicht – umgebende Luft	R_{thA}		420 K/W ²⁾

Marking - Stempelung

BF 554 = CC

¹⁾ Tested with pulses $t_p = 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$ – Gemessen mit Impulsen $t_p = 300\text{ }\mu\text{s}$, Schaltverhältnis $\leq 2\%$

²⁾ Mounted on P.C. board with 3 mm^2 copper pad at each terminal
Montage auf Leiterplatte mit 3 mm^2 Kupferbelag (Lötpad) an jedem Anschluß

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.