

SOT223 PNP SILICON PLANAR HIGH VOLTAGE TRANSISTOR

BSP15


ISSUE 3 – FEBRUARY 1996

FEATURES

- * High V_{CE0}
- * Low saturation voltage

COMPLEMENTARY TYPE: – BSP20

PARTMARKING DETAIL: – BSP15



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	-200	V
Collector-Emitter Voltage	V_{CEO}	-200	V
Emitter-Base Voltage	V_{EBO}	-5	V
Peak Pulse Current	I_{CM}	-1	A
Continuous Collector Current	I_C	-0.5	A
Power Dissipation at $T_{amb}=25^{\circ}C$	P_{tot}	2	W
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^{\circ}C$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-200		V	$I_C = -100\mu A$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-200		V	$I_C = -10mA^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-5		V	$I_E = -100\mu A$
Collector Cut-Off Current	I_{CBO}		-1	μA	$V_{CB} = -175V$
Emitter Cut-Off Current	I_{EBO}		-20	μA	$V_{EB} = -4V$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		- 2.0 -0.5	V	$I_C = -50mA, I_B = -5mA^*$ $I_C = -30mA, I_B = -3mA^*$
Static Forward Current Transfer Ratio	h_{FE}	30	150		$I_C = -50mA, V_{CE} = -10V^*$
Transition Frequency	f_T	15		MHz	$I_C = -10mA, V_{CE} = -20V^*$ $f = 20MHz$
Output Capacitance	C_{obo}		15	pF	$V_{CB} = -10V, f = 1MHz$

*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$
For typical characteristics graphs see FMMTA92 datasheet.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.