

# SOT89 PNP SILICON PLANAR HIGH VOLTAGE TRANSISTOR

ISSUE 3 – FEBRUARY 1996




## BST16

### FEATURES

- \* High  $V_{CE0}$
- \* Low saturation voltage

COMPLEMENTARY TYPE – BST39

PARTMARKING DETAIL – BT2



### ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	$V_{CBO}$	-350	V
Collector-Emitter Voltage	$V_{CEO}$	-300	V
Emitter-Base Voltage	$V_{EBO}$	-4	V
Peak Pulse Current	$I_{CM}$	-1	A
Continuous Collector Current	$I_C$	-500	mA
Power Dissipation at $T_{amb}=25^{\circ}C$	$P_{tot}$	1	W
Operating and Storage Temperature Range	$T_j; T_{stg}$	-65 to +150	$^{\circ}C$

### ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-350			V	$I_C = -100\mu A$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-300			V	$I_C = -1mA$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-4			V	$I_E = -100\mu A$
Collector Cut-Off Current	$I_{CBO}$			-1	$\mu A$	$V_{CB} = -280V$
Collector Cut-Off Current	$I_{CEO}$			-50	$\mu A$	$V_{CB} = -250V$
Emitter Cut-Off Current	$I_{EBO}$			-20	$\mu A$	$V_{EB} = -4V$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$			- 2.0 -0.5	V	$I_C = -50mA, I_B = -5mA^*$ $I_C = -30mA, I_B = -3mA^*$
Static Forward Current Transfer Ratio	$h_{FE}$	30		150		$I_C = -50mA, V_{CE} = -10V^*$
Transition Frequency	$f_T$	15			MHz	$I_C = -10mA, V_{CE} = -10V^*$ $f = 30MHz$
Output Capacitance	$C_{obo}$			15	pF	$V_{CB} = -10V, f = 1MHz$

\*Measured under pulsed conditions. Pulse width=300 $\mu s$ . Duty cycle  $\leq 2\%$   
For typical characteristics graphs see FMMTA92 datasheet.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

**[LittleDiode.com](http://LittleDiode.com)**

Looking forward to providing you with the best possible service.