

# Thyristors logic level

## BT149 series

### GENERAL DESCRIPTION

Glass passivated, sensitive gate thyristors in a plastic envelope, intended for use in general purpose switching and phase control applications. These devices are intended to be interfaced directly to microcontrollers, logic integrated circuits and other low power gate trigger circuits.


### QUICK REFERENCE DATA

| SYMBOL                   | PARAMETER  | MAX.            | MAX.            | MAX.            | MAX.            | UNIT |
|--------------------------|--|-----------------|-----------------|-----------------|-----------------|------|
| $V_{DRM}$ ,<br>$V_{RRM}$ | <b>BT149</b><br>Repetitive peak off-state voltages | <b>B</b><br>200 | <b>D</b><br>400 | <b>E</b><br>500 | <b>G</b><br>600 | V    |
| $I_{T(AV)}$              | Average on-state current                           | 0.5             | 0.5             | 0.5             | 0.5             | A    |
| $I_{T(RMS)}$             | RMS on-state current                               | 0.8             | 0.8             | 0.8             | 0.8             | A    |
| $I_{TSM}$                | Non-repetitive peak on-state current               | 8               | 8               | 8               | 8               | A    |


### PINNING - TO92 variant

| PIN | DESCRIPTION |
|-----|-------------|
| 1   | cathode     |
| 2   | gate        |
| 3   | anode       |

### PIN CONFIGURATION



### SYMBOL



### LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

| SYMBOL                | PARAMETER  | CONDITIONS  | MIN. | MAX.             |                  |                  |                  | UNIT             |
|-----------------------|--|---|------|------------------|------------------|------------------|------------------|------------------|
|                       |  |   |      | B                | D                | E                | G                |                  |
| $V_{DRM}$ , $V_{RRM}$ | Repetitive peak off-state voltages                           |   | -    | 200 <sup>1</sup> | 400 <sup>1</sup> | 500 <sup>1</sup> | 600 <sup>1</sup> | V                |
| $I_{T(AV)}$           | Average on-state current                                     | half sine wave;<br>$T_{lead} \leq 83^\circ\text{C}$   | -    | 0.5              |                  |                  |                  | A                |
| $I_{T(RMS)}$          | RMS on-state current   | all conduction angles   | -    | 0.8              |                  |                  |                  | A                |
| $I_{TSM}$             | Non-repetitive peak on-state current                         | $t = 10\text{ ms}$  | -    | 8                |                  |                  |                  | A                |
|                       |  | $t = 8.3\text{ ms}$   | -    | 9                |                  |                  |                  | A                |
| $I^2t$                | $I^2t$ for fusing  | half sine wave;<br>$T_j = 25^\circ\text{C}$ prior to surge  | -    | 0.32             |                  |                  |                  | A <sup>2</sup> s |
| $dl_T/dt$             | Repetitive rate of rise of on-state current after triggering | $t = 10\text{ ms}$<br>$I_{TM} = 2\text{ A}$ ; $I_G = 10\text{ mA}$ ;<br>$dl_G/dt = 100\text{ mA}/\mu\text{s}$ | -    | 50               |                  |                  |                  | A/ $\mu\text{s}$ |
| $I_{GM}$              | Peak gate current  |   | -    | 1                |                  |                  |                  | A                |
| $V_{GM}$              | Peak gate voltage  |   | -    | 5                |                  |                  |                  | V                |
| $V_{RGM}$             | Peak reverse gate voltage                                    |   | -    | 5                |                  |                  |                  | V                |
| $P_{GM}$              | Peak gate power  |   | -    | 2                |                  |                  |                  | W                |
| $P_{G(AV)}$           | Average gate power   | over any 20 ms period   | -    | 0.1              |                  |                  |                  | W                |
| $T_{stg}$             | Storage temperature  |   | -40  | 150              |                  |                  |                  | $^\circ\text{C}$ |
| $T_j$                 | Operating junction temperature                               |   | -    | 125              |                  |                  |                  | $^\circ\text{C}$ |

<sup>1</sup> Although not recommended, off-state voltages up to 800V may be applied without damage, but the thyristor may switch to the on-state. The rate of rise of current should not exceed 15 A/ $\mu\text{s}$ .

Thyristors  
logic level

## BT149 series

**THERMAL RESISTANCES**

| SYMBOL           | PARAMETER                              | CONDITIONS                     | MIN. | TYP. | MAX. | UNIT |
|------------------|--|--------------------------------|------|------|------|------|
| $R_{th\ j-lead}$ | Thermal resistance junction to lead    |                                | -    | -    | 60   | K/W  |
| $R_{th\ j-a}$    | Thermal resistance junction to ambient | pcb mounted; lead length = 4mm | -    | 150  | -    | K/W  |

**STATIC CHARACTERISTICS** $T_j = 25\text{ °C}$  unless otherwise stated







| SYMBOL     | PARAMETER                 | CONDITIONS  | MIN. | TYP. | MAX. | UNIT          |
|------------|---------------------------|---|------|------|------|---------------|
| $I_{GT}$   | Gate trigger current      | $V_D = 12\text{ V}$ ; $I_T = 10\text{ mA}$ ; gate open circuit                                    | -    | 50   | 200  | $\mu\text{A}$ |
| $I_L$      | Latching current          | $V_D = 12\text{ V}$ ; $I_{GT} = 0.5\text{ mA}$ ; $R_{GK} = 1\text{ k}\Omega$                      | -    | 2    | 6    | mA            |
| $I_H$      | Holding current           | $V_D = 12\text{ V}$ ; $I_{GT} = 0.5\text{ mA}$ ; $R_{GK} = 1\text{ k}\Omega$                      | -    | 2    | 5    | mA            |
| $V_T$      | On-state voltage          | $I_T = 1\text{ A}$  | -    | 1.2  | 1.35 | V             |
| $V_{GT}$   | Gate trigger voltage      | $V_D = 12\text{ V}$ ; $I_T = 10\text{ mA}$ ; gate open circuit                                    | -    | 0.5  | 0.8  | V             |
|            |                           | $V_D = V_{DRM(max)}$ ; $I_T = 10\text{ mA}$ ; $T_j = 125\text{ °C}$ ; gate open circuit           | 0.2  | 0.3  | -    | V             |
| $I_D, I_R$ | Off-state leakage current | $V_D = V_{DRM(max)}$ ; $V_R = V_{RRM(max)}$ ; $T_j = 125\text{ °C}$ ; $R_{GK} = 1\text{ k}\Omega$ | -    | 0.05 | 0.1  | mA            |

**DYNAMIC CHARACTERISTICS** $T_j = 25\text{ °C}$  unless otherwise stated

| SYMBOL    | PARAMETER                                  | CONDITIONS  | MIN. | TYP. | MAX. | UNIT             |
|-----------|--|---|------|------|------|------------------|
| $dV_D/dt$ | Critical rate of rise of off-state voltage | $V_{DM} = 67\% V_{DRM(max)}$ ; $T_j = 125\text{ °C}$ ; exponential waveform; $R_{GK} = 1\text{ k}\Omega$  | -    | 25   | -    | V/ $\mu\text{s}$ |
| $t_{gt}$  | Gate controlled turn-on time               | $I_{TM} = 2\text{ A}$ ; $V_D = V_{DRM(max)}$ ; $I_G = 10\text{ mA}$ ; $dI_G/dt = 0.1\text{ A}/\mu\text{s}$  | -    | 2    | -    | $\mu\text{s}$    |
| $t_q$     | Circuit commutated turn-off time           | $V_D = 67\% V_{DRM(max)}$ ; $T_j = 125\text{ °C}$ ; $I_{TM} = 1.6\text{ A}$ ; $V_R = 35\text{ V}$ ; $dI_{TM}/dt = 30\text{ A}/\mu\text{s}$ ; $dV_D/dt = 2\text{ V}/\mu\text{s}$ ; $R_{GK} = 1\text{ k}\Omega$ | -    | 100  | -    | $\mu\text{s}$    |







Thyristors  
logic level

BT149 series




Thyristors  
logic level

BT149 series



**MECHANICAL DATA**



**Notes**

- 1. Epoxy meets UL94 V0 at 1/8".

## Thyristors logic level

BT149 series

### DEFINITIONS

|  |   |
|--|---|
| <b>Data sheet status</b>   |   |
| Objective specification  | This data sheet contains target or goal specifications for product development.       |
| Preliminary specification  | This data sheet contains preliminary data; supplementary data may be published later. |
| Product specification  | This data sheet contains final product specifications.                                |
| <b>Limiting values</b>   |   |
| Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability. |   |
| <b>Application information</b>   |   |
| Where application information is given, it is advisory and does not form part of the specification.  |   |
| © Philips Electronics N.V. 1997  |   |
| All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.  |   |
| The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.   |   |

### LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.