

# CD4009UB, CD4010B Types

## CMOS Hex Buffers/Converters

High-Voltage Types (20-Volt Rating)

Inverting Type: CD4009UB

Non-Inverting Type: CD4010B

■ CD4009UB and CD4010B Hex Buffer/Converters may be used as CMOS to TTL or DTL logic-level converters or CMOS high-sink-current drivers.

The CD4049UB and CD4050B are preferred hex buffer replacements for the CD4009UB and CD4010B, respectively, in all applications except multiplexers. For applications not requiring high sink current or voltage conversion, the CD4069UB Hex Inverter is recommended.


The CD4009UB and CD4010B types are supplied in 16-lead hermetic dual-in-line ceramic packages (F3A suffix), 16-lead dual-in-line plastic packages (E suffix), 16-lead small-outline packages (M, M96, MT, and NSR suffixes), and 16-lead thin shink small-outline packages (PW and PWR suffixes).

### Features:

- 100% tested for quiescent current at 20 V
- Maximum input current of 1  $\mu$ A at 18 V over full package-temperature range; 100 nA at 18 V and 25°C
- 5-V, 10-V, and 15-V parametric ratings

### Applications:

- CMOS to DTL/TTL hex converter
- CMOS current “sink” or “source” driver
- CMOS high-to-low logic-level converter
- Multiplexer — 1 to 6 or 6 to 1



### TERMINAL ASSIGNMENTS

### MAXIMUM RATINGS, Absolute-Maximum Values:

#### DC SUPPLY-VOLTAGE RANGE, (V<sub>DD</sub>)

Voltages referenced to V<sub>SS</sub> Terminal) ..... -0.5V to +20V

INPUT VOLTAGE RANGE, ALL INPUTS ..... -0.5V to V<sub>DD</sub> +0.5V

DC INPUT CURRENT, ANY ONE INPUT .....  $\pm$ 10mA

#### POWER DISSIPATION PER PACKAGE (P<sub>D</sub>):

For T<sub>A</sub> = -55°C to +100°C ..... 500mW

For T<sub>A</sub> = +100°C to +125°C ..... Derate Linearly at 12mW/°C to 200mW

#### DEVICE DISSIPATION PER OUTPUT TRANSISTOR

FOR T<sub>A</sub> = FULL PACKAGE-TEMPERATURE RANGE (All Package Types) ..... 100mW

OPERATING-TEMPERATURE RANGE (T<sub>A</sub>) ..... -55°C to +125°C

STORAGE TEMPERATURE RANGE (T<sub>stg</sub>) ..... -65°C to +150°C

#### LEAD TEMPERATURE (DURING SOLDERING):

At distance 1/16  $\pm$  1/32 inch (1.59  $\pm$  0.79mm) from case for 10s max ..... +265°C






Fig. 3 – Minimum and maximum voltage transfer characteristics—CD4009UB.




Fig. 1 – Schematic diagram of CD4009UB—1 of 6 identical stages.





Fig. 2 – Schematic diagram of CD4010B—1 of 6 identical stages.



# CD4009UB, CD4010B Types

## RECOMMENDED OPERATING CONDITIONS

For maximum reliability, nominal operating conditions should be selected so that operation is always within the following ranges:

| CHARACTERISTIC  | LIMITS     |          | UNITS |
|---|------------|----------|-------|
|   | MIN.       | MAX.     |       |
| Supply-Voltage Range (For $T_A$ = Full Package Temperature Range), $V_{DD}$ | 3          | 18       | V     |
| $V_{CC}^*$  | 3          | $V_{DD}$ |       |
| Input Voltage Range ( $V_I$ )   | $V_{CC}^*$ | $V_{DD}$ | V     |

\*The CD4009UB and CD4010B have high-to-low level voltage conversion capability but not low-to-high level, therefore it is recommended that  $V_{DD} \geq V_I \geq V_{CC}$ .

## STATIC ELECTRICAL CHARACTERISTICS

| CHARACTERISTIC                             | CONDITIONS   |                 |                 | LIMITS AT INDICATED TEMPERATURES (°C) |           |         |         |       |               |           | UNITS   |
|--|--------------|-----------------|-----------------|---------------------------------------|-----------|---------|---------|-------|---------------|-----------|---------|
|  | $V_O$<br>(V) | $V_{IN}$<br>(V) | $V_{DD}$<br>(V) | -55                                   | -40       | +85     | +125    | +25   |               |           |         |
|  |              |                 |                 |                                       |           |         |         | Min.  | Typ.          | Max.      |         |
| Quiescent Device Current, $I_{DD}$ Max.    | -            | 0.5             | 5               | 1                                     | 1         | 30      | 30      | -     | 0.02          | 1         | $\mu A$ |
|  | -            | 0.10            | 10              | 2                                     | 2         | 60      | 60      | -     | 0.02          | 2         |         |
|  | -            | 0.15            | 15              | 4                                     | 4         | 120     | 120     | -     | 0.02          | 4         |         |
|  | -            | 0.20            | 20              | 20                                    | 20        | 600     | 600     | -     | 0.04          | 20        |         |
| Output Low (Sink) Current $I_{OL}$ Min.    | 0.4          | 0.5             | 4.5             | 3.2                                   | 3.1       | 2.1     | 1.8     | 2.6   | 3.4           | -         | $mA$    |
|  | 0.4          | 0.5             | 5               | 3.75                                  | 3.6       | 2.4     | 2.1     | 3     | 4             | -         |         |
|  | 0.5          | 0.10            | 10              | 10                                    | 9.6       | 6.4     | 5.6     | 8     | 10            | -         |         |
| Output High (Source) Current $I_{OH}$ Min. | 4.6          | 0.5             | 5               | -0.25                                 | -0.23     | -0.18   | -0.15   | -0.2  | -0.4          | -         | $mA$    |
|  | 2.5          | 0.5             | 5               | -1                                    | -0.9      | -0.65   | -0.58   | -0.8  | -1.6          | -         |         |
|  | 9.5          | 0.10            | 10              | -0.55                                 | -0.5      | -0.38   | -0.33   | -0.45 | -0.9          | -         |         |
| Output Voltage: Low-Level, $V_{OL}$ Max.   | -            | 0.5             | 5               | 0.05                                  |           |         | -       | 0     | 0.05          | -         | V       |
|  | -            | 0.10            | 10              | 0.05                                  |           |         | -       | 0     | 0.05          | -         |         |
|  | -            | 0.15            | 15              | 0.05                                  |           |         | -       | 0     | 0.05          | -         |         |
| Output Voltage: High-Level, $V_{OH}$ Min.  | -            | 0.5             | 5               | 4.95                                  |           |         | -       | 4.95  | 5             | -         | V       |
|  | -            | 0.10            | 10              | 9.95                                  |           |         | -       | 9.95  | 10            | -         |         |
|  | -            | 0.15            | 15              | 14.95                                 |           |         | -       | 14.95 | 15            | -         |         |
| Input Low Voltage: $V_{IL}$ Max. CD4009UB  | 4.5          | -               | 5               | 1                                     |           |         | -       | -     | 1             | -         | V       |
|  | 9            | -               | 10              | 2                                     |           |         | -       | -     | 2             | -         |         |
|  | 13.5         | -               | 15              | 2.5                                   |           |         | -       | -     | 2.5           | -         |         |
| Input Low Voltage: $V_{IL}$ Max. CD4010B   | 0.5          | -               | 5               | 1.5                                   |           |         | -       | -     | 1.5           | -         | V       |
|  | 1            | -               | 10              | 3                                     |           |         | -       | -     | 3             | -         |         |
|  | 1.5          | -               | 15              | 4                                     |           |         | -       | -     | 4             | -         |         |
| Input High Voltage: $V_{IH}$ Min. CD4009UB | 0.5          | -               | 5               | 4                                     |           |         | -       | 4     | -             | -         | V       |
|  | 1            | -               | 10              | 8                                     |           |         | -       | 8     | -             | -         |         |
|  | 1.5          | -               | 15              | 12.5                                  |           |         | -       | 12.5  | -             | -         |         |
| Input High Voltage: $V_{IH}$ Min. CD4010B  | 4.5          | -               | 5               | 3.5                                   |           |         | -       | 3.5   | -             | -         | V       |
|  | 9            | -               | 10              | 7                                     |           |         | -       | 7     | -             | -         |         |
|  | 13.5         | -               | 15              | 11                                    |           |         | -       | 11    | -             | -         |         |
| Input Current, $I_{IN}$ Max.               | -            | 0.18            | 18              | $\pm 0.1$                             | $\pm 0.1$ | $\pm 1$ | $\pm 1$ | -     | $\pm 10^{-5}$ | $\pm 0.1$ | $\mu A$ |




Fig. 4 - Typical voltage transfer characteristics as function of temp.-CD4009UB.




Fig. 5 - Minimum and maximum voltage transfer characteristics ( $V_{DD}=5$ )-CD4010B.




Fig. 6 - Minimum and maximum voltage transfer characteristics ( $V_{DD}=10$ )-CD4010B.




Fig. 7 - Minimum and maximum voltage transfer characteristics ( $V_{DD}=15$ )-CD4010B.

3  
COMMERCIAL CMOS  
HIGH VOLTAGE ICs

# CD4009UB, CD4010B Types

**DYNAMIC ELECTRICAL CHARACTERISTICS** at  $T_A=25^\circ\text{C}$ ; Input  $t_r, t_f=20\text{ ns}$ ,  $C_L=50\text{ pF}$ ,  $R_L=200\text{ K}\Omega$

| CHARACTERISTIC  | CONDITIONS          |                    |                     | LIMITS ALL PKGS |      | UNIT |    |
|---|---------------------|--------------------|---------------------|-----------------|------|------|----|
|   | V <sub>DD</sub> (V) | V <sub>I</sub> (V) | V <sub>CC</sub> (V) | TYP.            | MAX. |      |    |
| Propagation Delay Time: Low-to-High, t <sub>PLH</sub> | CD4009UB            | 5                  | 5                   | 5               | 70   | 140  | ns |
|   |                     | 10                 | 10                  | 10              | 40   | 80   |    |
|   |                     | 10                 | 10                  | 5               | 35   | 70   |    |
|   |                     | 15                 | 15                  | 15              | 30   | 60   |    |
|   | CD4010B             | 5                  | 5                   | 5               | 100  | 200  | ns |
|   |                     | 10                 | 10                  | 10              | 50   | 100  |    |
|   |                     | 10                 | 10                  | 5               | 50   | 100  |    |
|   |                     | 15                 | 15                  | 15              | 35   | 70   |    |
| High-to-Low, t <sub>PHL</sub>                         | CD4009UB            | 5                  | 5                   | 5               | 30   | 60   | ns |
|   |                     | 10                 | 10                  | 10              | 20   | 40   |    |
|   |                     | 10                 | 10                  | 5               | 15   | 30   |    |
|   |                     | 15                 | 15                  | 15              | 15   | 30   |    |
|   | CD4010B             | 5                  | 5                   | 5               | 65   | 130  | ns |
|   |                     | 10                 | 10                  | 10              | 35   | 70   |    |
|   |                     | 10                 | 10                  | 5               | 30   | 70   |    |
|   |                     | 15                 | 15                  | 15              | 25   | 50   |    |
| CD4010B   | 15                  | 15                 | 5                   | 20              | 40   | ns   |    |
|   | 15                  | 15                 | 5                   | 20              | 40   |      |    |
|   | 15                  | 15                 | 5                   | 20              | 40   |      |    |
|   | 15                  | 15                 | 5                   | 20              | 40   |      |    |
| Transition Time: Low-to-High, t <sub>TLH</sub>        | CD4009UB            | 5                  | 5                   | 5               | 150  | 350  | ns |
|   |                     | 10                 | 10                  | 10              | 75   | 150  |    |
|   |                     | 15                 | 15                  | 15              | 55   | 110  |    |
|   | CD4010B             | 5                  | 5                   | 5               | 35   | 70   | ns |
| 10  |                     | 10                 | 10                  | 20              | 40   |      |    |
| 15  |                     | 15                 | 15                  | 15              | 30   |      |    |
| Input Capacitance, C <sub>IN</sub>                    | CD4009UB            | -                  | -                   | -               | 15   | 22.5 | pF |
|   | CD4010B             | -                  | -                   | -               | 5    | 7.5  |    |




Fig. 8 – Typical voltage transfer characteristics as a function of temperature—CD4010B.




Fig. 9 – Typical output low (sink) current characteristics.




Fig. 10 – Minimum output low (sink) current characteristics.




Fig. 11 – Typical output high (source) current characteristics.




Fig. 12 – Minimum output high (source) current characteristics.




Fig. 13 – Typical low-to-high propagation delay time vs. load capacitance (CD4009UB).

# CD4009UB, CD4010B Types




Fig. 14 - Typical high-to-low propagation delay time vs. load capacitance (CD4009UB).




Fig. 15 - Typical low-to-high propagation delay time vs. load capacitance (CD4010B).




Fig. 16 - Typical high-to-low propagation delay time vs. load capacitance (CD4010B).




Fig. 17 - Typical low-to-high transition time vs. load capacitance.




Fig. 18 - Typical high-to-low transition time vs. load capacitance.




Fig. 19 - Typical dissipation characteristics.




Fig. 20 - Quiescent device current test circuit.




Fig. 21 - Noise immunity test circuit.





Fig. 22 - Input current test circuit.



Dimensions in parentheses are in millimeters and are derived from the basic inch dimensions as indicated. Grid Graduations Are In Mils ( $10^{-3}$  Inch)

Photograph of chip for CD4009UB. Dimensions and pad layout for CD4010B are identical.

3  
COMMERCIAL CMOS  
HIGH VOLTAGE ICs

PACKAGING INFORMATION

| Orderable Device | Status <sup>(1)</sup> | Package Type | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/Ball Finish | MSL Peak Temp <sup>(3)</sup>               |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|--|
| 89264UKB3T       | OBSOLETE              | CFP          | WR              | 16   |             | None                    | Call TI          | Call TI                                    |
| CD4009UBE        | ACTIVE                | PDIP         | N               | 16   | 25          | Pb-Free (RoHS)          | CU NIPDAU        | Level-NC-NC-NC                             |
| CD4009UBF        | ACTIVE                | CDIP         | J               | 16   | 1           | None                    | Call TI          | Level-NC-NC-NC                             |
| CD4009UBF3A      | ACTIVE                | CDIP         | J               | 16   | 1           | None                    | Call TI          | Level-NC-NC-NC                             |
| CD4009UBM        | ACTIVE                | SOIC         | D               | 16   | 40          | Pb-Free (RoHS)          | CU NIPDAU        | Level-2-260C-1 YEAR/<br>Level-1-235C-UNLIM |
| CD4009UBM96      | ACTIVE                | SOIC         | D               | 16   | 2500        | Pb-Free (RoHS)          | CU NIPDAU        | Level-2-260C-1 YEAR/<br>Level-1-235C-UNLIM |
| CD4009UBMT       | ACTIVE                | SOIC         | D               | 16   | 250         | Pb-Free (RoHS)          | CU NIPDAU        | Level-2-260C-1 YEAR/<br>Level-1-235C-UNLIM |
| CD4009UBNSR      | ACTIVE                | SO           | NS              | 16   | 2000        | Pb-Free (RoHS)          | CU NIPDAU        | Level-2-260C-1 YEAR/<br>Level-1-235C-UNLIM |
| CD4009UBPW       | ACTIVE                | TSSOP        | PW              | 16   | 90          | Pb-Free (RoHS)          | CU NIPDAU        | Level-1-250C-UNLIM                         |
| CD4009UBPWR      | ACTIVE                | TSSOP        | PW              | 16   | 2000        | Pb-Free (RoHS)          | CU NIPDAU        | Level-1-250C-UNLIM                         |
| CD4010BE         | ACTIVE                | PDIP         | N               | 16   | 25          | Pb-Free (RoHS)          | CU NIPDAU        | Level-NC-NC-NC                             |
| CD4010BF         | ACTIVE                | CDIP         | J               | 16   | 1           | None                    | Call TI          | Level-NC-NC-NC                             |
| CD4010BF3A       | ACTIVE                | CDIP         | J               | 16   | 1           | None                    | Call TI          | Level-NC-NC-NC                             |
| CD4010BM         | ACTIVE                | SOIC         | D               | 16   | 40          | Pb-Free (RoHS)          | CU NIPDAU        | Level-2-260C-1 YEAR/<br>Level-1-235C-UNLIM |
| CD4010BM96       | ACTIVE                | SOIC         | D               | 16   | 2500        | Pb-Free (RoHS)          | CU NIPDAU        | Level-2-260C-1 YEAR/<br>Level-1-235C-UNLIM |
| CD4010BMT        | ACTIVE                | SOIC         | D               | 16   | 250         | Pb-Free (RoHS)          | CU NIPDAU        | Level-2-260C-1 YEAR/<br>Level-1-235C-UNLIM |
| CD4010BNSR       | ACTIVE                | SO           | NS              | 16   | 2000        | Pb-Free (RoHS)          | CU NIPDAU        | Level-2-260C-1 YEAR/<br>Level-1-235C-UNLIM |
| CD4010BPW        | ACTIVE                | TSSOP        | PW              | 16   | 90          | Pb-Free (RoHS)          | CU NIPDAU        | Level-1-250C-UNLIM                         |
| CD4010BPWR       | ACTIVE                | TSSOP        | PW              | 16   | 2000        | Pb-Free (RoHS)          | CU NIPDAU        | Level-1-250C-UNLIM                         |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - May not be currently available - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**None:** Not yet available Lead (Pb-Free).

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean "Pb-Free" and in addition, uses package materials that do not contain halogens, including bromine (Br) or antimony (Sb) above 0.1% of total product weight.

<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.


**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


J (R-GDIP-T\*\*)

14 LEADS SHOWN

CERAMIC DUAL IN-LINE PACKAGE



| DIM \ PINS ** | 14                     | 16                     | 18                     | 20                     |
|---------------|------------------------|------------------------|------------------------|------------------------|
| A             | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC |
| B MAX         | 0.785<br>(19,94)       | .840<br>(21,34)        | 0.960<br>(24,38)       | 1.060<br>(26,92)       |
| B MIN         | —                      | —                      | —                      | —                      |
| C MAX         | 0.300<br>(7,62)        | 0.300<br>(7,62)        | 0.310<br>(7,87)        | 0.300<br>(7,62)        |
| C MIN         | 0.245<br>(6,22)        | 0.245<br>(6,22)        | 0.220<br>(5,59)        | 0.245<br>(6,22)        |




4040083/F 03/03

- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package is hermetically sealed with a ceramic lid using glass frit.
  - Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
  - Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

N (R-PDIP-T\*\*)

PLASTIC DUAL-IN-LINE PACKAGE

16 PINS SHOWN




- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - D The 20 pin end lead shoulder width is a vendor option, either half or full width.

4040049/E 12/2002

D (R-PDSO-G16)

PLASTIC SMALL-OUTLINE PACKAGE




- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
  - D. Falls within JEDEC MS-012 variation AC.

# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN




- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

PW (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-153

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

| <b>Products</b>  |  | <b>Applications</b> |  |
|------------------|--|---------------------|--|
| Amplifiers       | <a href="http://amplifier.ti.com">amplifier.ti.com</a>             | Audio               | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                   |
| Data Converters  | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>     | Automotive          | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>         |
| DSP              | <a href="http://dsp.ti.com">dsp.ti.com</a>                         | Broadband           | <a href="http://www.ti.com/broadband">www.ti.com/broadband</a>           |
| Interface        | <a href="http://interface.ti.com">interface.ti.com</a>             | Digital Control     | <a href="http://www.ti.com/digitalcontrol">www.ti.com/digitalcontrol</a> |
| Logic            | <a href="http://logic.ti.com">logic.ti.com</a>                     | Military            | <a href="http://www.ti.com/military">www.ti.com/military</a>             |
| Power Mgmt       | <a href="http://power.ti.com">power.ti.com</a>                     | Optical Networking  | <a href="http://www.ti.com/opticalnetwork">www.ti.com/opticalnetwork</a> |
| Microcontrollers | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a> | Security            | <a href="http://www.ti.com/security">www.ti.com/security</a>             |
|                  |  | Telephony           | <a href="http://www.ti.com/telephony">www.ti.com/telephony</a>           |
|                  |  | Video & Imaging     | <a href="http://www.ti.com/video">www.ti.com/video</a>                   |
|                  |  | Wireless            | <a href="http://www.ti.com/wireless">www.ti.com/wireless</a>             |

Mailing Address: Texas Instruments  
Post Office Box 655303 Dallas, Texas 75265

# Texas Instruments

<http://www.ti.com>

This file is the datasheet for the following electronic components:

CD4009UBE - <http://www.ti.com/product/cd4009ube?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4009UBM - <http://www.ti.com/product/cd4009ubm?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4009UBPWR - <http://www.ti.com/product/cd4009ubpwr?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4009UB - <http://www.ti.com/product/cd4009ub?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4009UBPW - <http://www.ti.com/product/cd4009ubpw?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4009UBMT - <http://www.ti.com/product/cd4009ubmt?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4010BF3A - <http://www.ti.com/product/cd4010bf3a?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4009UBF - <http://www.ti.com/product/cd4009ubf?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4009UBM96 - <http://www.ti.com/product/cd4009ubm96?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4010BM - <http://www.ti.com/product/cd4010bm?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4010BM96 - <http://www.ti.com/product/cd4010bm96?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4010BMT - <http://www.ti.com/product/cd4010bmt?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4010BNSR - <http://www.ti.com/product/cd4010bnsr?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4009UBF3A - <http://www.ti.com/product/cd4009ubf3a?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4010BPW - <http://www.ti.com/product/cd4010bpw?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4009UBNSR - <http://www.ti.com/product/cd4009ubnsr?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4010BE - <http://www.ti.com/product/cd4010be?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4010BPWR - <http://www.ti.com/product/cd4010bpwr?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
89264UKB3T - <http://www.ti.com/product/89264ukb3t?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4010B - <http://www.ti.com/product/cd4010b?HQS=TI-null-null-dscatalog-df-pf-null-wwe>  
CD4010BF - <http://www.ti.com/product/cd4010bf?HQS=TI-null-null-dscatalog-df-pf-null-wwe>



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.