


# EGP50A THRU EGP50G

## GLASS PASSIVATED FAST EFFICIENT RECTIFIER

Reverse Voltage - 50 to 400 Volts    Forward Current - 5.0 Amperes

**PATENTED \***

### Case Style GP20



Dimensions in inches and (millimeters)

\* Glass-plastic encapsulation technique is covered by Patent No. 3,996,602, brazed-lead assembly by Patent No. 3,930,306

### FEATURES

- ◆ Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- ◆ Glass passivated cavity-free junction
- ◆ Superfast recovery time for high efficiency
- ◆ Low forward voltage, high current capability
- ◆ Low leakage current
- ◆ High surge current capability
- ◆ High temperature metallurgically bonded construction
- ◆ High temperature soldering guaranteed: 300°C/10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension

### MECHANICAL DATA

**Case:** Molded plastic over solid glass body  
**Terminals:** Axial leads, solderable per MIL-STD-750, Method 2026

**Polarity:** Color band denotes cathode end

**Mounting Position:** Any

**Weight:** 0.03 ounce, 0.8 gram

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.


	SYMBOLS	EGP 50A	EGP 50B	EGP 50C	EGP 50D	EGP 50F	EGP 50G	UNITS
Maximum recurrent peak reverse voltage	V <sub>RRM</sub>	50	100	150	200	300	400	Volts
Maximum RMS voltage	V <sub>RMS</sub>	35	70	105	140	210	280	Volts
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	150	200	300	400	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length at T <sub>L</sub> =55°C	I <sub>(AV)</sub>	5.0						Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I <sub>FSM</sub>	150.0						Amps
Maximum instantaneous forward voltage at 5.0A	V <sub>F</sub>	0.95				1.25		Volts
Maximum DC reverse current at rated DC blocking voltage	I <sub>R</sub>	5.0 50.0						μA
Maximum reverse recovery time (NOTE 1)	t <sub>rr</sub>	50.0						ns
Typical thermal resistance (NOTE 2)	R <sub>θJA</sub> R <sub>θJL</sub>	20.0 5.0						°C/W
Typical junction capacitance (NOTE 3)	C <sub>J</sub>	95				75		pF
Operating junction and storage temperature range	T <sub>J</sub> , T <sub>STG</sub>	-65 to +150						°C

### NOTES:


- (1) Reverse recovery test conditions: I<sub>F</sub>=0.5A, I<sub>R</sub>=1.0A, I<sub>rr</sub>=0.25A
- (2) Thermal resistance from junction to ambient and from junction of lead at 0.375" (9.5mm) lead length, both leads measured attached to heat sinks
- (3) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts

# RATINGS AND CHARACTERISTIC CURVES EGP50A THRU EGP50G


**FIG. 1 - MAXIMUM FORWARD CURRENT DERATING CURVE**




**FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT**




**FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**




**FIG. 4 - TYPICAL REVERSE LEAKAGE CHARACTERISTICS**



**FIG. 5 - TYPICAL JUNCTION CAPACITANCE**



**FIG. 6 - TYPICAL TRANSIENT THERMAL IMPEDANCE**





LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.