

TOSHIBA ZENER DIODE SILICON EPITAXIAL PLANAR TYPE


02CZ2.0~02CZ47

CONSTANT VOLTAGE REGULATION APPLICATIONS.

REFERENCE VOLTAGE APPLICATIONS.

- Small Package : SC-59
- Nominal Voltage Tolerance About $\pm 2.5\%$ (4.3V~24V)

Unit in mm




MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$)


| CHARACTERISTIC | SYMBOL | RATING | UNIT |
|---------------------------|-----------|---------|------------------|
| Power Dissipation | P | 200 | mW |
| Junction Temperature | T_j | 150 | $^\circ\text{C}$ |
| Storage Temperature Range | T_{stg} | -55~150 | $^\circ\text{C}$ |

Weight : 0.012g

MARKING



(02CZ15-X)



(02CZ2.4-Z)

961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

| TYPE No. | ZENER VOLTAGE | | | DYNAMIC IMPEDANCE | | KNEE DYNAMIC IMPEDANCE | | REVERSE CURRENT | |
|--------------|------------------------|-------|---------------------|--------------------|---------------------|------------------------|---------------------|---------------------|--------------------|
| | (*) V _Z (V) | | I _Z (mA) | Z _Z (Ω) | I _Z (mA) | Z _{ZK} (Ω) | I _Z (mA) | I _R (μA) | V _R (V) |
| | MIN. | MAX. | | MAX. | | MAX. | | MAX. | |
| 02CZ2.0 (**) | 1.85 | 2.15 | 5 | 100 | 5 | 1000 | 0.5 | 120 | 1.0 |
| 02CZ2.2 (**) | 2.05 | 2.38 | 5 | 100 | 5 | 1000 | 0.5 | 120 | 1.0 |
| 02CZ2.4 | 2.28 | 2.60 | 5 | 100 | 5 | 1000 | 0.5 | 120 | 1.0 |
| 02CZ2.7 | 2.50 | 2.90 | 5 | 110 | 5 | 1000 | 0.5 | 120 | 1.0 |
| 02CZ3.0 | 2.80 | 3.20 | 5 | 120 | 5 | 1000 | 0.5 | 50 | 1.0 |
| 02CZ3.3 | 3.10 | 3.50 | 5 | 130 | 5 | 1000 | 0.5 | 20 | 1.0 |
| 02CZ3.6 | 3.40 | 3.80 | 5 | 130 | 5 | 1000 | 0.5 | 10 | 1.0 |
| 02CZ3.9 | 3.70 | 4.10 | 5 | 130 | 5 | 1000 | 0.5 | 10 | 1.0 |
| 02CZ4.3 | 4.00 | 4.50 | 5 | 130 | 5 | 1000 | 0.5 | 5 | 1.0 |
| 02CZ4.7 | 4.40 | 4.90 | 5 | 120 | 5 | 1000 | 0.5 | 5 | 1.0 |
| 02CZ5.1 | 4.80 | 5.40 | 5 | 70 | 5 | 1000 | 0.5 | 1 | 1.5 |
| 02CZ5.6 | 5.30 | 6.00 | 5 | 40 | 5 | 900 | 0.5 | 1 | 2.5 |
| 02CZ6.2 | 5.80 | 6.60 | 5 | 30 | 5 | 500 | 0.5 | 1 | 3.0 |
| 02CZ6.8 | 6.40 | 7.20 | 5 | 25 | 5 | 150 | 0.5 | 0.5 | 5.0 |
| 02CZ7.5 | 7.00 | 7.90 | 5 | 23 | 5 | 120 | 0.5 | 0.5 | 6.0 |
| 02CZ8.2 | 7.70 | 8.70 | 5 | 20 | 5 | 120 | 0.5 | 0.5 | 6.5 |
| 02CZ9.1 | 8.50 | 9.60 | 5 | 18 | 5 | 120 | 0.5 | 0.5 | 7.0 |
| 02CZ10 | 9.40 | 10.60 | 5 | 15 | 5 | 120 | 0.5 | 0.5 | 8.0 |
| 02CZ11 | 10.40 | 11.60 | 5 | 15 | 5 | 120 | 0.5 | 0.5 | 8.5 |
| 02CZ12 | 11.40 | 12.60 | 5 | 15 | 5 | 110 | 0.5 | 0.5 | 9.0 |
| 02CZ13 | 12.40 | 14.10 | 5 | 15 | 5 | 110 | 0.5 | 0.5 | 10 |
| 02CZ15 | 13.80 | 15.60 | 5 | 15 | 5 | 110 | 0.5 | 0.5 | 11 |
| 02CZ16 | 15.30 | 17.10 | 5 | 18 | 5 | 150 | 0.5 | 0.5 | 12 |
| 02CZ18 | 16.80 | 19.10 | 5 | 20 | 5 | 150 | 0.5 | 0.5 | 14 |
| 02CZ20 | 18.80 | 21.20 | 5 | 25 | 5 | 200 | 0.5 | 0.5 | 15 |
| 02CZ22 | 20.80 | 23.30 | 5 | 30 | 5 | 200 | 0.5 | 0.5 | 17 |
| 02CZ24 | 22.80 | 25.60 | 5 | 40 | 5 | 200 | 0.5 | 0.5 | 19 |
| 02CZ27 | 25.10 | 28.90 | 2 | 70 | 2 | 250 | 0.5 | 0.5 | 21 |
| 02CZ30 | 28.00 | 32.00 | 2 | 80 | 2 | 250 | 0.5 | 0.5 | 23 |
| 02CZ33 | 31.00 | 35.00 | 2 | 80 | 2 | 250 | 0.5 | 0.5 | 25 |
| 02CZ36 | 34.00 | 38.00 | 2 | 90 | 2 | 250 | 0.5 | 0.5 | 27 |
| 02CZ39 | 37.00 | 41.00 | 2 | 100 | 2 | 250 | 0.5 | 0.5 | 30 |
| 02CZ43 | 40.00 | 45.00 | 2 | 130 | 2 | — | — | 0.5 | 33 |
| 02CZ47 | 44.00 | 49.00 | 2 | 150 | 2 | — | — | 0.5 | 36 |

(*) Test time : t=30ms (**) Product by order

ZENER VOLTAGE CLASSIFICATION







| TYPE No. | | ZENER VOLTAGE V_Z (V) $t=30\text{ms}$ | | | | | |
|-----------|---|---|------|------------------|------|------------------|------|
| | | REFERENCE | | | | | |
| | | $I_Z=0.5\text{mA}$ | | $I_Z=1\text{mA}$ | | $I_Z=5\text{mA}$ | |
| | | MIN. | MAX. | MIN. | MAX. | MIN. | MAX. |
| 02CZ2.0-X | X | 1.28 | 1.46 | 1.40 | 1.62 | 1.85 | 2.05 |
| 02CZ2.0-Z | Z | 1.38 | 1.52 | 1.52 | 1.69 | 1.95 | 2.15 |
| 02CZ2.2-X | X | 1.45 | 1.60 | 1.59 | 1.78 | 2.05 | 2.26 |
| 02CZ2.2-Z | Z | 1.52 | 1.67 | 1.68 | 1.92 | 2.16 | 2.38 |
| 02CZ2.4-X | X | 1.64 | 1.81 | 1.82 | 2.03 | 2.28 | 2.50 |
| 02CZ2.4-Z | Z | 1.72 | 1.89 | 1.87 | 2.10 | 2.40 | 2.60 |
| 02CZ2.7-X | X | 1.81 | 2.00 | 2.00 | 2.21 | 2.50 | 2.75 |
| 02CZ2.7-Z | Z | 1.92 | 2.12 | 2.11 | 2.33 | 2.65 | 2.90 |
| 02CZ3.0-X | X | 2.04 | 2.23 | 2.23 | 2.46 | 2.80 | 3.05 |
| 02CZ3.0-Z | Z | 2.16 | 2.35 | 2.36 | 2.58 | 2.95 | 3.20 |
| 02CZ3.3-X | X | 2.27 | 2.47 | 2.48 | 2.73 | 3.10 | 3.35 |
| 02CZ3.3-Z | Z | 2.39 | 2.60 | 2.63 | 2.86 | 3.25 | 3.50 |
| 02CZ3.6-X | X | 2.51 | 2.74 | 2.76 | 3.00 | 3.40 | 3.65 |
| 02CZ3.6-Z | Z | 2.65 | 2.89 | 2.90 | 3.16 | 3.55 | 3.80 |
| 02CZ3.9-X | X | 2.79 | 3.06 | 3.06 | 3.33 | 3.70 | 3.97 |
| 02CZ3.9-Z | Z | 2.95 | 3.20 | 3.23 | 3.46 | 3.87 | 4.10 |
| 02CZ4.3-X | X | 3.06 | 3.35 | 3.36 | 3.63 | 4.00 | 4.23 |
| 02CZ4.3-Y | Y | 3.23 | 3.46 | 3.53 | 3.75 | 4.13 | 4.35 |
| 02CZ4.3-Z | Z | 3.35 | 3.72 | 3.65 | 3.93 | 4.25 | 4.50 |
| 02CZ4.7-X | X | 3.56 | 3.92 | 3.83 | 4.10 | 4.40 | 4.63 |
| 02CZ4.7-Y | Y | 3.74 | 4.05 | 4.00 | 4.25 | 4.53 | 4.76 |
| 02CZ4.7-Z | Z | 3.90 | 4.22 | 4.15 | 4.44 | 4.66 | 4.90 |
| 02CZ5.1-X | X | 4.08 | 4.48 | 4.34 | 4.66 | 4.80 | 5.07 |
| 02CZ5.1-Y | Y | 4.32 | 4.73 | 4.56 | 4.90 | 4.97 | 5.24 |
| 02CZ5.1-Z | Z | 4.56 | 4.96 | 4.80 | 5.12 | 5.14 | 5.40 |
| 02CZ5.6-X | X | 4.80 | 5.36 | 5.02 | 5.43 | 5.30 | 5.63 |
| 02CZ5.6-Y | Y | 5.00 | 5.63 | 5.23 | 5.65 | 5.43 | 5.81 |
| 02CZ5.6-Z | Z | 5.30 | 5.90 | 5.45 | 5.90 | 5.61 | 6.00 |






ZENER VOLTAGE CLASSIFICATION

| TYPE No. | | ZENER VOLTAGE V_Z (V) $t=30\text{ms}$ | | | | | |
|-----------|---|---|-------|------------------|-------|------------------|-------|
| | | REFERENCE | | | | | |
| | | $I_Z=0.5\text{mA}$ | | $I_Z=1\text{mA}$ | | $I_Z=5\text{mA}$ | |
| | | MIN. | MAX. | MIN. | MAX. | MIN. | MAX. |
| 02CZ6.2-X | X | 5.60 | 6.12 | 5.70 | 6.13 | 5.80 | 6.20 |
| 02CZ6.2-Y | Y | 5.89 | 6.34 | 5.93 | 6.35 | 6.00 | 6.39 |
| 02CZ6.2-Z | Z | 6.12 | 6.57 | 6.15 | 6.58 | 6.19 | 6.60 |
| 02CZ6.8-X | X | 6.35 | 6.80 | 6.38 | 6.80 | 6.40 | 6.80 |
| 02CZ6.8-Y | Y | 6.59 | 7.02 | 6.60 | 7.02 | 6.60 | 7.02 |
| 02CZ6.8-Z | Z | 6.81 | 7.20 | 6.82 | 7.20 | 6.82 | 7.20 |
| 02CZ7.5-X | X | 6.96 | 7.43 | 6.97 | 7.43 | 7.00 | 7.43 |
| 02CZ7.5-Y | Y | 7.19 | 7.66 | 7.20 | 7.66 | 7.23 | 7.66 |
| 02CZ7.5-Z | Z | 7.42 | 7.90 | 7.43 | 7.90 | 7.46 | 7.90 |
| 02CZ8.2-X | X | 7.66 | 8.16 | 7.67 | 8.16 | 7.70 | 8.16 |
| 02CZ8.2-Y | Y | 7.92 | 8.43 | 7.93 | 8.43 | 7.96 | 8.43 |
| 02CZ8.2-Z | Z | 8.19 | 8.70 | 8.20 | 8.70 | 8.23 | 8.70 |
| 02CZ9.1-X | X | 8.46 | 9.00 | 8.47 | 9.00 | 8.50 | 9.00 |
| 02CZ9.1-Y | Y | 8.76 | 9.30 | 8.77 | 9.30 | 8.80 | 9.30 |
| 02CZ9.1-Z | Z | 9.06 | 9.60 | 9.07 | 9.60 | 9.10 | 9.60 |
| 02CZ10-X | X | 9.36 | 9.93 | 9.37 | 9.93 | 9.40 | 9.93 |
| 02CZ10-Y | Y | 9.69 | 10.26 | 9.70 | 10.26 | 9.73 | 10.26 |
| 02CZ10-Z | Z | 10.02 | 10.60 | 10.03 | 10.60 | 10.06 | 10.60 |
| 02CZ11-X | X | 10.34 | 10.95 | 10.36 | 10.96 | 10.40 | 10.98 |
| 02CZ11-Y | Y | 10.67 | 11.23 | 10.69 | 11.24 | 10.73 | 11.26 |
| 02CZ11-Z | Z | 11.00 | 11.57 | 11.02 | 11.58 | 11.06 | 11.60 |
| 02CZ12-X | X | 11.34 | 11.90 | 11.36 | 11.91 | 11.40 | 11.93 |
| 02CZ12-Y | Y | 11.67 | 12.23 | 11.69 | 12.24 | 11.73 | 12.26 |
| 02CZ12-Z | Z | 12.00 | 12.57 | 12.02 | 12.58 | 12.06 | 12.60 |
| 02CZ13-X | X | 12.34 | 13.05 | 12.36 | 13.06 | 12.40 | 13.08 |
| 02CZ13-Y | Y | 12.82 | 13.54 | 12.84 | 13.55 | 12.88 | 13.57 |
| 02CZ13-Z | Z | 13.31 | 14.07 | 13.33 | 14.08 | 13.37 | 14.10 |

ZENER VOLTAGE CLASSIFICATION

| TYPE No. | | ZENER VOLTAGE V_Z (V) $t=30\text{ms}$ | | | | | |
|----------|---|---|-------|------------------|-------|------------------|-------|
| | | REFERENCE | | | | | |
| | | $I_Z=0.5\text{mA}$ | | $I_Z=1\text{mA}$ | | $I_Z=5\text{mA}$ | |
| | | MIN. | MAX. | MIN. | MAX. | MIN. | MAX. |
| 02CZ15-X | X | 13.74 | 14.60 | 13.76 | 14.61 | 13.80 | 14.63 |
| 02CZ15-Y | Y | 14.27 | 15.08 | 14.29 | 15.09 | 14.33 | 15.11 |
| 02CZ15-Z | Z | 14.75 | 15.54 | 14.77 | 15.56 | 14.81 | 15.60 |
| 02CZ16-X | X | 15.15 | 16.04 | 15.18 | 16.06 | 15.30 | 16.10 |
| 02CZ16-Y | Y | 15.65 | 16.54 | 15.68 | 16.56 | 15.80 | 16.60 |
| 02CZ16-Z | Z | 16.15 | 17.04 | 16.18 | 17.06 | 16.30 | 17.10 |
| 02CZ18-X | X | 16.65 | 17.70 | 16.68 | 17.72 | 16.80 | 17.76 |
| 02CZ18-Y | Y | 17.31 | 18.37 | 17.34 | 18.39 | 17.46 | 18.43 |
| 02CZ18-Z | Z | 17.98 | 19.04 | 18.01 | 19.06 | 18.13 | 19.10 |
| 02CZ20-X | X | 18.65 | 19.72 | 18.68 | 19.74 | 18.80 | 19.78 |
| 02CZ20-Y | Y | 19.33 | 20.40 | 19.36 | 20.42 | 19.48 | 20.46 |
| 02CZ20-Z | Z | 19.97 | 21.14 | 20.01 | 21.16 | 20.16 | 21.20 |
| 02CZ22-X | X | 20.61 | 21.82 | 20.65 | 21.84 | 20.80 | 21.88 |
| 02CZ22-Y | Y | 21.29 | 22.50 | 21.33 | 22.52 | 21.48 | 22.56 |
| 02CZ22-Z | Z | 21.97 | 23.24 | 22.01 | 23.26 | 22.16 | 23.30 |
| 02CZ24-X | X | 22.61 | 24.05 | 22.65 | 24.07 | 22.80 | 24.11 |
| 02CZ24-Y | Y | 23.42 | 24.86 | 23.46 | 24.88 | 23.61 | 24.92 |
| 02CZ24-Z | Z | 24.23 | 25.54 | 24.27 | 25.56 | 24.42 | 25.60 |





This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.