




CET3055L

March 1998

N-Channel Enhancement Mode Field Effect Transistor

FEATURES

- 60V , 3.7A , $R_{DS(ON)}=100m\Omega$ @ $V_{GS}=10V$.
 $R_{DS(ON)}=120m\Omega$ @ $V_{GS}=4.5V$.
- High dense cell design for low $R_{DS(ON)}$.
- Rugged and reliable.
- SOT-223 Package.



SOT-223



SOT-223 (J23Z)

8

ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous ^a @ $T_J=125^\circ\text{C}$ -Pulsed ^b	I_D	± 3.7	A
	I_{DM}	± 25	A
Drain-Source Diode Forward Current ^a	I_S	2.5	A
Maximum Power Dissipation ^a	PD	3	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-65 to 150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Ambient ^a	$R_{\theta JA}$	42	$^\circ\text{C/W}$
--	-----------------	----	--------------------

CET3055L

ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BVDSS	VGS=0V, ID=250μA	60			V
Zero Gate Voltage Drain Current	IDSS	VDS=60V, VGS=0V			1	μA
Gate-Body Leakage	IGSS	VGS=±20V, VDS=0V			±100	nA
ON CHARACTERISTICS^b						
Gate Threshold Voltage	VGS(th)	VDS=VGS, ID=250μA	1	1.4	2	V
Drain-Source On-State Resistance	RDS(ON)	VGS=10V, ID=3.9A		63	100	mΩ
		VGS=4.5V, ID=3.7A		79	120	mΩ
On-State Drain Current	ID(ON)	VDS=10V, VGS=5V	10			A
Forward Transconductance	gFS	VDS=5V, ID=3.7A	3	6		S
DYNAMIC CHARACTERISTICS^c						
Input Capacitance	Ciss	VDS=25V, VGS=0V f=1.0MHz		428	560	pF
Output Capacitance	Coss			128	170	pF
Reverse Transfer Capacitance	Crss			29	40	pF
SWITCHING CHARACTERISTICS^c						
Turn-On Delay Time	tD(ON)	VDD=25V, ID=1A, VGS=10V, RGEN=6Ω		8	20	ns
Rise Time	tr			4	20	ns
Turn-Off Delay Time	tD(OFF)			23	50	ns
Fall Time	tf			6	20	ns
Total Gate Charge	Qg	VDS=40V, ID=3.7A, VGS=10V		14	17	nC
Gate-Source Charge	Qgs			2		nC
Gate-Drain Charge	Qgd			4		nC

8

CET3055L

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS^b						
Diode Forward Voltage	V_{SD}	$V_{GS} = 0V, I_s = 1.5A$		0.8	1.2	V

Notes

- a. Surface Mounted on FR4 Board, $t \leq 10\text{sec}$.
- b. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.
- c. Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Drain Current and Temperature

CET3055L




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature

8




Figure 7. Transconductance Variation with Drain Current




Figure 8. Body Diode Forward Voltage Variation with Source Current




Figure 9. Gate Charge




Figure 10. Maximum Safe Operating Area

CET3055L




Figure 11. Switching Test Circuit




Figure 12. Switching Waveforms

8




Figure 13. Normalized Thermal Transient Impedance Curve



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.