

# 2PB1424

20 V, 3 A PNP low  $V_{CEsat}$  (BISS) transistor

Rev. 02 — 15 January 2007

Product data sheet

## 1. Product profile

### 1.1 General description

PNP low  $V_{CEsat}$  Breakthrough In Small Signal (BISS) transistor in a medium power SOT89 (SC-62/TO-243) flat lead Surface-Mounted Device (SMD) plastic package.

NPN complement: 2PD2150.

### 1.2 Features

- Low collector-emitter saturation voltage  $V_{CEsat}$
- High collector current capability  $I_C$  and  $I_{CM}$
- High collector current gain ( $h_{FE}$ ) at high  $I_C$
- High efficiency due to less heat generation
- Smaller required Printed-Circuit Board (PCB) area than for conventional transistors

### 1.3 Applications

- DC-to-DC conversion
- MOSFET gate driving
- Motor control
- Charging circuits
- Power switches (e.g. motors, fans)
- Thin Film Transistor (TFT) backlight inverter

### 1.4 Quick reference data



Table 1. Quick reference data

| Symbol      | Parameter                            | Conditions                       | Min | Typ | Max  | Unit |   |
|-------------|--------------------------------------|----------------------------------|-----|-----|------|------|---|
| $V_{CEO}$   | collector-emitter voltage            | open base                        | -   | -   | -20  | V    |   |
| $I_C$       | collector current                    |                                  | -   | -   | -3   | A    |   |
| $I_{CM}$    | peak collector current               | single pulse;<br>$t_p \leq 1$ ms | -   | -   | -5   | A    |   |
| $V_{CEsat}$ | collector-emitter saturation voltage | $I_C = -2$ A;<br>$I_B = -0.1$ A  | [1] | -   | -0.2 | -0.5 | V |

[1] Pulse test:  $t_p \leq 300$   $\mu$ s;  $\delta \leq 0.02$ .

## 2. Pinning information

Table 2. Pinning

| Pin | Description | Simplified outline  | Symbol  |
|-----|-------------|---|---|
| 1   | emitter     |  |  |
| 2   | collector   |   |   |
| 3   | base        |   |   |

006aaa231

## 3. Ordering information

Table 3. Ordering information

| Type number | Package |  |         |
|-------------|---------|--|---------|
|             | Name    | Description  | Version |
| 2PB1424     | SC-62   | plastic surface-mounted package; collector pad for good heat transfer; 3 leads | SOT89   |

## 4. Marking

Table 4. Marking codes

| Type number | Marking code |
|-------------|--------------|
| 2PB1424     | M1           |

## 5. Limiting values


Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol    | Parameter                 | Conditions                       | Min | Max  | Unit |   |
|-----------|---------------------------|----------------------------------|-----|------|------|---|
| $V_{CBO}$ | collector-base voltage    | open emitter                     | -   | -20  | V    |   |
| $V_{CEO}$ | collector-emitter voltage | open base                        | -   | -20  | V    |   |
| $V_{EBO}$ | emitter-base voltage      | open collector                   | -   | -6   | V    |   |
| $I_C$     | collector current         |                                  | -   | -3   | A    |   |
| $I_{CM}$  | peak collector current    | single pulse;<br>$t_p \leq 1$ ms | -   | -5   | A    |   |
| $P_{tot}$ | total power dissipation   | $T_{amb} \leq 25$ °C             | [1] | -    | 0.5  | W |
|           |                           |                                  | [2] | -    | 2    | W |
| $T_j$     | junction temperature      |                                  | -   | 150  | °C   |   |
| $T_{amb}$ | ambient temperature       |                                  | -65 | +150 | °C   |   |
| $T_{stg}$ | storage temperature       |                                  | -65 | +150 | °C   |   |

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Device mounted on a ceramic PCB,  $Al_2O_3$ , standard footprint.




## 6. Thermal characteristics

**Table 6. Thermal characteristics**

| Symbol               | Parameter                                   | Conditions  | Min | Typ | Max | Unit |
|----------------------|---|-------------|-----|-----|-----|------|
| R <sub>th(j-a)</sub> | thermal resistance from junction to ambient | in free air | [1] | -   | 250 | K/W  |
|                      |   |             | [2] | -   | 62  | K/W  |


[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Device mounted on a ceramic PCB, Al<sub>2</sub>O<sub>3</sub>, standard footprint.



FR4 PCB, standard footprint

Fig 2. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values



Ceramic PCB,  $Al_2O_3$ , standard footprint

Fig 3. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values


## 7. Characteristics

**Table 7. Characteristics**

$T_{amb} = 25\text{ }^{\circ}\text{C}$  unless otherwise specified.


| Symbol      | Parameter                            | Conditions   | Min | Typ | Max  | Unit          |   |
|-------------|--------------------------------------|--|-----|-----|------|---------------|---|
| $I_{CBO}$   | collector-base cut-off current       | $V_{CB} = -20\text{ V}$ ; $I_E = 0\text{ A}$                               | -   | -   | -0.1 | $\mu\text{A}$ |   |
| $I_{EBO}$   | emitter-base cut-off current         | $V_{EB} = -5\text{ V}$ ; $I_C = 0\text{ A}$                                | -   | -   | -0.1 | $\mu\text{A}$ |   |
| $h_{FE}$    | DC current gain                      | $V_{CE} = -2\text{ V}$ ; $I_C = -0.1\text{ A}$                             | 180 | -   | 390  |               |   |
| $V_{CEsat}$ | collector-emitter saturation voltage | $I_C = -2\text{ A}$ ; $I_B = -0.1\text{ A}$                                | [1] | -   | -0.2 | -0.5          | V |
| $f_T$       | transition frequency                 | $V_{CE} = -2\text{ V}$ ; $I_E = 0.5\text{ A}$ ;<br>$f = 100\text{ MHz}$    | -   | 125 | -    | MHz           |   |
| $C_{ib}$    | common-base input capacitance        | $V_{EB} = -5\text{ V}$ ; $I_E = i_e = 0\text{ A}$ ;<br>$f = 1\text{ MHz}$  | -   | 130 | -    | pF            |   |
| $C_{ob}$    | common-base output capacitance       | $V_{CB} = -10\text{ V}$ ; $I_E = i_e = 0\text{ A}$ ;<br>$f = 1\text{ MHz}$ | -   | 37  | -    | pF            |   |

[1] Pulse test:  $t_p \leq 300\text{ }\mu\text{s}$ ;  $\delta \leq 0.02$ .




$V_{CE} = -2\text{ V}$   
 (1)  $T_{amb} = 100\text{ °C}$   
 (2)  $T_{amb} = 25\text{ °C}$   
 (3)  $T_{amb} = -40\text{ °C}$

**Fig 4. Collector current as a function of base-emitter voltage; typical values**




$T_{amb} = 25\text{ °C}$

**Fig 5. Collector current as a function of collector-emitter voltage; typical values**




$T_{amb} = 25\text{ °C}$

**Fig 6. Collector current as a function of collector-emitter voltage; typical values**



$V_{CE} = -2\text{ V}$   
 (1)  $T_{amb} = 100\text{ °C}$   
 (2)  $T_{amb} = 25\text{ °C}$   
 (3)  $T_{amb} = -40\text{ °C}$


**Fig 7. DC current gain as a function of collector current; typical values**



$I_C/I_B = 10$

- (1)  $T_{amb} = 100\text{ °C}$
- (2)  $T_{amb} = 25\text{ °C}$
- (3)  $T_{amb} = -40\text{ °C}$


**Fig 8. Collector-emitter saturation voltage as a function of collector current; typical values**



$I_C/I_B = 20$

- (1)  $T_{amb} = 100\text{ °C}$
- (2)  $T_{amb} = 25\text{ °C}$
- (3)  $T_{amb} = -40\text{ °C}$


**Fig 9. Collector-emitter saturation voltage as a function of collector current; typical values**



$I_C/I_B = 50$


- (1)  $T_{amb} = 100\text{ °C}$
- (2)  $T_{amb} = 25\text{ °C}$
- (3)  $T_{amb} = -40\text{ °C}$

**Fig 10. Collector-emitter saturation voltage as a function of collector current; typical values**




$T_{amb} = 25\text{ °C}; V_{CE} = -2\text{ V}$

**Fig 11. Transition frequency as a function of emitter current; typical values**



$T_{amb} = 25\text{ }^{\circ}\text{C}$ ;  $f = 1\text{ MHz}$ ;  $I_E = I_e = 0\text{ A}$

**Fig 12. Common-base input capacitance as a function of emitter-base voltage; typical values**



$T_{amb} = 25\text{ }^{\circ}\text{C}$ ;  $f = 1\text{ MHz}$ ;  $I_E = I_e = 0\text{ A}$

**Fig 13. Common-base output capacitance as a function of collector-base voltage; typical values**

## 8. Package outline




Fig 14. Package outline SOT89 (SC-62/TO-243)

## 9. Packing information


**Table 8. Packing methods**

The indicated -xxx are the last three digits of the 12NC ordering code.<sup>[1]</sup>

| Type number | Package | Description                     | Packing quantity |      |
|-------------|---------|---------------------------------|------------------|------|
|             |         |                                 | 1000             | 4000 |
| 2PB1424     | SOT89   | 8 mm pitch, 12 mm tape and reel | -115             | -135 |


[1] For further information and the availability of packing methods, see [Section 13](#).

10. Soldering



SOT89 standard mounting conditions for reflow soldering

Fig 15. Reflow soldering footprint SOT89 (SC-62/TO-243)



Not recommended for wave soldering

Fig 16. Wave soldering footprint SOT89 (SC-62/TO-243)

## 11. Revision history

**Table 9. Revision history**

| Document ID    | Release date  | Data sheet status  | Change notice | Supersedes |
|----------------|---|--------------------|---------------|------------|
| 2PB1424_2      | 20070115  | Product data sheet | -             | 2PB1424_1  |
| Modifications: | <ul style="list-style-type: none"> <li>• The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors.</li> <li>• Legal texts have been adapted to the new company name where appropriate.</li> <li>• <a href="#">Table 1 “Quick reference data”</a>: <math>I_C</math> collector current added</li> <li>• <a href="#">Table 1 “Quick reference data”</a>: <math>I_{CM}</math> peak collector current maximum value adapted</li> <li>• <a href="#">Table 1 “Quick reference data”</a>: <math>V_{CEsat}</math> collector-emitter saturation voltage added</li> <li>• <a href="#">Table 5 “Limiting values”</a>: <math>V_{CBO}</math> collector-base voltage maximum value adapted</li> <li>• <a href="#">Table 5 “Limiting values”</a>: <math>V_{EBO}</math> emitter-base voltage maximum value adapted</li> <li>• <a href="#">Table 5 “Limiting values”</a>: <math>I_C</math> collector current maximum value adapted</li> <li>• <a href="#">Table 5 “Limiting values”</a>: <math>I_{CM}</math> peak collector current maximum value adapted</li> <li>• <a href="#">Table 5 “Limiting values”</a>: <math>P_{tot}</math> total power dissipation for ceramic PCB condition added</li> <li>• <a href="#">Figure 1 “Power derating curves”</a>: adapted</li> <li>• <a href="#">Table 6 “Thermal characteristics”</a>: adapted</li> <li>• <a href="#">Table 6 “Thermal characteristics”</a>: <math>R_{th(j-a)}</math> thermal resistance from junction to ambient for ceramic PCB condition added</li> <li>• <a href="#">Figure 2</a>: <math>t_p</math> pulse time redefined to pulse duration</li> <li>• <a href="#">Figure 3</a>: added</li> <li>• <a href="#">Table 7 “Characteristics”</a>: <math>I_{CBO}</math> collector-base cut-off current conditions adapted</li> <li>• <a href="#">Table 7 “Characteristics”</a>: <math>V_{CEsat}</math> collector-emitter saturation voltage typical value added</li> <li>• <a href="#">Table 7 “Characteristics”</a>: <math>f_T</math> transition frequency conditions and typical value adapted</li> <li>• <a href="#">Table 7 “Characteristics”</a>: <math>C_{ib}</math> common-base input capacitance added</li> <li>• <a href="#">Table 7 “Characteristics”</a>: <math>C_{ob}</math> common-base output capacitance added</li> <li>• <a href="#">Figure 4</a>, <a href="#">6</a>, <a href="#">10</a>, <a href="#">11</a>, <a href="#">12</a>, <a href="#">13</a> and <a href="#">16</a>: added</li> <li>• <a href="#">Figure 5</a>, <a href="#">7</a>, <a href="#">8</a> and <a href="#">9</a>: adapted</li> <li>• <a href="#">Section 12 “Legal information”</a>: updated</li> </ul> |                    |               |            |
| 2PB1424_1      | 20050502  | Product data sheet | -             | -          |

## 12. Legal information

### 12.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition  |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

### 12.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

### 12.3 Disclaimers

**General** — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

**Right to make changes** — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or

malfunction of a NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Terms and conditions of sale** — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

### 12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 13. Contact information

For additional information, please visit: <http://www.nxp.com>

For sales office addresses, send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

**14. Contents**

**1 Product profile . . . . . 1**

1.1 General description . . . . . 1

1.2 Features . . . . . 1

1.3 Applications . . . . . 1

1.4 Quick reference data . . . . . 1

**2 Pinning information . . . . . 2**

**3 Ordering information . . . . . 2**

**4 Marking . . . . . 2**

**5 Limiting values . . . . . 2**

**6 Thermal characteristics . . . . . 3**

**7 Characteristics . . . . . 5**

**8 Package outline . . . . . 9**

**9 Packing information . . . . . 9**

**10 Soldering . . . . . 10**

**11 Revision history . . . . . 11**

**12 Legal information . . . . . 12**

12.1 Data sheet status . . . . . 12

12.2 Definitions . . . . . 12

12.3 Disclaimers . . . . . 12

12.4 Trademarks . . . . . 12

**13 Contact information . . . . . 12**

**14 Contents . . . . . 13**

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.



© NXP B.V. 2007.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

Date of release: 15 January 2007

Document identifier: 2PB1424\_2



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.