


$I_{T(RMS)}$ $T_c = 65^\circ C$ 50% Duty Cycle, Half Sine 1KHz (Amps)	I_{TSM} (Amps $\times 10^3$)		I_{DRM}/I_{RRM} @ Rated V_{DRM}/V_{RRM} and $T_{J(Max)}$ (mA)	I^2t for Fusing @ 8.3 ms ($A^2sec \times 10^4$)	V_{DRM}/V_{RRM} Range (Volts)	V_{TM} @ I_{TM} $T_J = 25^\circ C$		Chip Size (mm)	Junction Temp. Range ($^\circ C$)	$R_{\theta JC}$ ($^\circ C/W$)	$t_{q(Max)}$ @ $T_{J(Max)}$ (μsec)
	50 Hz	60 Hz				I_{TM} (Amps)	V_{TM} (Volts)				
630	5.5	6	100	14.9	800-1200	400	1.95+	33	-40 to 125	.05	5
630	7300	8000	70	26.6	1000-1200	1250	2.2+	33	-40 to 125	.045	30
630	7300	8000	70	26.6	1000-1200	1250	2.2+	33	-40 to 125	.045	20
630	6400	7000	100	20.3	800-1200	1250	2.8+	33	-40 to 125	.045	8 to 10
650	6800	7500	35	23.4	100-1400	1500	2.3	33	-40 to 125	.06	25 to 50
650	7300	8000	35	26.6	100-1200	1500	3.15	33	-40 to 125	.045	10 to 50
690	7.8	8.5	35	30.1	100-1400	1500	2	33	-40 to 125	.045	25 to 50
700	6.8	7.5	45	23.3	500-1400	1500	2.25	30	-40 to 125	.045	40
700	6.2	6.8	35	19.3	1400-1800	1500	2.2	33	-40 to 125	.045	80 to 100
700	11.8	13	60	70.4	600-2000	1500	2.25	50	-40 to 125	.023	60 to 100
700	7.3	8	45	26.6	100-600	3000	2.5	30	-40 to 125	.06	14
700	7.3	8	45	26.6	100-600	3000	2.5	30	-40 to 125	.06	20
750	6.4	7	35	20.5	100-800	1500	2	33	-40 to 125	.06	10 to 20
770	7.3	8	45	30	2000-2400	1500	2.8	38	-40 to 125	.037	60 to 100
800	13.7	15	60	93.7	600-1200	1500	2.1	50	-40 to 125	.023	20 to 60
850	7.8	8.5	35	30.1	100-800	3000	2.4	33	-40 to 125	.045	10 to 20
900	7.3	8	45	26.6	100-700	3000	2.5	30	-40 to 125	.04	14
900	7.3	8	45	26.6	100-700	3000	2.5	30	-40 to 125	.04	20
900	7.7	8.5	45	30.1	100-1200	1500	2.2	38	-40 to 125	.037	15-50
950	9.1	10	45	41.5	500-1300	3000	2.9	40	-40 to 125	.04	17
950	9.1	10	45	41.5	500-1200	2000	2.9	40	-40 to 125	.04	40
950	9.1	10	45	41.5	500-1200	2000	2.9	40	-40 to 125	.04	25
950	8.2	9	35	33.8	100-800	1500	1.55	33	-40 to 125	.045	20 to 40

* = 25°C Value ° = Tentative Specifications + = Rating at $T_{J(Max)}$

$Q_{rr(Max)}$ @ $T_J=25^\circ C$ ($\mu coul$)	Min di/dt Repetitive on-State (A/ μsec)	Min Critical dv/dt @ $T_J(Max)$ (V/ μsec)	Max V _{GT} (V)	Max I _{er} (mA)	PACKAGE INFORMATION			
					Max Mounting Force or Torque	STYLE	Outline	TYPE NO.
—	1000	200	4*	350*	4000 lbs 17.8 KN	Press Pak	18 x 85 mm	°FT500HZ
120	800	200	2.5*	250*	4000 lbs 17.8 KN	Press Pak	18 x 85 mm	°FT500EX
120	800	200	2.5*	250*	4000 lbs 17.8 KN	Press Pak	18 x 85 mm	°FT500EY
—	1000	200	2.5*	250*	4000 lbs 17.8 KN	Press Pak	18 x 85 mm	°FT500GZ
—	600	300	3*	150*	2400 lbs 10.7 KN	Press Pak	T72	T72H ___45
—	600	300	3*	150*	2400 lbs 10.7 KN	Press Pak	T7S	T7SH ___40
—	600	300	3*	150*	2400 lbs 10.7 KN	Press Pak	T7S	T7SH ___45
150	500	200	5	400	2500 lbs 11.1 KN	Press Pak	TO-200AB	C477
—	400	300	3*	150*	2400 lbs 10.7 KN	Press Pak	T7S	T7SH ___46
—	600	400	3*	300*	5500 lbs 24.5 KN	Press Pak	T9G	T9GH ___09
—	500	200	5	400	2000 lbs 8.9 KN	Press Pak	TO-200AC	C394
—	500	200	5	400	2000 lbs 8.9 KN	Press Pak	TO-200AC	C395
—	500	300	3*	150*	2400 lbs 10.7 KN	Press Pak	T72	T72H ___40
125	400	400	3*	200*	4000 lbs 17.8 KN	Press Pak	T82	T82F ___60
—	500	400	3*	300*	5500 lbs 24.5 KN	Press Pak	T9G	T9GH ___10
—	500	300	3*	150*	2400 lbs 10.7 KN	Press Pak	T7S	T7SH ___50
—	500	200	5	400	2500 lbs 11.1 KN	Press Pak	TO-200AB	C434
—	500	200	5	400	2500 lbs 11.1 KN	Press Pak	TO-200AB	C435
125	400	400	3*	200*	4000 lbs 17.8 KN	Press Pak	T82	T82F ___65
250	500	400	5	400	3500 lbs 15.6 KN	Press Pak	TO-200AC	C446
150	500	400	5	400	3500 lbs 15.6 KN	Press Pak	TO-200AC	C447
150	500	400	5	400	3500 lbs 15.6 KN	Press Pak	TO-200AC	C448
—	600	300	3*	150*	2400 lbs 10.7 KN	Press Pak	T7S	T7SH ___60



JEDEC TO-94



JEDEC TO-200AB



This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.