


Variable Capacitance Diode

Description

The 1T408 is a variable capacitance diode designed for electronic tuning of wide-band CATV tuners using a super-small-miniature flat package (SSVC).

Features

- Super-small-miniature flat package
- Small series resistance 0.75Ω Max. (f = 470MHz)
- Large capacitance ratio 11.7 Typ. (C<sub>2</sub>/C<sub>25</sub>)  
18.0 Typ. (C<sub>1</sub>/C<sub>28</sub>)
- Small leakage current 10nA Max. (V<sub>R</sub> = 28V)
- Capacitance deviation in a matching group: within 2%



Applications

Electronic tuning of wide-band CATV tuners

Structure

Silicon epitaxial planar-type diode

Absolute Maximum Ratings (Ta = 25°C)

- Reverse voltage V<sub>R</sub> 34 V
- Operating temperature Topr -20 to +75 °C
- Storage temperature Tstg -65 to +150 °C

Electrical Characteristics


(Ta = 25°C)

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Reverse current	I <sub>R</sub>	V <sub>R</sub> = 28V			10	nA
Diode capacitance	C <sub>2</sub>	V <sub>R</sub> = 2V, f = 1MHz	29.46		35.46	pF
	C <sub>25</sub>	V <sub>R</sub> = 25V, f = 1MHz	2.49		2.89	pF
Capacitance ratio	C <sub>2</sub> /C <sub>25</sub>		11.0	11.7		
	C <sub>25</sub> /C <sub>28</sub>		1.03			
Series resistance	r <sub>s</sub>	C <sub>D</sub> = 14pF, f = 470MHz			0.75	Ω
Capacitance deviation in a matching group	ΔC	V <sub>R</sub> = 2 to 25V, f = 1MHz			2	%


Sony reserves the right to change products and specifications without prior notice. This information does not convey any license by any implication or otherwise under any patents or other right. Application circuits shown, if any, are typical examples illustrating the operation of the devices. Sony cannot assume responsibility for any problems arising out of the use of these circuits.

Example of Representative Characteristics


Diode capacitance vs. Reverse voltage




Reverse current vs. Ambient temperature




Forward voltage vs. Ambient temperature




Reverse voltage vs. Ambient temperature




Diode capacitance vs. Ambient temperature



Reverse current vs. Reverse voltage






Temperature coefficient of diode capacitance



Package Outline

Unit: mm

M-290



	BASE METAL	WITH PLATING
c	0.11 ± 0.005	0.11 <sup>+0.05</sup> / <sub>-0.01</sub>
b	0.3 ± 0.025	0.3 <sup>+0.05</sup> / <sub>-0.02</sub>

SONY CODE	M-290
EIAJ CODE	_____
JEDEC CODE	_____

PACKAGE MATERIAL	EPOXY RESIN
LEAD TREATMENT	SOLDER PLATING
LEAD MATERIAL	COPPER
PACKAGE WEIGHT	0.002g



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.