

SOT23 PNP SILICON PLANAR MEDIUM POWER TRANSISTORS


FMMTA56

ISSUE 4 – MARCH 2001

FEATURES

* Gain of 50 at $I_C=100\text{mA}$

PARTMARKING DETAIL - FMMTA56 - 2G
FMMTA56R - MB



SOT23

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	FMMTA56	UNIT
Collector-Base Voltage	V_{CBO}	-80	V
Collector-Emitter Voltage	V_{CEO}	-80	V
Emitter-Base Voltage	V_{EBO}	-4	V
Continuous Collector Current	I_C	-500	mA
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{tot}	330	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$).

PARAMETER	SYMBOL	FMMTA56		UNIT	CONDITIONS.
		MIN.	MAX.		
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-80		V	$I_C=-1\text{mA}, I_B=0^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-4		V	$I_E=-100\mu\text{A}, I_C=0$
Collector-Emitter Cut-Off Current	I_{CES}		-0.1	μA	$V_{CE}=-60\text{V}$
Collector-Base Cut-Off Current	I_{CBO}		-0.1	μA	$V_{CB}=-80\text{V}, I_E=0$ $V_{CB}=-60\text{V}, I_E=0$
Static Forward Current Transfer Ratio	h_{FE}	50 50			$I_C=-10\text{mA}, V_{CE}=1\text{V}^*$ $I_C=-100\text{mA}, V_{CE}=1\text{V}^*$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		-0.25	V	$I_C=-100\text{mA}, I_B=-10\text{mA}^*$
Base-Emitter Turn-On Voltage	$V_{BE(on)}$		-1.2	V	$I_C=-100\text{mA}, V_{CE}=-1\text{V}^*$
Transition Frequency	f_T	100		MHz	$I_C=-10\text{mA}, V_{CE}=-2\text{V}$ $f=100\text{MHz}$

*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.