

SOT23 PNP SILICON PLANAR DARLINGTON TRANSISTOR


ISSUE 3 – MARCH 2001



FMMTA64

PARTMARKING DETAIL – FMMTA64 - Z2V

COMPLEMENTARY TYPES – FMMTA64 - FMMTA14



SOT23

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	-30	V
Collector-Emitter Voltage	V_{CEO}	-30	V
Emitter-Base Voltage	V_{EBO}	-10	V
Peak Pulse Current	I_{CM}	-800	mA
Continuous Collector Current	I_C	-500	mA
Peak Base Current	I_{BM}	-200	mA
Power Dissipation at $T_{amb}=25^{\circ}C$	P_{tot}	330	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^{\circ}C$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$).

PARAMETER	SYMBOL	FMMTA64		UNIT	CONDITIONS.
		MIN.	MAX.		
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-30		V	$I_C = -10\mu A, I_E = 0$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-30		V	$I_C = -10mA, I_B = 0^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-10		V	$I_E = -10\mu A, I_C = 0$
Collector Cut-Off Current	I_{CBO}		-0.1	μA	$V_{CB} = -30V, I_E = 0$
Emitter Cut-Off Current	I_{EBO}		-0.1	μA	$V_{CE} = -10V$
Static Forward Current Transfer Ratio	h_{FE}	10K 20K			$I_C = -10mA, V_{CE} = 5V^*$ $I_C = -100mA, V_{CE} = 5V^*$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		-1.5	V	$I_C = -100mA, I_B = -0.1mA^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$		-2.0	V	$I_C = -100mA, I_B = -0.1mA^*$
Transition Frequency	f_T	125		MHz	$I_C = -50mA, V_{CE} = -5V$ $f = 20MHz$

*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$

For typical characteristics graphs see FZTA64 datasheet.





LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.