



SOT23 SILICON PLANAR VARIABLE CAPACITANCE DIODE

ISSUE 4 – JANUARY 1998

FMMV105G



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Power Dissipation at $T_{amb}=25^{\circ}\text{C}$	P_{tot}	330	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Reverse Breakdown Voltage	V_{BR}	30			V	$I_R = 10\mu\text{A}$
Reverse current	I_R			10	nA	$V_R = 28\text{V}$
Series Inductance	L_S		3.0		nH	$f=250\text{MHz}$
Diode Capacitance Temperature Coefficient	T_{CC}		280		ppm/ $^{\circ}\text{C}$	$V_R = 3\text{V}, f=1\text{MHz}$

TUNING CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Diode Capacitance	C_d	1.8		2.8	pF	$V_R = 25\text{V}, f=1\text{MHz}$
Capacitance Ratio	C_d / C_d	4.0		6.0		$V_R = 3\text{V}/25\text{V}, f=1\text{MHz}$
Figure of MERIT	Q	250	350			$V_R = 3\text{V}, f=50\text{MHz}$

Spice parameter data is available upon request for this device



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.