

LOW LEVEL AMPLIFIERS (Cont'd)

Type NPN	Maximum Ratings				Electrical Characteristics @ 25°C								Case
	Pd Ambient mW	V _{CB} Volts	V _{CE} Volts	V _{EB} Volts	HFE @ I _C		V _{CE(Sat)} @ I _C /I _B		f _t MHz Min	C _{ob} pF Max	NF @ f		
					Min/Max	mA	Volts	mA/mA			dB Max	kHz BW kHz	
PNP													
2N2601	400	60	60	6	18/90	1	0.5	10/1	50	6	-	-	TO-46
2N2521	400	60	60	8	36/90	1	0.5	10/1	80	6	-	-	TO-46
2N2602	400	60	60	6	36/90	1	0.5	10/1	60	6	-	-	TO-46
2N2522	400	60	60	8	76/333	1	0.5	10/1	90	6	-	-	TO-46
2N2603	400	60	60	6	76/333	1	0.5	10/1	70	6	-	-	TO-46
2N2459	400	100	60	8	40/80	5	0.3	10/1	90	5	-	-	TO-46
2N2590	400	100	60	7	40/80	5	0.4	10/1	50	5	-	-	TO-46
2N2460	400	100	60	8	70/130	5	0.3	10/1	100	5	-	-	TO-46
2N2591	400	100	60	7	70/135	5	0.4	10/1	55	5	-	-	TO-46
2N2461	400	100	60	8	120/180	5	0.3	10/1	110	5	-	-	TO-46
2N2592	400	100	60	7	115/200	5	0.4	10/1	65	5	-	-	TO-46
2N2462	400	100	60	8	170/230	5	0.3	10/1	125	5	-	-	TO-46
2N2593	400	100	60	7	160/275	5	0.4	10/1	75	5	-	-	TO-46
2N2515	400	80	60	6	30/100	5	0.5	10/2	80	6	-	-	TO-46
2N2595	400	80	60	6	20/50	5	0.5	10/2	30	6	-	-	TO-46
2N2596	400	80	60	6	40/100	5	0.5	10/2	45	6	-	-	TO-46
2N2516	400	80	60	6	60/200	5	0.5	10/2	100	6	-	-	TO-46
2N2597	400	80	60	6	80/200	5	0.5	10/2	60	6	-	-	TO-46
2N2518	400	125	80	8	40/100	5	0.5	10/2	80	6	-	-	TO-46
2N2598	400	125	80	7	20/50	5	0.5	10/2	30	6	-	-	TO-46
2N2599	400	125	80	7	40/100	5	0.5	10/2	45	6	-	-	TO-46
2N2519	400	125	80	8	80/200	5	0.5	10/2	100	6	-	-	TO-46
2N2600	400	125	80	7	80/200	5	0.5	10/2	60	6	-	-	TO-46
2N2599A	400	125	100	7	30/120	5	0.5	10/2	40	6	-	-	TO-46
2N2600A	400	125	100	7	60/240	5	0.5	10/2	60	6	-	-	TO-46

RF-IF HIGH FREQUENCY AMPLIFIERS

Type NPN	Maximum Ratings				Electrical Characteristics @ 25°C										Case
	Pd Ambient mW	V _{CB} Volts	V _{CE} Volts	V _{EB} Volts	HFE @ I _C		f _t MHz Min	C _{ob} pF Max	GPE @ f		P _o @ f		NF @ f		
					Min/Max	mA			dB Min	MHz	mW Min	MHz	dB Max	MHz	
PNP															
2N917	200	30	15	3	20/200	3	500	1.7	-	-	-	-	-	-	TO-72
2N995	360	20	15	4	35/140	20	100	10.0	-	-	-	-	6	1kHz	TO-18
2N957	250	40	20	3	45/	10	200	6.0	-	-	-	-	-	-	TO-18
2N916	360	45	25	5	100/	10	-	6.0	-	-	-	-	-	-	TO-18
2N707	300	56	28*	4	9/	10	70	10.0	-	-	2000	100	-	-	TO-18
2N707A	300	70	40	5	90/50	10	70	6.0	-	-	400	100	-	-	TO-18
2N3250	360	50	40	5	50/150	10	250	6.0	-	-	-	-	6	100Hz	TO-18
2N4034	360	40	40	5	70/200	10	400	3.5	-	-	-	-	6	100	TO-18
2N3337	300	40	40	5	30	4	400	1.6	30	60	-	-	5.5	200	TO-72
2N3338	300	40	40	5	30	4	400	1.6	30	60	-	-	5.5	60	TO-72
2N3339	300	40	40	5	30	4	400	1.6	30	200	-	-	5.5	200	TO-72
2N915	360	70	50	5	50/200	10	-	3.5	-	-	-	-	-	-	TO-18

U-H-F AMPLIFIERS

2N5031	200	15	10	3	25/300	1	1000	1.5	14	450	-	-	2.5	450	TO-72
2N5032	200	15	10	3	25/300	1	1000	1.5	14	450	-	-	3.0	450	TO-72
2N5841	350	20	10	3	25/200	25	2200	1.5	-	-	-	-	-	-	TO-72
2N5842	350	20	10	3	25/250	25	1700	1.5	-	-	-	-	-	-	TO-72
2N5179	200	20	12	2.5	25/250	1	900	1.0	15	200	20	500	4.5	200	TO-72
40894	200	20	12	2.5	50/250	1	1200	1.0	15	200	-	-	4.5	200	TO-72
40895	200	20	12	2.5	40/250	1	1200	1.0	15	200	-	-	-	-	TO-72
40896	200	20	12	2.5	27/250	1	1200	1.0	15	200	-	-	-	-	TO-72
40897	200	20	12	2.5	70/250	1	800	1.0	18	200	-	-	-	-	TO-72
2N5180	180	30	15	2	20/200	8	650	1.0	12	200	-	-	4.5	200	TO-72
2N4260	200	15	15	4.5	30/150	10	1600	2.5	-	-	-	-	-	-	TO-72
2N4261	200	15	15	4.5	30/150	10	2000	2.5	-	-	-	-	-	-	TO-72
2N2615	300	30	15	3	20/	3	800	2.8	-	-	50	500	8	60	TO-18
2N2729	300	30	15	3	20/	3	600	2.8	-	-	30	500	6	60	TO-46
2N3289	200	30	15	3	10/150	2	300	1.5	17	200	-	-	7	200	TO-72
2N3290	200	30	15	3	10/150	2	300	1.5	17	200	-	-	7	200	TO-72
2N3291	200	25	15	3	10	2	250	2.0	16	200	-	-	8	200	TO-72

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.