


## Inductors

Epoxy Conformal Coated, Axial Leaded



### FEATURES

- Axial lead type, small lightweight design.
- Special magnetic core structure contributes to high Q and self-resonant frequencies.
- Treated with epoxy resin coating for humidity resistance to ensure long life.
- Heat resistant adhesives and special structural design for effective open circuit measurement.

STANDARD ELECTRICAL SPECIFICATIONS						
IND. @ 1KHz ( $\mu$ H)	TOL.	Q MIN.	TEST FREQ. Q (MHz)	DCR MAX. ( $\Omega$ )	SRF MIN. (MHz)	RATED DC CURRENT (mA)
1000	$\pm 5\%$ , $\pm 10\%$	80	2.52	8	1.7	200
1200	$\pm 5\%$ , $\pm 10\%$	80	2.52	9	1.5	180
1500	$\pm 5\%$ , $\pm 10\%$	80	2.52	10	1.4	160
1800	$\pm 5\%$ , $\pm 10\%$	80	2.52	11	1.3	150
2200	$\pm 5\%$ , $\pm 10\%$	80	2.52	14	1.2	120
2700	$\pm 5\%$ , $\pm 10\%$	80	2.52	18	1.0	110
3300	$\pm 5\%$ , $\pm 10\%$	80	2.52	22	0.9	105
3900	$\pm 5\%$ , $\pm 10\%$	80	2.52	26	0.8	100
4700	$\pm 5\%$ , $\pm 10\%$	80	2.52	30	0.7	95
5600	$\pm 5\%$ , $\pm 10\%$	60	2.52	34	0.7	80
6800	$\pm 5\%$ , $\pm 10\%$	60	2.52	48	0.5	75
8200	$\pm 5\%$ , $\pm 10\%$	60	2.52	62	0.5	70
10,000	$\pm 5\%$ , $\pm 10\%$	60	2.52	74	0.5	65
12,000	$\pm 5\%$ , $\pm 10\%$	50	2.52	88	0.4	60
15,000	$\pm 5\%$ , $\pm 10\%$	50	2.52	102	0.4	55
18,000	$\pm 5\%$ , $\pm 10\%$	40	0.0796	150	0.3	50
22,000	$\pm 5\%$ , $\pm 10\%$	40	0.0796	180	0.3	45
27,000	$\pm 5\%$ , $\pm 10\%$	40	0.0796	210	0.3	40
30,000	$\pm 5\%$ , $\pm 10\%$	40	0.0796	240	0.3	35
33,000	$\pm 5\%$ , $\pm 10\%$	40	0.0796	250	0.2	30
39,000	$\pm 5\%$ , $\pm 10\%$	40	0.0796	270	0.2	25

### ELECTRICAL SPECIFICATIONS

**Inductance Range:** 1000 $\mu$ H to 39,000 $\mu$ H.  
**Inductance Tolerance:**  $\pm 10\%$  standard,  $\pm 5\%$  optional.  
**Operating Temperature Range:** - 20°C to + 105°C.  
**Dielectric Strength:** 250VRMS.

### MECHANICAL SPECIFICATIONS

**Terminal Strength:** Pull = 5 pounds. Twist = 360°C x 3.  
**Protection:** Epoxy uniform roll coated.  
**Leads:** Tinned copper.

### ENVIRONMENTAL SPECIFICATIONS

**Maximum Temperature Rise:** + 20°C.

DIMENSIONS in inches [millimeters]				
MODEL	A (Max.)	B (Max.)	C (Max.)	D (Max.)
IRF-46	0.236 [6.0]	0.197 [5.0]	0.551 [14.0]	0.026 [0.65]

ORDERING INFORMATION		
IRF-46 MODEL	15,000 $\mu$ H INDUCTANCE VALUE	$\pm 10\%$ INDUCTANCE TOLERANCE



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.