

Inductors

Epoxy Conformal Coated, Axial Leaded



STANDARD ELECTRICAL SPECIFICATIONS						
IND. (μH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RES. FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED DC CURRENT (mA)
0.10	± 5%, ± 10%	30	25.2	280	0.085	1400
0.12	± 5%, ± 10%	30	25.2	280	0.085	1350
0.15	± 5%, ± 10%	30	25.2	280	0.095	1270
0.18	± 5%, ± 10%	30	25.2	280	0.12	1200
0.22	± 5%, ± 10%	40	25.2	280	0.15	1150
0.27	± 5%, ± 10%	40	25.2	260	0.15	1110
0.33	± 5%, ± 10%	40	25.2	260	0.15	1110
0.39	± 5%, ± 10%	40	25.2	220	0.17	1000
0.47	± 5%, ± 10%	40	25.2	200	0.17	1000
0.56	± 5%, ± 10%	40	25.2	180	0.17	950
0.68	± 5%, ± 10%	40	25.2	160	0.18	900
0.82	± 5%, ± 10%	40	25.2	140	0.18	900
1.0	± 5%, ± 10%	40	25.2	135	0.18	815
1.2	± 5%, ± 10%	40	7.96	135	0.18	740
1.5	± 5%, ± 10%	40	7.96	130	0.20	700
1.8	± 5%, ± 10%	40	7.96	125	0.23	655
2.2	± 5%, ± 10%	40	7.96	80	0.25	630
2.7	± 5%, ± 10%	40	7.96	80	0.28	595
3.3	± 5%, ± 10%	40	7.96	70	0.30	575
3.9	± 5%, ± 10%	40	7.96	65	0.32	555
4.7	± 5%, ± 10%	40	7.96	45	0.35	530
5.6	± 5%, ± 10%	40	7.96	40	0.40	500
6.8	± 5%, ± 10%	40	7.96	30	0.45	470
8.2	± 5%, ± 10%	40	7.96	28	0.56	425
10	± 5%, ± 10%	40	7.96	22	0.72	370
12	± 5%, ± 10%	40	2.52	20	0.80	350
15	± 5%, ± 10%	40	2.52	16	0.88	335
18	± 5%, ± 10%	40	2.52	15	1.0	315
22	± 5%, ± 10%	40	2.52	13	1.2	285
27	± 5%, ± 10%	40	2.52	11	1.35	270
33	± 5%, ± 10%	40	2.52	10	1.50	255
39	± 5%, ± 10%	40	2.52	9.5	1.70	240
47	± 5%, ± 10%	50	2.52	8.5	2.30	205
56	± 5%, ± 10%	50	2.52	7.5	2.60	195
68	± 5%, ± 10%	50	2.52	6.5	2.90	185
82	± 5%, ± 10%	50	2.52	6.0	3.20	175
100	± 5%, ± 10%	50	2.52	5.5	3.70	165
120	± 5%, ± 10%	60	0.796	5.4	3.80	160
150	± 5%, ± 10%	60	0.796	4.75	4.90	150
180	± 5%, ± 10%	60	0.796	4.35	5.0	140
220	± 5%, ± 10%	60	0.796	4.0	6.50	130
270	± 5%, ± 10%	60	0.796	3.7	7.5	120
330	± 5%, ± 10%	60	0.796	3.4	9.5	100
390	± 5%, ± 10%	60	0.796	2.8	10.5	95
470	± 5%, ± 10%	60	0.796	2.56	17.5	90
560	± 5%, ± 10%	60	0.796	2.35	18.5	85
680	± 5%, ± 10%	60	0.796	2.0	20.0	75
820	± 5%, ± 10%	60	0.796	1.60	23.7	65
1000	± 5%, ± 10%	50	0.796	1.15	30.0	60

FEATURES

- High performance ferrite core is used in this epoxy conformally coated choke which allows for inductance values to 1000μH.
- Axial lead type, small lightweight design.
- Special magnetic core structure contributes to high Q and self-resonant frequencies.
- Treated with epoxy resin coating for humidity resistance to ensure long life.
- Heat resistant adhesives.

ELECTRICAL SPECIFICATIONS

Inductance Range: 0.1μH to 1000μH.

Inductance Tolerance: ± 10% from 0.1μH to 1000μH standard, ± 5% optional.

Operating Temperature Range: - 20°C to + 105°C.

Dielectric Strength: 250V RMS.

MECHANICAL SPECIFICATIONS

Terminal Strength: Pull = 5 pounds. Twist = 360°C x 3.

Protection: Epoxy uniform roll coated.

Leads: Tinned copper.

ENVIRONMENTAL SPECIFICATIONS

Maximum Temperature Rise: + 20°C.

DIMENSIONS in inches [millimeters]				
MODEL	A (Max.)	B (Max.)	C (Max.)	D (Max.)
IRF-24	0.157 [4.0]	0.118 [3.0]	0.394 [10.0]	0.020 [0.5]

ORDERING INFORMATION		
IRF-24	6.8μH	± 10%
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.