

GP1L50/GP1L51 GP1L52V/GP1L54

High Sensitivity Photointerrupter

■ Features


1. High sensing accuracy (Slit width: 0.5mm)
2. High current transfer ratio
(CTR: MIN. 50% at $I_F = 1\text{mA}$)
3. Both-sides mounting type: **GP1L50** (Case height: 10mm)
Either-side mounting type: **GP1L51** (Case height: 10mm)
PWB direct mounting type: **GP1L52V** (Case height: 10mm)
PWB direct mounting type: **GP1L54** (Case height: 8mm)


■ Applications

1. OA equipment, such as floppy disk drives, printers, facsimiles, etc.
2. VCRs

■ Outline Dimensions

(Unit : mm)





Absolute Maximum Ratings

(Ta = 25°C)

Parameter		Symbol	Rating	Unit
Input	Forward current	I_F	50	mA
	*1 Peak forward current	I_{FM}	1	A
	Reverse voltage	V_R	6	V
	Power dissipation	P	75	mW
Output	Collector-emitter voltage	V_{CEO}	35	V
	Emitter-collector voltage	V_{ECO}	6	V
	Collector current	I_C	40	mA
	Collector power dissipation	P_C	75	mW
Operating temperature		T_{opr}	- 25 to + 85	°C
Storage temperature		T_{stg}	- 40 to + 100	°C
*2 Soldering temperature		T_{sol}	260	°C

*1 Pulse width $\leq 100 \mu s$, Duty ratio = 0.01

*2 For 5 seconds

Electro-optical Characteristics

(Ta = 25°C)

Parameter		Symbol	Conditions	MIN.	TYP.	MAX.	Unit			
Input	Forward voltage	V_F	$I_F = 20mA$	-	1.25	1.4	V			
	Peak forward voltage	V_{FM}	$I_{FM} = 0.5A$	-	3	4	V			
	Reverse current	I_R	$V_R = 3V$	-	-	10	μA			
Output	Collector dark current	I_{CEO}	$V_{CE} = 10V$	-	-	10^{-6}	A			
Transfer characteristics	Collector Current	I_C	$I_F = 1mA, V_{CE} = 2V$	0.5	-	20	mA			
	Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_F = 2mA, I_C = 0.5mA$	-	-	1.0	V			
			Response time	Rise time	t_r	$V_{CE} = 2V, I_C = 2mA$	-	80	400	μs
				Fall time	t_f	$R_L = 100\Omega$	-	70	300	μs

Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Collector Power Dissipation vs. Ambient Temperature




Fig. 3 Peak Forward Current vs. Duty Ratio




Fig. 4 Forward Current vs. Forward Voltage




Fig. 5 Collector Current vs. Forward Current




Fig. 6 Collector Current vs. Collector-emitter Voltage




Fig. 7 Collector Current vs. Ambient Temperature




Fig. 8 Collector-emitter Saturation Voltage vs. Ambient Temperature





Fig. 9 Response Time vs. Load Resistance



Test Circuit for Response Time




Fig.10 Frequency Response




Fig.11 Collector Dark Current vs. Ambient Temperature




Fig.12 Relative Collector Current vs. Shield Distance (1)





Fig. 13 Relative Collector Current vs. Shield Distance (2)



■ Precautions for Use

- (1) In case of cleaning, use only the following type of cleaning solvent.
Ethyl alcohol, Methyl alcohol, Isopropyl alcohol
- (2) As for other general cautions, refer to the chapter“Precautions for Use”.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.