


# SOT23 PNP SILICON PLANAR SWITCHING TRANSISTOR

## FMMT4126

ISSUE 2 – MARCH 1995



PARTMARKING DETAIL – ZE



### ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	$V_{CBO}$	-25	V
Collector-Emitter Voltage	$V_{CEO}$	-25	V
Emitter-Base Voltage	$V_{EBO}$	-4	V
Continuous Collector Current	$I_C$	-200	mA
Power Dissipation at $T_{amb}=25^{\circ}C$	$P_{tot}$	330	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^{\circ}C$

### ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ ).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-25		V	$I_C = -10\mu A$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-25		V	$I_C = -1mA^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-4		V	$I_E = -10\mu A$
Collector Cut-Off Current	$I_{CBO}$		-50	nA	$V_{CB} = -20V$
Emitter Cut-Off Current	$I_{EBO}$		-50	nA	$V_{EB} = -3V$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		0.4	V	$I_C = -50mA, I_B = -5mA^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$		0.95	V	$I_C = -50mA, I_B = -5mA^*$
Static Forward Current Transfer Ratio	$h_{FE}$	120 60	360		$I_C = -2mA, V_{CE} = -1V^*$ $I_C = -50mA, V_{CE} = -1V^*$
Transition Frequency	$f_T$	250		MHz	$I_C = -10mA, V_{CE} = -20V, f = 100MHz$
Output Capacitance	$C_{obo}$		4.5	pF	$V_{CB} = -5V, I_E = 0, f = 140KHz$
Input Capacitance	$C_{ibo}$		10	pF	$V_{BE} = -0.5V, I_E = 0, f = 140KHz$
Noise Figure	N		4	dB	$I_C = -200\mu A, V_{CE} = -5V, R_g = -2k\Omega$ $f = 30Hz$ to $15KHz$ at 3dB points
Small Signal Current Transfer	$h_{fe}$	120	180		$I_C = -2mA, V_{CE} = -1V, f = 1KHz$

### SWITCHING CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ ).

PARAMETER	SYMBOL	TYP.	UNIT	CONDITIONS
Delay Time	$t_d$	25	ns	$V_{CC} = -3V, V_{BE(off)} = -0.5V$ $I_C = -10mA, I_{B1} = -1mA$
Rise Time	$t_r$	18	ns	
Storage Time	$t_s$	140	ns	$V_{CC} = -3V, I_C = -10mA$
Fall Time	$t_f$	15	ns	$I_{B1} = I_{B2} = -1mA$

\*Measured under pulsed conditions. Pulse width=300 $\mu s$ . Duty cycle  $\leq 2\%$



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.