

SOT23 SILICON PLANAR HIGH SPEED SWITCHING DIODE


FMMD6050

ISSUE 2 - OCTOBER 1995

DIODE PIN CONNECTION



PARTMARKING DETAIL – 5A



SOT23

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Breakdown Voltage ($I_R=100\mu A$)	$V_{(BR)}$	70	V
Peak Forward Current	I_F	200	mA
Peak Forward Surge Current	I_{FM}	500	mA
Power Dissipation at $T_{amb} = 25^\circ C$	P_{tot}	330	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^\circ C$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Breakdown Voltage	$V_{(BR)}$	70		V	$I_R=10\mu A$
Forward Voltage	V_F	0.5 0.8	0.7 1.1	V V	$I_F=1mA$ $I_F=100mA$
Reverse Current	I_R		0.1	μA	$V_R=50V$
Recovery Time*	t_{rr}		5	ns	$I_F= I_R=10mA,$ $I_{R(REC)}=1 mA$
Diode Capacitance	C_d		2.5	pF	$V_R=0, f=1MHz$

*For switching test circuit diagram see FMMD7000 datasheet



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.