

6501130 NATL SEMICOND, (DISCRETE)

28C 35511 D

T-29-01

Pro Electron Series

PRO ELECTRON SERIES (Bipolar—see page 5-37 for JFET)

Type No.	Case Style	V <sub>CE0</sub> <sup>*</sup> (V) Min	V <sub>CE0</sub> <sup>*</sup> (V) Min	V <sub>EB0</sub> (V) Min	I <sub>CB0</sub> <sup>*</sup> (mA) Max	V <sub>CB</sub> (V)	HFE I <sub>fe</sub> 1 kHz <sup>*</sup> Min	HFE I <sub>fe</sub> 1 kHz <sup>*</sup> Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V)	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V)		I <sub>C</sub> (mA)	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
											Min	Max								
BC107	TO-18	45	6	50	15*	50	40	0.01	5	0.6	0.55	0.7*	10	4.5	150	10		10	1	04
BC107A	TO-18	45	6	50	15*	50	125	500*	5	0.6	0.55	0.7*	10	4.5	150	10		10	1	04
BC107B	TO-18	45	6	50	15*	50	40	0.01	5	0.6	0.55	0.7*	10	4.5	150	10		10	1	04
BC108	TO-18	20	5	30	15*	30	40	0.01	5	0.6	0.55	0.7*	10	4.5	150	10		10	1	04
BC108A	TO-18	20	5	30	15*	30	125	260*	5	0.6	0.55	0.7*	10	4.5	150	10		10	1	04
BC108B	TO-18	20	5	30	15*	30	40	0.01	5	0.6	0.55	0.7*	10	4.5	150	10		10	1	04
BC108C	TO-18	20	5	30	15*	30	40	0.01	5	0.6	0.55	0.7*	10	4.5	150	10		10	1	04
BC109	TO-18	20	5	30	15*	30	100	0.01	5	0.6	0.55	0.7*	10	4.5	150	10		4	1	04
BC109B	TO-18	20	5	30	15*	30	240	500*	5	0.6	0.55	0.7*	10	4.5	150	10		4	1	04
BC109C	TO-18	20	5	30	15*	30	100	0.01	5	0.6	0.55	0.7*	10	4.5	150	10		4	1	04
BC140	TO-39	40	7	80*	100*	60	40	250	100-1	1.0	1.8*	1A	25	25	50	50	850	850	2	14
BC140-6	TO-39	40	7	80*	100*	60	40	100	100	1.0	1.8*	1A	25	25	50	50	850	850	2	14
BC140-10	TO-39	40	7	80*	100*	60	63	160	100	1.0	1.8*	1A	25	25	50	50	850	850	2	14
BC140-16	TO-39	40	7	80*	100*	60	100	250	100	1.0	1.8*	1A	25	25	50	50	850	850	2	14
BC141	TO-39	60	7	100*	100*	60	40	250	100	1.0	1.8*	1A	25	25	50	50	850	850	2	14
BC141-6	TO-39	60	7	100*	100*	60	40	100	100	1.0	1.8*	1A	25	25	50	50	850	850	2	14
BC141-10	TO-39	60	7	100*	100*	60	63	160	100	1.0	1.8*	1A	25	25	50	50	850	850	2	14

6501130 NATL SEMICOND, (DISCRETE)

28C 35512

D



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB0</sub> (V) Min	V <sub>CE0</sub> (V) Min	V <sub>EB0</sub> (V) Min	IC <sub>ES</sub> <sup>*</sup> IC <sub>BO</sub> (mA) Max	H <sub>FE</sub> h <sub>FE</sub> @ 1 kHz Min Max	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) Min Max	IC (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC143	TO-5	60	60	5	50	20	1.5	1.5	500	20	60				63
BC146-1	TO-92 (94)	20	20	4	50	80	1.5	1.5	500	20	60				04
BC146-2	TO-92 (94)	20	20	4	50	140	1.5	1.5	500	20	60				04
BC146-3	TO-92 (94)	20	20	4	50	280	1.5	1.5	500	20	60				04
BC160	TO-39	40*	5	40	100	40	1.0	1.7*	1A	30	50	650		2	67
BC160-6	TO-39	40*	5	40	100	40	1.0	1.7*	1A	30	50	650		2	67
BC160-10	TO-39	40*	5	40	100	63	1.0	1.7*	1A	30	50	650		2	67
BC160-16	TO-39	40*	5	40	100	100	1.0	1.7*	1A	30	50	650		2	67
BC161	TO-39	60*	5	60	100	40	1.0	1.7*	1A	30	50	650		2	67
BC161-6	TO-39	60*	5	60	100	40	1.0	1.7*	1A	30	50	650		2	67
BC161-10	TO-39	60*	5	60	100	63	1.0	1.7*	1A	30	50	650		2	67
BC161-16	TO-39	60*	5	60	100	100	1.0	1.7*	1A	30	50	650		2	67
BC167	TO-92 (94)	60*	45	6	15*	110	0.2	0.55	10	4.5	150		10	1	04
BC167A	TO-92 (94)	60*	45	6	15*	125	0.6	0.55	100	4.5	150		10	1	04
BC167B	TO-92 (94)	60*	45	6	15*	110	0.2	0.55	10	4.5	150		10	1	04
BC168	TO-92 (94)	20	20	5	15*	110	0.2	0.55	10	4.5	150		10	1	04
BC168A	TO-92 (94)	20	20	5	15*	125	0.6	0.55	100	4.5	150		10	1	04
BC168B	TO-92 (94)	20	20	5	15*	110	0.2	0.55	10	4.5	150		10	1	04

T-29-01

TEST CONDITIONS:  
 (1) IC = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) IC = 100 mA, V<sub>CE</sub> = 20V, IB<sup>1</sup> = IB<sup>2</sup> = 5 mA. (3) IC = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) IC = 100 mA, V<sub>CE</sub> = 10V, IB<sup>1</sup> = IB<sup>2</sup> = 10 mA. (5) IC = 10 mA, V<sub>CE</sub> = 3V, IB<sup>1</sup> = IB<sup>2</sup> = 1 mA. (6) IC = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) IC = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) IC = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) IC = 150 mA, V<sub>CE</sub> = 6V, IB<sup>1</sup> = IB<sup>2</sup> = 15 mA. (10) IC = 10 μA, V<sub>CE</sub> = 5V, f = WB.

Pro Electron Series

5

6501130 NATL SEMICOND, (DISCRETE)

28C 35513 D

Pro Electron Series

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	VCES* VCBO (V) Min	VCEO (V) Min	VEBO (V) Min	ICES* ICBO (mA) Max	HFE hfe 1 kHz* Min Max	VCE(SAT) (V) Max	VBE(SAT) & VBE(ON)* (V)		Cob (pF) Max	fT (MHz) Min Max	toff (ns) Max	NF (dB) Max	Test Conditions	Process No.
								Min	Max						
BC168C	TO-92 (94)		20	5	15*	110 450	0.2 0.6	0.55	0.70* 2	4.5	150		10	1	04
BC169	TO-92 (94)		20	5	15*	110 240	0.2 0.6	0.55	0.70* 2	4.5	150		4	1	04
BC169B	TO-92 (94)		20	5	15*	110 240	0.2 0.6	0.55	0.70* 2	4.5	150		4	1	04
BC169C	TO-92 (94)		20	5	15*	110 450	0.2 0.6	0.55	0.70* 2	4.5	150		4	1	04
BC177	TO-18	50	45	5	100	110 125	0.18		0.78 10 0.75* 2 1.0* 100	4.5	150		10	1	71
BC177A	TO-18	50	45	5	100	110 125	0.18		0.78 10 0.75* 2 1.0* 100	4.5	150		10	1	71
BC177B	TO-18	50	45	5	100	110 240	0.18		0.78 10 0.75* 2 1.0* 100	4.5	150		10	1	71
BC177VI	TO-18	50	45	5	100	110 75	0.18		0.78 10 0.75* 2 1.0* 100	4.5	150		10	1	71
BC178	TO-18	30	25	5	100	110 125	0.18		0.78 10 0.75* 2 1.0* 100	4.5	150		10	1	71
BC178A	TO-18	30	25	5	100	110 125	0.18		0.78 10 0.75* 2 1.0* 100	4.5	150		10	1	71
BC178B	TO-18	30	25	5	100	110 240	0.18		0.78 10 0.75* 2 1.0* 100	4.5	150		10	1	71
BC179	TO-18	25	20	5	100	110 125	0.18		0.78 10 0.75* 2 1.0* 100	4.5	150		4	1	71
BC179A	TO-18	25	20	5	100	110 125	0.18		0.78 10 0.75* 2 1.0* 100	4.5	150		4	1	71

T-29-01

6501130 NATL SEMICOND, (DISCRETE)

28C 35514

T-29-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE5</sub> <sup>*</sup> V <sub>CB0</sub> (V) Min	V <sub>CE0</sub> (V) Min	V <sub>EBO</sub> (V) Min	I <sub>CE5</sub> <sup>*</sup> I <sub>CB0</sub> (mA) Max	HFE h <sub>fe</sub> 1 kHz Min	HFE h <sub>fe</sub> 1 kHz Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V) Min	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) Min	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	f <sub>T</sub> (MHz) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC179B	TO-18	25	20	5	100	110	500*	2	0.18	0.78	10	4.5	150	10		4	1	71
BC182	TO-92 (97)	60	50	5	15	40	500*	0.01	0.6	1.2	100	5	150	10		10	1	04
BC182A	TO-92 (97)	60	50	5	15	40	500*	0.01	0.6	1.2	100	5	150	10		10	1	04
BC182B	TO-92 (97)	60	50	5	15	40	500*	0.01	0.6	1.2	100	5	150	10		10	1	04
BC182L	TO-92 (94)	60	50	5	15	40	500*	0.01	0.6	1.2	100	5	150	10		10	1	04
BC182LA	TO-92 (94)	60	50	5	15	40	500*	0.01	0.6	1.2	100	5	150	10		10	1	04
BC182LB	TO-92 (94)	60	50	5	15	40	500*	0.01	0.6	1.2	100	5	150	10		10	1	04
BC183	TO-92 (97)	45	30	5	15	40	900*	0.01	0.6	1.2	100	5	150	10		10	1	04
BC183A	TO-92 (97)	45	30	5	15	40	900*	0.01	0.6	1.2	100	5	150	10		10	1	04
BC183B	TO-92 (97)	45	30	5	15	40	900*	0.01	0.6	1.2	100	5	150	10		10	1	04
BC183C	TO-92 (97)	45	30	5	15	40	900*	0.01	0.6	1.2	100	5	150	10		10	1	04

TEST CONDITIONS:

(1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35515 D

T-29-01

Pro Electron Series

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE</sub> * V <sub>CB0</sub> (V) Min	V <sub>CEO</sub> (V) Min	V <sub>EB0</sub> (V) Min	I <sub>CE</sub> * I <sub>CB0</sub> (nA) Max	V <sub>CB</sub> (V)	H <sub>FE</sub> h <sub>FE</sub> @ 1 kHz*		I <sub>C</sub> & V <sub>CE</sub> (mA) (V)	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)*</sub> (V)		I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	I <sub>C</sub> (mA) @ Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
							Min	Max			Min	Max								
BC183L	TO-92 (94)	45	30	5	15	30	40 80 125	0.01 100 900*	5 5 5	0.6 0.25	1.2 0.55	100 10 2	5	150	10			10	1	04
BC183LA	TO-92 (94)	45	30	5	15	30	40 80 125	0.01 100 900*	5 5 5	0.6 0.25	1.2 0.55	100 10 2	5	150	10			10	1	04
BC183LB	TO-92 (94)	45	30	5	15	30	40 80 240	0.01 100 500*	5 5 5	0.6 0.25	1.2 0.55	100 10 2	5	150	10			10	1	04
BC183LC	TO-92 (94)	45	30	5	15	30	40 80 450	0.01 100 900*	5 5 5	0.6 0.25	1.2 0.55	100 10 2	5	150	10			10	1	04
BC184	TO-92 (97)	45	30	5	15	30	100 130 240	0.01 100 900*	5 5 5	0.6 0.25	1.2 0.55	100 10 2	5	150	10			4	1	04
BC184B	TO-92 (97)	45	30	5	15	30	100 130 240	0.01 100 500*	5 5 5	0.6 0.25	1.2 0.55	100 10 2	5	150	10			4	1	04
BC184C	TO-92 (97)	45	30	50	15	30	100 130 450	0.01 100 900*	5 5 5	0.6 0.25	1.2 0.55	100 10 2	5	150	10			4	1	04
BC184L	TO-92 (94)	45	30	50	15	30	100 130 240	0.01 100 900*	5 5 5	0.6 0.25	1.2 0.55	100 10 2	5	150	10			4	1	04
BC184LB	TO-92 (94)	45	30	50	15	30	100 130 240	0.01 100 500*	5 5 5	0.6 0.25	1.2 0.55	100 10 2	5	150	10			4	1	04
BC184LC	TO-92 (94)	45	30	50	15	30	100 130 450	0.01 100 900*	5 5 5	0.6 0.25	1.2 0.55	100 10 2	5	150	10			4	1	04
BC204	TO-92 (92)	50	45	5	50	45	50	450	2	5	0.3	10						10	1	71
BC207	TO-92 (92)	50	45	5	15	40	110	450	2	5	0.25 0.6	10 100	6					10	1	04
BC212	TO-92 (97)	60	50	5	15	30	60	400*	2	5	0.6 0.25	1.1 0.6	10 10 2	200	10			10	1	63

6501130 NATL SEMICOND, (DISCRETE)

28C 35516

T-29-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> * V <sub>CB0</sub> (V) Min	V <sub>CE0</sub> (V) Min	V <sub>EB0</sub> (V) Min	I <sub>CE</sub> * I <sub>CB0</sub> (mA) Max	HFE h <sub>FE</sub> 1 kHz* Min	I <sub>C</sub> & V <sub>CE</sub> (mA) (V) Max	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)*</sub> (V) Min	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC212A	TO-92 (97)	60	50	5	15	100	300* 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC212B	TO-92 (97)	60	50	5	15	200	400* 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC212L	TO-92 (94)	60	50	5	15	40 60 60*	0.01 2 5 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC212LA	TO-92 (94)	60	50	5	15	40 60 100	0.01 2 5 300* 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC212LB	TO-92 (94)	60	50	5	15	40 60 200	0.01 2 5 400* 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC213	TO-92 (97)	45	30	5	15	40 60 80	0.01 2 5 600* 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC213A	TO-92 (97)	45	30	5	15	40 60 100	0.01 2 5 300* 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC213B	TO-92 (97)	45	30	5	15	40 60 200	0.01 2 5 400* 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC213C	TO-92 (97)	45	30	5	15	40 60 350	0.01 2 5 600* 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC213L	TO-92 (94)	45	30	5	15	40 80 80*	0.01 2 5 400 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC213LA	TO-92 (94)	45	30	5	15	40 80 100	0.01 2 5 300* 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63

TEST CONDITIONS:

(1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

D

Pro Electron Series

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35517 D

T-29-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE0</sub> <sup>*</sup> (V)		V <sub>BE0</sub> (V)	I <sub>CE0</sub> <sup>*</sup> (mA)		H <sub>FE</sub> I <sub>hfe</sub> @ 1 kHz <sup>*</sup>	I <sub>C</sub> & V <sub>CE</sub> (V)		V <sub>CE(SAT)</sub> (V) & V <sub>BE(ON)</sub> <sup>*</sup> (V)		I <sub>C</sub> (mA)		C <sub>ob</sub> (pF)	f <sub>T</sub> (MHz)		t <sub>off</sub> (ns)	NF (dB)	Test Conditions	Process No.
		Min	Max		Min	Max		Min	Max	Min	Max	Min	Max		Min	Max				
BC213LB	TO-92 (94)	45	30	5	15	30	40	0.01	5	0.6	1.1	100	10	10	200	10	1	63		
BC213LC	TO-92 (94)	45	30	5	15	30	200	400*	5	0.25	0.6	0.72*	2	10	200	10	1	63		
BC214	TO-92 (97)	45	30	5	15	30	350	600*	5	0.6	1.1	100	10	10	200	10	1	63		
BC214A	TO-92 (97)	45	30	5	15	30	140	600*	5	0.6	1.1	100	10	10	200	10	1	63		
BC214B	TO-92 (97)	45	30	5	15	30	40	0.01	5	0.6	1.1	100	10	10	200	10	1	63		
BC214C	TO-92 (97)	45	30	5	15	30	200	400*	5	0.25	0.6	0.72*	2	10	200	10	1	63		
BC214L	TO-92 (94)	45	30	5	15	30	40	0.01	5	0.6	1.1	100	10	10	200	10	1	63		
BC214LB	TO-92 (94)	45	30	5	15	30	80	2	5	0.6	1.1	100	10	10	200	10	1	63		
BC214LC	TO-92 (94)	45	30	5	15	30	120	100	5	0.25	0.6	0.72*	2	10	200	10	1	63		
BC237-92	TO-92 (97)	50	45	6	50	20	100	0.01	5	0.25	0.77*	10	4.5	10	200	10	1	04		
BC237A-92	TO-92 (97)	50	45	6	50	20	140	2	5	0.25	0.6	100	4.5	10	200	10	1	04		

6501130 NATL SEMICOND, (DISCRETE)

28C 35518  
T-24-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	VCES* V <sub>CE0</sub> (V) Min	VEBO (V) Min	ICES* I <sub>CB0</sub> (mA) Max	HFE h <sub>FE</sub> @ 1 kHz	VCE(SATI) & VBE(ON)* (V) Max	VBE(SATI) & VBE(ON)* (V) Min	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.		
															I <sub>C</sub> & V <sub>CE</sub> (mA) (V) Max	I <sub>C</sub> (mA) Max
BC237B-92	TO-92 (97)	50	45	50	100	0.25	0.77*	4.5		10		10	1	04		
					140										0.01	100
					240										500*	2
BC238-92	TO-92 (97)	30	20	50	100	0.25	0.77*	4.5		10		10	1	04		
					140										0.01	100
					120										100	5
BC238A-92	TO-92 (97)	30	20	50	100	0.25	0.77*	4.5		10		10	1	04		
					140										0.01	100
					120										100	5
BC238B-92	TO-92 (97)	30	20	50	100	0.25	0.77*	4.5		10		10	1	04		
					140										0.01	100
					120										100	5
BC238C-92	TO-92 (97)	30	20	50	100	0.25	0.77*	4.5		10		10	1	04		
					140										0.01	100
					120										100	5
BC239-92	TO-92 (97)	30	20	50	100	0.25	0.77*	4.5		10		4	1	04		
					140										0.01	100
					120										100	5
BC239B-92	TO-92 (97)	30	20	50	100	0.25	0.77*	4.5		10		4	1	04		
					140										0.01	100
					120										100	5
BC239C-92	TO-92 (97)	30	20	50	100	0.25	0.77*	4.5		10		4	1	04		
					140										0.01	100
					120										100	5
BC281A	TO-18	45	45	50	100	0.25	0.9	4.5		10		6	3	71		
					140										0.01	100
					120										100	5

TEST CONDITIONS:  
 (1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

Pro Electron Series

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35519 D  
T-29-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> <sup>*</sup> (V) Min	V <sub>CE</sub> <sup>*</sup> (V) Min	V <sub>EB</sub> <sup>*</sup> (V) Min	I <sub>CE</sub> <sup>*</sup> I <sub>CB</sub> <sup>*</sup> (mA) Max	HFE h <sub>FE</sub> 1 kHz <sup>*</sup> Min	HFE h <sub>FE</sub> 1 kHz <sup>*</sup> Max	I <sub>C</sub> & V <sub>CE</sub> (mA) (V) Min	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) Min	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	f <sub>T</sub> (MHz) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC261B	TO-18		45		50	100	0.01	5	0.25	0.9	10					6	3	71
						140	2	5	0.6		100							
						120	100	5										
						240	500*	5										
BC262A	TO-18		20	5	50	100	0.01	5	0.25	0.9	10					6	3	71
						140	2	5										
						120	100	5	0.6		100							
						125	260*	2										
BC262B	TO-18		20	5	50	100	0.01	5	0.25	0.9	10					6	3	71
						140	2	5										
						120	100	5	0.6		100							
						240	500*	2										
BC263A	TO-18		20	5	50	100	0.01	5	0.25	0.9	10					2.5	3	71
						140	2	5										
						120	100	5	0.6		100							
						125	260*	2										
BC263B	TO-18		20	5	50	100	0.01	5	0.25	0.9	10					2.5	3	71
						140	2	5										
						120	100	5	0.6		100							
						240	500*	2										
BC307-92	TO-92 (97)		45	5	100	100	0.01	5	0.18	0.78	10					10	1	71
						140	2	5		1.0*	100							
						120	100	5										
						75	500*	2		0.75*	2							
BC307A-92	TO-92 (97)		45	5	100	100	0.01	5	0.18	0.78	10					10	1	71
						140	2	5		1.0*	100							
						120	100	5										
						125	260*	2		0.75*	2							
BC307B-92	TO-92 (97)		45	5	100	100	0.01	5	0.18	0.78	10					10	1	71
						140	2	5		1.0*	100							
						120	100	5										
						240	500*	2		0.75*	2							
BC308-92	TO-92 (97)		25	5	100	100	0.01	5	0.18	0.78	10					10	1	71
						140	2	5		1.0*	100							
						120	100	5										
						125	900*	2		0.75*	2							
BC308A-92	TO-92 (97)		25	5	100	100	0.01	5	0.18	0.78	10					10	1	71
						140	2	5		1.0*	100							
						120	100	5										
						125	260*	2		0.75*	2							

6501130 NATL SEMICOND, (DISCRETE)

28C 35520

T-29-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> (V) Min	V <sub>CE0</sub> (V) Min	V <sub>EB0</sub> (V) Min	I <sub>CE</sub> <sup>*</sup> I <sub>CB0</sub> (mA) Max	HFE h <sub>fe</sub> 1 kHz <sup>*</sup>		I <sub>C</sub> & V <sub>CE</sub> (mA) (V)		V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V)		I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
						Min	Max	Min	Max		Min	Max								
BC308B-92	TO-92 (97)	25	25	5	100	100	0.01	5	0.18	0.78	10	71	10	1	71					
BC308C-92	TO-92 (97)	25	25	5	100	100	0.01	5	0.18	0.78	10	71	10	1	71					
BC309-92	TO-92 (97)	25	20	5	100	100	0.01	5	0.18	0.78	10	71	4	1	71					
BC309B-92	TO-92 (97)	25	20	5	100	100	0.01	5	0.18	0.78	10	71	4	1	71					
BC309C-92	TO-92 (97)	25	20	5	100	100	0.01	5	0.8	0.78	10	71	4	1	71					
BC317	TO-92 (92)	45	45	6	30	20	110	450	0.2	0.77	10	04	6	1	04					
BC317A	TO-92 (92)	45	45	6	30	20	110	220	0.2	0.77	10	04	6	1	04					
BC317B	TO-92 (92)	45	45	6	30	20	200	450	0.2	0.77	10	04	6	1	04					
BC318	TO-92 (92)	20	20	5	30	20	110	800	0.2	0.77	10	04	6	1	04					
BC318A	TO-92 (92)	20	20	5	30	20	110	220	0.2	0.77	10	04	6	1	04					

TEST CONDITIONS:  
 (1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35521 D

Pro Electron Series

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE</sub> <sup>s</sup> V <sub>CB</sub> <sup>s</sup> (V) Min	V <sub>CE</sub> <sup>s</sup> (V) Min	V <sub>EB</sub> <sup>s</sup> (V) Min	I <sub>CB</sub> <sup>s</sup> I <sub>CB</sub> <sup>s</sup> @ (mA) Max	HFE h <sub>FE</sub> 1 kHz Min Max	V <sub>CE</sub> <sup>s</sup> & V <sub>CE</sub> (V) Min Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> (V) Min Max	I <sub>C</sub> (mA) Min Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	I <sub>C</sub> (mA) Min Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC318B	TO-92 (92)	30	20	5	30	200 240	0.2 0.5	0.77* 0.72* 2	10 100	4				6	1	04
BC318C	TO-92 (92)	30	20	5	30	100 450	0.2 0.5	0.77* 0.72* 2	10 100	4				6	1	04
BC319	TO-92 (92)	30	20	5	30	40 200 240	0.2 0.5	0.77* 0.72* 2	10 100	4				4	1	04
BC319B	TO-92 (92)	30	20	5	30	200 240	0.2 0.5	0.77* 0.72* 2	10 100	4				4	1	04
BC319C	TO-92 (92)	30	20	5	30	100 420 450	0.2 0.5	0.77* 0.72* 2	10 100	4				4	1	04
BC327	TO-92 (97)	50†	45	5	100†	40	0.7	12*	500	4				4	1	67
BC327-10	TO-92 (97)	50†	45	5	100†	40 63	0.7	1.2*	500	4				4	1	67
BC327-16	TO-92 (97)	50†	45	5	100†	40 100	0.7	1.2*	500	4				4	1	67
BC327-25	TO-92 (97)	50†	45	5	100†	40 160	0.7	1.2*	500	4				4	1	67
BC328	TO-92 (97)	30†	25	5	100†	40 100	0.7	1.2*	500	4				4	1	67
BC328-10	TO-92 (97)	30†	25	5	100†	40 63	0.7	1.2*	500	4				4	1	67
BC328-16	TO-92 (97)	30†	25	5	100†	40 100	0.7	1.2*	500	4				4	1	67
BC328-25	TO-92 (97)	30†	25	5	100†	40 160	0.7	1.2*	500	4				4	1	67
BC337	TO-92 (97)	50†	45	5	100†	40 100	0.7	1.2*	500	4				4	1	14
BC337-10	TO-92 (97)	50†	45	5	100†	40 63	0.7	1.2*	500	4				4	1	14
BC337-16	TO-92 (97)	50†	45	5	100†	40 100	0.7	1.2*	500	4				4	1	14
BC337-25	TO-92 (97)	50†	45	5	100†	40 160	0.7	1.2*	500	4				4	1	14

T-29-01

6501130 NATL SEMICOND, (DISCRETE)

28C 35522

T-29-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE0</sub> <sup>*</sup> (V) Min	V <sub>BE0</sub> <sup>*</sup> (V) Min	I <sub>CB0</sub> <sup>*</sup> (mA) Max	h <sub>FE</sub> @ 1 kHz <sup>*</sup> Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V)	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) Min Max	I <sub>C</sub> (mA) Min Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC338	TO-92 (97)	30†	5	100†	40 100	300 100	0.7	1.2*	500 300	4			4	1	14
BC338-10	TO-92 (97)	30†	5	100†	40 63	300 100	0.7	1.2*	500 300	4			4	1	14
BC338-16	TO-92 (97)	30†	5	100†	40 100	300 100	0.7	1.2*	500 300	4			4	1	14
BC338-25	TO-92 (97)	30†	5	100†	40 160	300 100	0.7	1.2*	500 300	4			4	1	14
BC415	TO-92 (97)	45	5	15	40 120	0.01 800	0.25 0.6	1.2*	10 100				2	10	71
BC415A	TO-92 (97)	45	5	15	40 120	0.01 220	0.25 0.6	1.2*	10 100				2	10	71
BC415B	TO-92 (97)	45	5	15	100 180	0.01 460	0.25 0.6	1.2*	10 100				2	10	71
BC415C	TO-92 (97)	45	5	15	100 380	0.01 800	0.25 0.6	1.2*	10 100				2	10	71
BC485	TO-92 (97)	45	5	100	15 40	1A 10	0.5	1.2*	500 300	4			4	1	14
BC485A	TO-92 (97)	45	5	100	15 40	1A 10	0.5	1.2*	500 300	4			4	1	14
BC485B	TO-92 (97)	45	5	100	15 100	1A 250	0.5	1.2*	500 300	4			4	1	14
BC485L	TO-92 (97)	45	5	100	15 60	1A 150	0.5	1.2*	500 300	4			4	1	14
BC547	TO-92 (97)	50	6	10	125	500*	0.25 0.6	0.77* 0.55	10 100	4.5			10	1	04
BC547A	TO-92 (97)	50	6	10	125	260*	0.25 0.6	0.77* 0.55	10 2	4.5			10	1	04

TEST CONDITIONS:

(1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

5

Pro Electron Series

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35523 D

T-29-01

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE</sub> * V <sub>CB</sub> (V) Min	V <sub>CE0</sub> (V) Min	V <sub>EBO</sub> (V) Min	I <sub>CE</sub> * I <sub>CB</sub> (mA) Max	HFE h <sub>FE</sub> 1 kHz* Min	I <sub>C</sub> & V <sub>CE</sub> (mA) (V) Max	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> * (V) Min		I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
									Max	Max								
BC547B	TO-92 (97)	50	45	6	10	240	500*	0.25 0.6	0.55	0.77*	100	4.5				10	1	04
BC547C	TO-92 (97)	50	45	6	10	450	900*	0.25 0.6	0.55	0.77*	100	4.5				10	1	04
BC548	TO-92 (97)	30	20	5	10	125	900*	0.25 0.6	0.55	0.77*	100	4.5				10	1	04
BC548A	TO-92 (97)	30	20	5	10	125	260*	0.25 0.6	0.55	0.77*	100	4.5				10	1	04
BC548B	TO-92 (97)	30	20	5	10	240	500*	0.25 0.6	0.55	0.77*	100	4.5				10	1	04
BC548C	TO-92 (97)	30	20	5	10	450	900*	0.25 0.6	0.55	0.77*	100	4.5				10	1	04
BC549	TO-92 (97)	30	20	5	10	240	900*	0.25 0.6	0.55	0.77*	100	4.5				4	1	04
BC549B	TO-92 (97)	30	20	5	10	240	500*	0.25 0.6	0.55	0.77*	100	4.5				4	1	04
BC549C	TO-92 (97)	30	20	5	10	450	900*	0.25 0.6	0.55	0.77*	100	4.5				4	1	04
BC550	TO-92 (97)	50	45	5	10	240	900*	0.25 0.6	0.55	0.77*	100					3	1	04
BC550B	TO-92 (97)	50	45	5	10	240	500*	0.25 0.6	0.55	0.77*	100					3	1	04
BC550C	TO-92 (97)	50	45	5	10	450	900*	0.25 0.6	0.55	0.77*	100					3	1	04
BC557	TO-92 (97)	50	45	5	100	75	260*	0.3 0.65	0.6	0.82*	100					10	1	71

6501130 NATL SEMICOND, (DISCRETE)

28C 35524

T-29-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> * VCBO (V) Min	V <sub>CEO</sub> (V) Min	V <sub>EB0</sub> (V) Min	I <sub>CE</sub> * I <sub>CB0</sub> (mA) Max	HFE h <sub>FE</sub> 1 kHz*	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)*</sub> (V) Min Max	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC557A	TO-92 (97)	50	45	5	100	20	0.3 0.65	0.82* 0.6 0.75* 2	10 100					10	1	71
BC557B	TO-92 (97)	50	45	5	100	20	0.3 0.65	0.82* 0.6 0.75* 2	10 100					10	1	71
BC558	TO-92 (97)	30	25	5	100	20	0.3 0.65	0.82* 0.6 0.75* 2	10 100					10	1	71
BC558A	TO-92 (97)	30	25	5	100	20	0.3 0.65	0.82* 0.6 0.75* 2	10 100					10	1	71
BC558B	TO-92 (97)	30	25	5	100	20	0.3 0.65	0.82* 0.6 0.75* 2	10 100					10	1	71
BC558C	TO-92 (97)	30	25	5	100	20	0.3 0.65	0.82* 0.6 0.75* 2	10 100					10	1	71
BC559	TO-92 (97)	25	20	5	100	20	0.3 0.65	0.82* 0.6 0.75* 2	10 100					4	1	71
BC559A	TO-92 (97)	25	20	5	100	20	0.3 0.65	0.82* 0.6 0.75* 2	10 100					4	1	71
BC559B	TO-92 (97)	25	20	5	100	20	0.3 0.65	0.82* 0.6 0.75* 2	10 100					4	1	71
BC559C	TO-92 (97)	25	20	5	100	20	0.3 0.65	0.82* 0.6 0.75* 2	10 100					4	1	71
BC560	TO-92 (97)	50	45	5	100	45	0.3 0.65	0.82* 0.6 0.75* 2	10 100					2	1	71

TEST CONDITIONS:

(1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CC</sub> = 20V, I<sub>B</sub> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CC</sub> = 10V, I<sub>B</sub> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CC</sub> = 3V, I<sub>B</sub> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CC</sub> = 6V, I<sub>B</sub> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35525

D

T-29-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE0</sub> <sup>*</sup> (V) Min	V <sub>CE0</sub> <sup>*</sup> (V) Max	V <sub>BE0</sub> (V) Min	V <sub>BE0</sub> (V) Max	I <sub>CE0</sub> <sup>*</sup> (mA) Max	I <sub>CE0</sub> <sup>*</sup> (mA) Min	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> (V) Min	V <sub>BE(SAT)</sub> (V) Max	I <sub>C</sub> (mA) Min	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	f <sub>T</sub> (MHz) Max	I <sub>C</sub> (mA) Min	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC560A	TO-92 (97)	45	100	5	45	100	100	0.3 0.65	0.82* 0.75* 2	0.82* 0.75* 2	2	100							2	1	71
BC560B	TO-92 (97)	45	100	5	45	100	100	0.3 0.65	0.82* 0.75* 2	0.82* 0.75* 2	2	100							2	1	71
BC560C	TO-92 (97)	45	100	5	45	100	100	0.3 0.65	0.82* 0.75* 2	0.82* 0.75* 2	2	100							2	1	71
BCX58	TO-92 (97)	32	10	7	32	10	100				2	100		125					6	3/4	04
BCX58-7	TO-92 (97)	32	10	7	32	10	100				2	100		125					6	3/4	04
BCX58-8	TO-92 (97)	32	10	7	32	10	100				2	100		125					6	3/4	04
BCX58-9	TO-92 (97)	32	10	7	32	10	100				2	100		125					6	3/4	04
BCX58-10	TO-92 (97)	32	10	7	32	10	100				2	100		125					6	3/4	04
BCX59	TO-92 (97)	45	100	7	45	100	100	0.5	1.0	1.0	2	100		125						5	04
BCX59-7	TO-92 (97)	45	100	7	45	100	100	0.5	1.0	1.0	2	100		125						5	04
BCX59-8	TO-92 (97)	45	100	7	45	100	100	0.5	1.0	1.0	2	100		125						5	04
BCX59-9	TO-92 (97)	45	100	7	45	100	100	0.5	1.0	1.0	2	100		125						5	04

6501130 NATL SEMICOND, (DISCRETE)

28C 35526

D

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> (V) Min	V <sub>CEO</sub> (V) Min	V <sub>EB</sub> (V) Min	I <sub>CE</sub> <sup>*</sup> I <sub>CB</sub> (mA) Max	H <sub>FE</sub> I <sub>FE</sub> 1 kHz <sup>*</sup> Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) (V)	V <sub>CE</sub> (SAT) (V) Max	V <sub>BE</sub> (SAT) (V) Min Max	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BCX59-10	TO-92 (97)		45	7		100 380 240 60	0.01 2 10 100	0.5	1.0	100		125	800		5	04
BCX78	TO-92 (97)		32	5		120 80 40	2 10 100	0.6	1.0	100						71
BCX78-7	TO-92 (97)		32	5		120 80 40	2 10 100	0.6	1.0	100						71
BCX78-8	TO-92 (97)		32	5		30 180 120 45	0.01 2 10 100	0.6	1.0	100						71
BCX78-9	TO-92 (97)		32	5		40 250 160 60	0.01 2 10 100	0.6	1.0	100						71
BCX78-10	TO-92 (97)		32	5		100 380 240 60	0.01 2 10 100	0.6	1.0	100						71
BCX79	TO-92 (97)		45	5		80 40	10 100	0.6	1.0	100						71
BCX79-7	TO-92 (97)		45	5		120 60	2 100	0.6	1.0	100						71
BCX79-8	TO-92 (97)		45	5		120 45 30 180	2 100 0.01 2	0.6	1.0	100						71
BCX79-9	TO-92 (97)		45	5		160 60 40 250	10 100 0.01 2	0.6	1.0	100						71

T-29-01

TEST CONDITIONS:

(1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub> = I<sub>C</sub> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub> = I<sub>C</sub> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub> = I<sub>C</sub> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub> = I<sub>C</sub> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

5

Pro Electron Series

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35527 D

T-29-01

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE</sub> <sup>+</sup> V <sub>CB</sub> (V) Min	V <sub>CE0</sub> <sup>+</sup> (V) Min	V <sub>EBO</sub> (V) Min	I <sub>CS</sub> <sup>+</sup> I <sub>CS0</sub> (mA) Max	V <sub>CB</sub> (V) Max	HFE h <sub>FE</sub> 1 kHz* Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) (V) Min Max	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) Min Max	I <sub>C</sub> (mA) Min Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.	
BCX79-10	TO-92 (97)		45	5			240 60 100 380	1000 100 0.01 630	1 1 5 5	0.6	1.0 100							71	
BCY56	TO-18	45	45	5	100	20	40 100 125 40	10 2 500* 0.01	5 5 2 5	0.6 0.7*	2					5	1	04	
BCY57	TO-18	25	20	5	100	20	200 200 240 100	10 5 2 0.01	5 5 5 5	0.6 0.7*	2					5	1	04	
BCY58	TO-18		32	7	10 <sup>†</sup>	32	40 80 125	100 10 700*	1 1 2	0.35 0.7	0.85 1.2 100 2	6	125	10	800		6	4/1	04
BCY58-7	TO-18		32	7	10 <sup>†</sup>	32	40 80 175	100 10 350*	1 1 2	0.35 0.7	0.85 1.2 100 2	6	125	10	800		6	4/1	04
BCY58-8	TO-18		32	7	10 <sup>†</sup>	32	40 80	100 10	1 1	0.35 0.7	0.85 1.2 100	6	125	10	800		6	4/1	04
BCY58-9	TO-18		32	7	10 <sup>†</sup>	32	40 80 250	100 10 500*	1 1 2	0.35 0.7	0.85 1.2 100 2	6	125	10	800		6	4/1	04
BCY58-10	TO-18		32	7	10 <sup>†</sup>	32	40 80 350	100 10 700*	1 1 2	0.35 0.7	0.85 1.2 100 2	6	125	10	800		6	4/1	04
BCY59	TO-18		45	7	10 <sup>†</sup>	45	40 80 125	100 10 700*	1 1 2	0.35 0.7	0.85 1.2 100 2	6	125	10	800		6	4/1	04
BCY59-7	TO-18		45	7	10 <sup>†</sup>	45	40 80 125	100 10 250*	1 1 2	0.35 0.7	0.85 1.2 100 2	6	125	10	800		6	4/1	04
BCY59-8	TO-18		45	7	10 <sup>†</sup>	45	40 80 175	100 10 350*	1 1 2	0.35 0.7	0.85 1.2 100 2	6	125	10	800		6	4/1	04
BCY59-9	TO-18		45	7	10 <sup>†</sup>	45	40 80 250	100 10 500*	1 1 2	0.35 0.7	0.85 1.2 100 2	6	125	10	800		6	4/1	04

6501130 NATL SEMICOND, (DISCRETE)

28C 35528



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	VCES* VCBO (V) Min	VCEO (V) Min	VEBO (V) Min	ICES* ICBO (mA) Max	HFE h <sub>FE</sub> 1 kHz* e Min Max	IC & VCE (mA) (V)	VCE(SAT) (V) Max	VBE(SAT) & VBE(ON)* e (V) Min Max		Cob (pF) Max	f <sub>T</sub> (MHz) Min Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
									Max	Min						
BCY59-10	TO-18		45	7	10†	40 80 350	100 10 700*	0.35 0.7	0.6 0.75 0.55	0.85 1.2 0.7*	6	125	800	6	4/1	04
BCY70	TO-18		40	5	10	40 45 50 15	0.1 1 10 50	0.25	0.6 0.9	10 10 1	6	250	420	6	5/6	71
BCY71	TO-18	45	45	5	500	40 80 90 100	0.01 0.1 1 600	0.25	0.6 0.9	10 10 50	6	200		2	6	71
BCY71A	TO-18	45	45	5	500	40 80 90 100	0.01 0.1 1 600	0.25	0.6 0.9	10 10 50	6	300	420	2	6	71
BCY72	TO-18	25	25	5	500	40	1	0.25	1.2	50	6	200	420	6	5/6	71
BD135	TO-126	45	45	5	100	25	500	0.5	1.2	50		50	420	6	5/6	37
BD135-6	TO-126	45	45	5	100	40	150	0.5	1.0*	500		50	420	6	5/6	37
BD135-10	TO-126	45	45	5	100	63	150	0.5		500		50				37
BD135-16	TO-126	45	45	5	100	100	250	0.5		500		50				37
BD136	TO-126	45	45	5	100	40	250	0.5		500		50				77
BD136-6	TO-126	45	45	5	100	40	150	0.5		500		50				77
BD136-10	TO-126	45	45	5	100	63	150	0.5		500		50				77
BD136-16	TO-126	45	45	5	100	100	250	0.5		500		50				77
BD137	TO-126	60	60	5	100	40	150	0.5		500		50				38

7-33-01

TEST CONDITIONS:

(1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CC</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CC</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CC</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CC</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

D

Pro Electron Series

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35529 D

T-33-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> (V) Min	V <sub>CEO</sub> (V) Min	V <sub>EBO</sub> (V) Min	I <sub>CE</sub> <sup>*</sup> I <sub>CB</sub> (mA) Max	V <sub>CB</sub> (V) Min	H <sub>FE</sub> h <sub>FE</sub> 1 kHz <sup>*</sup> Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V) Min Max	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> (V) Min	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD137-6	TO-126	60	60	5	100	30	40 100 25 500	150 2 500 2	0.5		500		50	50				38
BD137-10	TO-126	60	60	5	100	30	63 160 25 500	150 2 500 2	0.5		500		50	50				38
BD138	TO-126	60	60	5	100	30	40 160 25 500	150 2 500 2	0.5		500		50	50				78
BD138-6	TO-126	60	60	5	100	30	40 100 25 500	150 2 500 2	0.5		500		50	50				78
BD138-10	TO-126	60	60	5	100	30	63 160 25 500	150 2 500 2	0.5		500		50	50				78
BD139	TO-126	80	80	5	100	30	25 500 40 160	500 2 50 2	0.5	1.0*	500		50	50	420	6	5/6	39
BD139-6	TO-126	80	80	5	100	30	25 500 40 100	500 2 2	0.5	1.0*	500		50	50				39
BD139-10	TO-126	80	80	5	100	30	25 500 40 160	500 2 50 2	0.5	1.0*	500		50	50				39
BD140	TO-126	80	80	5	100	30	25 500 40 160	500 2 50 2	0.5	1.0*	500		50	50	420	6	5/6	79
BD157	TO-126		250		100	275	30 240	50 10										36
BD158	TO-126		300		100	325	30 240	50 10										36
BD159	TO-126		350		100	325	30 240	50 10										36
BD185	TO-126		30		100	40	40 500 15 2A	2 2	1.0	1.2*	2A							4F
BD186	TO-126		30		100	40	40 500 15 2A	2 2	1.0	1.5*	2A							5F
BD187	TO-126		45		100	55	40 500 15 2A	2 2	1.0	1.5*	2A							4F
BD188	TO-126		45		100	55	40 500 15 2A	2 2	1.0	1.5*	2A							5F
BD189	TO-126		60		100	70	40 500 15 2A	2 2	1.0	1.5*	2A							4F
BD190	TO-126		60		100	70	40 500 15 2A	2 2	1.0	1.5*	2A							5F
BD201	TO-220	60	45	5	10	40	30 3A 30 1A 75 235	2 2 2 2 500 1	1.0	1.5*	3A		3	300	420	6	5/6	4A
BD202	TO-220	60	45	5	10	40	30 3A 30 1A 75 235	2 2 2 2 500 1	1.0	1.5*	3A		3	300	420	6	5/6	5A

6501130 NATL SEMICOND, (DISCRETE)

28C 35530

D

T-33-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> * V <sub>CB</sub> (V) Min	V <sub>CE</sub> (V) Min	V <sub>EB</sub> (V) Min	I <sub>CB</sub> * (mA) Max	H <sub>FE</sub> h <sub>FE</sub> 1 kHz* Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) (V)	V <sub>CE</sub> (SAT) (V) Max	V <sub>BE</sub> (SAT) & V <sub>BE</sub> (ON)* (V) Min Max	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD203	TO-220	60	60	5		30 30	2 1 2	1.0		3A		3	300				4A
BD204	TO-220	60	60	5	10 μA	30 30	2A 1A 1	1.0	1.5*	3A							5A
BD220	TO-220	70	70			30 30	120 1A 4	1.0	1.1*	500							4F
BD221	TO-220	40	40			30 30	120 1A 4	1.0	1.3*	1A							4F
BD222	TO-220	60	60			20 20	80 1.5A 4	1.0	1.5*	1.5A							4F
BD223	TO-220	70	70			30 30	120 300 4	1.0	1.1*	500							5F
BD224	TO-220	40	40			30 30	120 1A 4	1.0	1.3*	1A							5F
BD225	TO-220	60	60			20 20	80 1.5A 4	1.0	1.5*	1.5A							5F
BD233	TO-126	45	45		100 μA	25 40	1A 150 2	0.6	1.3*	1A		3	250	420	6	5/6	4F
BD234	TO-126	45	45		100 μA	25 40	1A 150 2	0.6	1.3*	1A		3	250	420	6	5/6	5F
BD235	TO-126	60	60		100 μA	25 40	1A 150 2	0.6	1.3*	1A		3	250	420	6	5/6	4F
BD236	TO-126	60	60		100 μA	25 40	1A 150 2	0.6	1.3*	1A		3	250	420	6	5/6	5F
BD237	TO-126	80	80		100 μA	25 40	1A 150 2	0.6	1.3*	1A		3	250	420	6	5/6	4F
BD238	TO-126	80	80		100 μA	25 40	1A 150 2	0.6	1.3*	1A		3	250	420	6	5/6	5F
BD239	TO-220	45	45		200 μA*	15 40	1A 200 4	0.7	1.3*	1A		3	200	420	6	5/6	4F
BD239A	TO-220	60	60		200 μA*	15 40	1A 200 4	0.7	1.3*	1A		3	200	420	6	5/6	4F
BD239B	TO-220	80	80		200 μA*	15 40	1A 200 4	0.7	1.3*	1A		3	200	420	6	5/6	4F
BD239C	TO-220	100	100		200 μA*	15 40	1A 200 4	0.7	1.3*	1A		3	200	420	6	5/6	4F
BD240	TO-220	45	45		200 μA*	15 40	1A 200 4	0.7	1.3*	1A		3	200	420	6	5/6	5F
BD240A	TO-220	80	80		200 μA*	15 40	1A 200 4	0.7	1.3*	1A		3	200	420	6	5/6	5F

TEST CONDITIONS:

(1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35531 D

T-33-01

Pro Electron Series

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> <sup>*</sup> (V) Min	V <sub>CE</sub> <sup>*</sup> (V) Min	V <sub>EB</sub> <sup>*</sup> (V) Min	I <sub>CB</sub> <sup>*</sup> I <sub>BO</sub> <sup>*</sup> (mA) Max	HFE h <sub>FE</sub> 1 kHz Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V) Min Max	V <sub>CE(SAT)</sub> (V) & V <sub>BE(ON)</sub> (V) Max Min	I <sub>C</sub> (mA) Min Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD240B	TO-220	80	80		200 μA* 80	15 40	1A 4 200 4	0.7 1.3* 1A	200		3	420	6	5/6	5F
BD240C	TO-220	80	100		200 μA* 100	15 40	1A 4 200 4	0.7 1.3* 1A	200		3	420	6	5/6	5F
BD241	TO-220	80	45		200 μA* 45	10 25	3A 4 1A 4	1.3 1.8* 3A	500		3	420	6	5/6	4F
BD241A	TO-220	80	60		200 μA* 60	10 25	3A 4 1A 4	1.3 1.8* 3A	500		3	420	6	5/6	4F
BD241B	TO-220	80	80		200 μA* 80	10 25	3A 4 1A 4	1.3 1.8* 3A	500		3	420	6	5/6	4F
BD241C	TO-220	80	100		200 μA* 100	10 25	3A 4 1A 4	1.3 1.8* 3A	500		3	420	6	5/6	4F
BD242	TO-220	80	45		200 μA* 45	10 25	3A 4 1A 4	1.2 1.8* 3A	500		3	420	6	5/6	5E
BD242A	TO-220	80	60		200 μA* 60	10 25	3A 4 1A 4	1.2 1.8* 3A	500		3	420	6	5/6	5E
BD242B	TO-220	80	80		200 μA* 80	10 25	3A 4 1A 4	1.2 1.8* 3A	500		3	420	6	5/6	5E
BD242C	TO-220	80	100		200 μA* 100	10 25	3A 4 1A 4	1.2 1.8* 3A	500		3	420	6	5/6	5E
BD243	TO-220		45		400 μA* 45	30 15	300 4 3A 4		500		3				4A
BD243A	TO-220		60		400 μA* 60	30 15	300 4 3A 4		500		3				4A
BD243B	TO-220		80		400 μA* 80	30 15	300 4 3A 4		500		3				4A
BD243C	TO-220		100		400 μA* 100	30 15	300 4 3A 4		500		3				4A
BD244	TO-220		45		400 μA* 45	30 15	300 4 3A 4								4A
BD244A	TO-220		60		400 μA* 60	30 15	300 4 3A 4								5A
BD244B	TO-220		80		400 μA* 80	30 15	300 4 3A 4		500		3				5A
BD244C	TO-220		100		400 μA* 100	30 15	300 4 3A 4		500		3				5A
BD344	TO-126	60	60	5	500 60	60 40	50 1 200 1	0.4	50	20	50				78

6501130 NATL SEMICOND, (DISCRETE)

28C 35532

D Pro Electron Series



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CE0</sub> (V) Min	V <sub>BE0</sub> (V) Min	I <sub>CE</sub> <sup>*</sup> I <sub>CE0</sub> (mA) Max	HFE h <sub>FE</sub> 1 kHz <sup>*</sup> Min	I <sub>C</sub> & V <sub>CE</sub> (mA) (V) Max	V <sub>CE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) (V) Max Min		I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max		t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
							V <sub>CE(SAT)</sub> Max	V <sub>BE(ON)</sub> Min			f <sub>T</sub> Min	f <sub>T</sub> Max				
BD345	TO-126	60	5	500	60	50	0.4	200	20	50	50				38	
BD346	TO-220	60		10 μA	40	140			200	4	250				5A	
BD347	TO-220	60		10 μA	40	140			200	4	250				4A	
BD348	TO-126	80	5	500	60	100	0.5	250	17	50	50				79	
BD349	TO-126	80		500	50	250	0.5	250	15	50	50				39	
BD370A	TO-237 (91)	45		100	25	500	0.7	1A	30	50	200	420	6	5/6	78	
BD370A-10	TO-237 (91)	80		100	25	500	0.7	1A	30	50	200	420	6	5/6	78	
BD370A-16	TO-237 (91)	80		100	25	500	0.7	1A	30	50	200	420	6	5/6	78	
BD370A-25	TO-237 (91)	80		100	25	500	0.7	1A	30	50	200	420	6	5/6	78	
BD370B	TO-237 (91)	60		100	40	400	0.7	1A	30	50	200	420	6	5/6	78	
BD370B-10	TO-237 (91)	80		100	25	500	0.7	1A	30	50	200	420	6	5/6	78	
BD370B-16	TO-237 (91)	80		100	25	500	0.7	1A	30	50	200	420	6	5/6	78	
BD370B-25	TO-237 (91)	80		100	25	500	0.7	1A	30	50	200	420	6	5/6	78	
BD370C	TO-237 (91)	80		100	63	160	0.7	1A	30	50	200	420	6	5/6	78	
BD370C-6	TO-237 (91)	80		100	25	500	0.7	1A	30	50	200	420	6	5/6	78	
BD370C-10	TO-237 (91)	80		100	25	500	0.7	1A	30	50	200	420	6	5/6	78	
BD370C-16	TO-237 (91)	80		100	25	500	0.7	1A	30	50	200	420	6	5/6	78	

T-33-01

TEST CONDITIONS:  
 (1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35533 D

T-33-01

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> (V) Min	V <sub>CE</sub> <sup>*</sup> (V) Min	V <sub>EB</sub> (V) Min	I <sub>CB</sub> <sup>*</sup> (mA) Max	HFE h <sub>FE</sub> 1 kHz Min	HFE h <sub>FE</sub> 1 kHz Max	I <sub>C</sub> & V <sub>CE</sub> (mA) (V)	V <sub>CE</sub> (SAT) & V <sub>BE</sub> (ON) <sup>*</sup> (V)		I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz)		t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
									Max	Min			Min	Max				
BD370D	TO-237 (91)	80	100		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	79
BD370D-6	TO-237 (91)	80	100		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	79
BD370D-10	TO-237 (91)	80	100		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	79
BD371A	TO-237 (91)	80	45		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371A-10	TO-237 (91)	80	45		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371A-16	TO-237 (91)	80	45		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371A-25	TO-237 (91)	80	45		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371B	TO-237 (91)	80	60		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371B-10	TO-237 (91)	80	60		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371B-16	TO-237 (91)	80	60		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371B-25	TO-237 (91)	80	60		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371C	TO-237 (91)	80	80		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371C-6	TO-237 (91)	80	80		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371C-10	TO-237 (91)	80	80		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371C-16	TO-237 (91)	80	80		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371D	TO-237 (91)	80	100		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	39
BD371D-6	TO-237 (91)	80	100		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	39
BD371D-10	TO-237 (91)	80	100		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	39
BD372A	TO-237 (90)	80	45		100	25	500	2	0.7	1.2*	1A	30	50	200	420	6	5/6	78

6501130 NATL SEMICOND, (DISCRETE)

28C 35534

T-33-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> (V) Min	V <sub>CE</sub> (V) Min	V <sub>EB</sub> (V) Min	I <sub>CS</sub> <sup>*</sup> I <sub>CB</sub> (mA) Max	H <sub>FE</sub> h <sub>FE</sub> @ 1 kHz Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V) Min Max	V <sub>CE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) & (V) Max Min	I <sub>C</sub> @ (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	I <sub>C</sub> @ (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD372A-10	TO-237 (90)	80	45		100	25 63	500 2 100 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372A-16	TO-237 (90)	80	45		100	25 100	500 2 250 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372A-25	TO-237 (90)	80	45		100	25 160	500 2 400 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372B	TO-237 (90)	80	60		100	25 40	500 2 400 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372B-10	TO-237 (90)	80	60		100	25 63	500 2 160 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372B-16	TO-237 (90)	80	60		100	25 100	500 2 250 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372B-25	TO-237 (90)	80	60		100	25 160	500 2 400 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372C	TO-237 (90)	80	80		100	25 40	500 2 400 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372C-6	TO-237 (90)	80	80		100	25 40	500 2 100 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372C-10	TO-237 (90)	80	80		100	25 63	500 2 160 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372C-16	TO-237 (90)	80	100		100	25 100	500 2 250 1	0.7 1.2*	1A	30	50	200	420	6	5/6	78
BD372D	TO-237 (90)	80	100		100	25 40	500 2 400 1	0.7 1.2*	1A	30	50	200	420	6	5/6	79
BD372D-6	TO-237 (90)	80	100		100	25 40	500 2 100 1	0.7 1.2*	1A	30	50	200	420	6	5/6	79
BD372D-10	TO-237 (90)	80	100		100	25 63	500 2 160 1	0.7 1.2*	1A	30	50	200	420	6	5/6	79
BD373A	TO-237 (90)	80	45		100	25 40	500 2 400 1	0.7 1.2*	1A	30	50	200	420	6	5/6	38
BD373A-10	TO-237 (90)	80	45		100	25 63	500 2 160 1	0.7 1.2*	1A	30	50	200	420	6	5/6	38
BD373A-16	TO-237 (90)	80	45		100	25 100	500 2 250 1	0.7 1.2*	1A	30	50	200	420	6	5/6	38

TEST CONDITIONS:

(1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = 100 kHz.



Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35535 D

Pro Electron Series

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE</sub> * V <sub>CB0</sub> (V) Min	V <sub>CE0</sub> (V) Min	V <sub>EB0</sub> (V) Min	ICES* IC <sub>BO</sub> @ (mA) Max	HFE h <sub>FE</sub> 1 kHz* Min	HFE h <sub>FE</sub> 1 kHz* Max	IC & V <sub>CE</sub> (mA) & (V) Max	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> * (V) Min	IC (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	f <sub>T</sub> (MHz) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD373A-25	TO-237 (90)	80	45		100	25	160	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD373B	TO-237 (90)	80	80		100	25	40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD373B-10	TO-237 (90)	80	60		100	25	63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/8	38
BD373B-16	TO-237 (90)	80	60		100	25	100	500 2 250 1	0.7	1.2*	1A	30	50	200	420	6	5/8	38
BD373B-25	TO-237 (90)	80	60		100	25	160	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD373C	TO-237 (90)	80	80		100	25	40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD373C-6	TO-237 (90)	80	80		100	25	40	500 2 100 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD373C-10	TO-237 (90)	80	80		100	25	63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD373C-16	TO-237 (90)	80	80		100	25	100	500 2 250 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD373D	TO-237 (90)	80	100		100	25	40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	39
BD373D-6	TO-237 (90)	80	100		100	25	40	500 2 100 1	0.7	1.2*	1A	30	50	200	420	6	5/6	39
BD373D-10	TO-237 (90)	80	100		100	25	63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/6	39
BD375	TO-126	50	45		2 μA	20	40	1A 2 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38
BD375-6	TO-126	50	45		2 μA	20	40	1A 2 100 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38
BD375-10	TO-126	50	45		2 μA	20	63	1A 2 160 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38
BD375-16	TO-126	50	45		2 μA	20	100	1A 2 250 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38
BD375-25	TO-126	50	45		2 μA	20	150	1A 2 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38
BD376	TO-126	50	45		2 μA	20	40	1A 2 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78
BD376-6	TO-126	50	45		2 μA	20	40	1A 2 100 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78

T-33-01

6501130 NATL SEMICOND, (DISCRETE)

28C 35536

D

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> (V) Min	V <sub>CE</sub> (V) Min	V <sub>EBO</sub> (V) Min	I <sub>CB</sub> <sup>*</sup> (nA) Max	HFE h <sub>fe</sub> 1 kHz <sup>*</sup> Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) (V)	V <sub>CE</sub> (SAT) & V <sub>BE</sub> (ON) <sup>*</sup> (V)		C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz)		t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.	
								Max	Min		Max	Min					
BD376-10	TO-126	50	45		2 μA	20 63	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	78
BD376-16	TO-126	50	45		2 μA	20 100	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	78
BD376-25	TO-126	50	45		2 μA	20 150	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	78
BD377	TO-126	75	60		2 μA	20 40	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	38
BD377-6	TO-126	75	60		2 μA	20 40	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	38
BD377-10	TO-126	75	60		2 μA	20 63	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	38
BD377-16	TO-126	75	60		2 μA	20 100	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	38
BD377-25	TO-126	75	60		2 μA	20 150	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	38
BD378	TO-126	75	60		2 μA	20 40	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	78
BD378-6	TO-126	75	60		2 μA	20 40	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	78
BD378-10	TO-126	75	60		2 μA	20 63	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	78
BD378-16	TO-126	75	60		2 μA	20 100	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	78
BD378-25	TO-126	75	60		2 μA	20 150	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	78
BD379	TO-126	100	80		2 μA	20 40	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	39
BD379-6	TO-126	100	80		2 μA	20 40	1A 150	2 2	1.0	1.5*	30	50	200	420	6	5/6	39

T-33-01

TEST CONDITIONS:  
 (1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

Pro Electron Series

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35537 D

T-33-01

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE0</sub> <sup>*</sup> (V) Min	V <sub>CE0</sub> <sup>*</sup> (V) Min	V <sub>EB0</sub> (V) Min	I <sub>CB0</sub> <sup>*</sup> (mA) Max	V <sub>CB</sub> (V)	H <sub>FE</sub> h <sub>FE</sub> 1 kHz <sup>*</sup> Min	H <sub>FE</sub> h <sub>FE</sub> 1 kHz <sup>*</sup> Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V) Min	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) Min	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	f <sub>T</sub> (MHz) Max	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD379-10	TO-126	100	80		2 μA	80	20	160	1A 2	1.0	1.5*	1A	30	50	200	420		6	5/6	39
BD379-16	TO-126	100	80		2 μA	80	20	250	1A 2	1.0	1.5*	1A	30	50	200	420		6	5/6	39
BD379-25	TO-126	100	80		2 μA	80	20	375	1A 2	1.0	1.5*	1A	30	50	200	420		6	5/6	39
BD380	TO-126	100	80		2 μA	80	20	375	1A 2	1.0	1.5*	1A	30	50	200	420		6	5/6	79
BD380-6	TO-126	100	80		2 μA	80	20	100	1A 2	1.0	1.5*	1A	30	50	200	420		6	5/6	79
BD380-10	TO-126	100	80		2 μA	80	20	160	1A 2	1.0	1.5*	1A	30	50	200	420		6	5/6	79
BD380-16	TO-126	100	80		2 μA	80	20	250	1A 2	1.0	1.5*	1A	30	50	200	420		6	5/6	79
BD380-25	TO-126	100	80		2 μA	80	20	375	1A 2	1.0	1.5*	1A	30	50	200	420		6	5/6	79
BD433	TO-126	22†	22	5	100 μA	22	50	475	2A 1	0.5	1.1*	2A		3	250	420		6	5/6	4E
BD434	TO-126	22†	22	5	100 μA	22	50	475	2A 1	0.5	1.1*	2A	30	3	250	420		6	5/6	5E
BD435	TO-126	32†	32	5	100 μA	32	50	475	2A 1	0.5	1.1*	2A	30	3	250	420		6	5/6	4E
BD436	TO-126	32†	32	5	100 μA	32	50	475	2A 1	0.5	1.1*	2A	30	3	250	420		6	5/6	5E
BD437	TO-126	46†	45	5	100 μA	45	40	236	2A 1	0.6	1.2*	2A	30	3	250	420		6	5/6	4E
BD438	TO-126	46†	45	5	100 μA	45	40	236	2A 1	0.6	1.2*	2A	30	3	250	420		6	5/6	5E
BD439	TO-126	60†	60	5	100 μA	60	25	236	2A 1	0.8	1.5*	2A	30	3	250	420		6	5/6	4E

6501130 NATL SEMICOND, (DISCRETE)

28C 35538

T-33-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB0</sub> (V) Min	V <sub>CEO</sub> (V) Min	V <sub>EB0</sub> (V) Min	I <sub>CB0</sub> <sup>*</sup> (mA) Max	V <sub>CB</sub> (V) Max	H <sub>FE</sub> h <sub>FE</sub> 1 kHz <sup>*</sup> Min	H <sub>FE</sub> h <sub>FE</sub> 1 kHz <sup>*</sup> Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V) Min	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) Min	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	f <sub>T</sub> (MHz) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD440	TO-126	60†	60	5	100 μA	60	25 40 40	2A 500 10	1 5	0.8	1.5*	2A	80	3	250	420	6	5/6	5E
BD441	TO-126	80†	80	5	100 μA	80	15 40 15	2A 500 10	1 5	0.8	1.5*	2A	30	3	250	420	6	5/6	4E
BD442	TO-126	80†	80	5	100 μA	80	15 40 15	2A 500 10	1 5	0.8	1.5*	2A	30	3	250	420	6	5/6	5E
BD533	TO-220	80†	45	5	100 μA	45	25 40 20	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	4E
BD534	TO-220	80†	45	5	100 μA	45	25 40 20	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	5E
BD535	TO-220	80†	60	5	100 μA	60	25 40 20	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	4E
BD536	TO-220	80†	60	5	100 μA	60	25 40 20	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	5E
BD537	TO-220	80†	80	5	100 μA	80	15 40 15	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	4E
BD538	TO-220	80†	80	5	100 μA	80	15 40 15	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	5E
BD633	TO-220	45	45	5	200 μA†	45	25 40	1A 25	2 2	0.6	1.3*	1A	30	3	250	420	6	5/6	4F
BD634	TO-220	45	45	5	200 μA†	45	25 40	1A 25	2 2	0.6	1.3*	1A	30	3	250	420	6	5/6	5F
BD635	TO-220	60	60	5	200 μA†	60	25 40	1A 25	2 2	0.6	1.3*	1A	30	3	250	420	6	5/6	4F

TEST CONDITIONS:  
 (1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V.  
 I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 μA.  
 V<sub>CE</sub> = 5V, f = WB.

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35539 D

T-33-01

Pro Electron Series

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> (V) Min	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> (V) Min	V <sub>EB</sub> (V) Min	I <sub>CB</sub> <sup>*</sup> I <sub>BO</sub> (mA) Max	V <sub>CB</sub> (V) Min	HFE h <sub>FE</sub> 1 kHz <sup>*</sup> Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V) Min Max	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> (V) Min	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	I <sub>C</sub> (mA) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD636	TO-220	60	60	5	200 μA†	60	25 40	1A 25	0.6	1.3*	1A	30	3	250	420	6	5/6	5F
BD637	TO-220	100	80	5	200 μA†	100	25 40	1A 25	0.6	1.3*	1A	30	3	250	420	6	5/6	4F
BD638	TO-220	100	80	5	200 μA†	100	25 40	1A 25	0.6	1.3	1A	30	3	250	420	6	5/6	5F
BD675	TO-126	45	45		200 μA	45	750	1.5A 3	2.5	2.5*	1.5A		1	1.5A				4J
BD675A	TO-126	45	45		200 μA	45	750	2A 3	2.8	2.5*	2A		1	1.5A				4J
BD676	TO-126	45	45		200 μA	45	750	1.5A 3V	2.5	2.5*	1.5A		1	1.5A				5J
BD676A	TO-126	45	45		200 μA	45	750	2A 3V	2.8	2.5*	2A		1	1.5A				5J
BD677	TO-126	60	60		200 μA	60	750	1.5A 3V	2.5	2.5*	1.5A		1	1.5A				4J
BD677A	TO-126	60	60		200 μA	60	750	2A 3V	2.8	2.5*	2A		1	1.5A				4J
BD678	TO-126	60	60		200 μA	60	750	1.5A 3V	2.5	2.5*	1.5A		1	1.5A				5J
BD678A	TO-126	60	60		200 μA	60	750	2A 3V	2.8	2.5*	2A		1	1.5A				5J
BD679	TO-126	80	80		200 μA	80	750	1.5A 3V	2.5	2.5*	1.5A		1	1.5A				4J
BD679A	TO-126	80	80		200 μA	80	750	2A 3V	2.8	2.5*	2A		1	1.5A				4J
BD680	TO-126	80	80		200 μA	80	750	1.5A 3V	2.5	2.5*	1.5A		1	1.5A				4J
BD680A	TO-126	80	80		200 μA	80	750	2A 3V	2.8	2.5*	2A		1	1.5A				4J
BD681	TO-126	100	100		200 μA	100	750	1.5A 3V	2.5	2.5*	1.5A		1	1.5A				5J
BD682	TO-126	100	100		200 μA	100	750	2A 3V	2.5	2.5*	1.5A		1	1.5A				5J
BD733	TO-220	25	25	5	200 μA†	25	50 40	2A 20	0.6	1.1*	2A		1	1.5A				4F
BD734	TO-220	25	25	5	200 μA†	25	50 40	2A 20	0.6	1.1*	2A		1	1.5A				5E
BD735	TO-220	35	35	5	200 μA†	35	40	2A 20	0.6	1.1*	2A		1	1.5A				4F
BD736	TO-220	35	35	5	200 μA†	35	40	2A 20	0.6	1.1*	2A		1	1.5A				5E
BD737	TO-220	45	45	5	200 μA†	45	40	2A 20	0.8	1.1*	2A		1	1.5A				4F
BD738	TO-220	45	45	5	200 μA†	45	40	2A 20	0.8	1.1*	2A		1	1.5A				5E
BD795	TO-220		45		100	45	40	2A 20	0.8	1.1*	2A		1	1.5A				4E
BD796	TO-220		45		100	45	25	1A 3A	1.0	1.6*	3A	3	3	250				5E
BD797	TO-220		60		100 μA	60	40 25	1A 3A	1.0	1.6*	3A	3	3	250				4E

6501130 NATL SEMICOND, (DISCRETE)

28C 35540

T-33-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> (V) Min	V <sub>CE0</sub> (V) Min	V <sub>EB0</sub> (V) Min	I <sub>CS</sub> <sup>*</sup> I <sub>CB0</sub> (mA) Max	h <sub>FE</sub> h <sub>FE</sub> @ 1 kHz <sup>*</sup> Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V) Min Max	V <sub>CE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) & (V) Min Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD798	TO-220		60		100 μA	40	1A 2	1.0 1.6*		3				5E
BD799	TO-220		80		100 μA	30	1A 2	1.0 1.6*		3				4E
BD800	TO-220		80		100 μA	15	3A 2	1.0 1.6*		3				5E
BD801	TO-220		100		100 μA	15	3A 2	1.0 1.6*		3				4E
BD802	TO-220		100		100 μA	30	1A 2	1.0 1.6*		3				5E
BD895	TO-220		45		200 μA	750	3A 3	2.5* 3A		1				4K
BD895A	TO-220		45		200 μA	45	4A 3	2.5* 4A		1				4K
BD896	TO-220		45		200 μA	750	3A 3	2.5* 3A		1				5K
BD896A	TO-220		45		200 μA	45	4A 3	2.5* 4A		1				5K
BD897	TO-220		60		200 μA	750	3A 3	2.5* 3A		1				4K
BD897A	TO-220		60		200 μA	45	4A 3	2.5* 4A		1				4K
BD898	TO-220		60		200 μA	750	3A 3	2.5* 3A		1				5K
BD898A	TO-220		60		200 μA	45	4A 3	2.5* 4A		1				5K
BD899	TO-220		80		200 μA	750	3A 3	2.5* 3A		1				4K
BD899A	TO-220		80		200 μA	45	4A 3	2.5* 4A		1				4K
BD900	TO-220		80		200 μA	750	3A 3	2.5* 3A		1				5K
BD900A	TO-220		80		200 μA	45	4A 3	2.5* 4A		1				5K
BD901	TO-220		100		200 μA	750	3A 3	2.5* 3A		1				4K
BD902	TO-220		100		200 μA	45	4A 3	2.5* 4A		1				4K
BDX33	TO-220		45		1 mA	750	4A 3	2.5* 4A		20				4K
BDX33A	TO-220		60		1 mA	45	4A 3	2.5* 4A		20				4K
BDX33B	TO-220		80		1 mA	750	3A 3	2.5* 3A		20				4K
BDX33C	TO-220		100		1 mA	45	4A 3	2.5* 4A		20				4K
BDX33D	TO-220		120		1 mA	750	3A 3	2.5* 3A		20				4K
BDX34	TO-220		45		1 mA	45	4A 3	2.5* 4A		20				5K
BDX34A	TO-220		60		1 mA	750	4A 3	2.5* 4A		20				5K
BDX34B	TO-220		80		1 mA	45	4A 3	2.5* 4A		20				5K

TEST CONDITIONS:  
 (1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

Pro Electron Series

5

6501130 NATL SEMICOND, (DISCRETE)

28C 35541 D

7-31-01

Pro Electron Series

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> (V) Min	V <sub>CE</sub> <sup>*</sup> V <sub>CB</sub> (V) Max	V <sub>BE</sub> (V) Min	V <sub>BE</sub> (V) Max	ICES <sup>*</sup> I <sub>CB</sub> (mA) Max	HFE h <sub>fe</sub> @ 1 kHz <sup>*</sup> Min Max	I <sub>C</sub> & V <sub>CE</sub> (mA) (V) Min Max	V <sub>CE</sub> (SAT) (V) & V <sub>BE</sub> (ON) <sup>*</sup> (V) (V) Min Max	I <sub>C</sub> (mA) Min Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BDX34C	TO-220	100	100	4	4	1 mA	750	3A 3	2.5*	3A		20				5K
BDX34D	TO-220	120	120	4	4	1 mA	750	3A 3	2.5*	3A		20				5K
BF167	TO-72 (28)	40	30	4	3	100†	26	4 10	0.84* 4							45
BF180	TO-72 (25)	30	20	3	3	100	13	2 10								41
BF181	TO-72 (25)	30	20	3	3	100	13	2 10								41
BF194	TO-92 (98)	Same as BF254, see page 5-33 for explanation														
BF195	TO-92 (98)	Same as BF255, see page 5-33 for explanation														
BF196	TO-92 (98)	Same as BF198, see below for explanation														
BF197	TO-92 (98)	Same as BF199, see below for explanation														
BF198	TO-92 (98)	40	30	4	4	100	26	4 10		0.88* 4						45
BF199	TO-92 (98)	40	25	4	4	100	36	7 10				1100 typ				47
BF200	TO-72 (25)	30	20	3	3	100	15	3 10								41
BF233-2	TO-92 (96)	30	30	4	4	100	40	1 10	0.65 0.74*	1	1.0	150				49
BF233-3	TO-92 (96)	30	30	4	4	100	60	1 10	0.65 0.74*	1	1.0	150				49
BF233-4	TO-92 (96)	30	30	4	4	100	90	1 10	0.65 0.74*	1	1.0	150				49
BF233-5	TO-92 (96)	30	30	4	4	100	140	1 10	0.65 0.74*	1	1.0	150				49
BF237	TO-92 (98)	45	30	4	4	100			0.25	10						47
BF238	TO-92 (98)	45	30	4	4	100			0.25	10						47
BF240	TO-92 (98)	40	40	4	4	100	67	1 10	0.65 0.74*	1	0.34			3.5	7	47
BF241	TO-92 (98)	40	40	4	4	100	36	1 10	0.65 0.74*	1	0.34			3.5	7	47

6501130 NATL SEMICOND, (DISCRETE)

28C 35542

D

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE</sub> (V)		V <sub>BE</sub> (V)	V <sub>BO</sub> (V)	I <sub>CB</sub> (mA)	h <sub>FE</sub> @ 1 kHz		I <sub>C</sub> & V <sub>CE</sub> (V)	V <sub>CE(SAT)</sub> (V)		V <sub>BE(SAT)</sub> (V)		C <sub>ob</sub> (pF)	f <sub>T</sub> (MHz)		I <sub>C</sub> (mA)	t <sub>off</sub> (ns)	NF (dB)	Test Conditions	Process No.
		Min	Max				Min	Max		Min	Max	Min	Max		Min	Max					
BF254	TO-92 (98)	30	20	5	20	100	67	220	1 10 6 7	0.65	0.74*	1	0.34				1		3.5	7	46
BF255	TO-92 (98)	30	20	5	20	100	36	125	1 10 6 7	0.65	0.74*	1	0.34				1		3.5	7	46
BF257	TO-39	100	100	5	100	50	25	30	30 10 6 7	1.0	0.65	0.74*	30	0.34			1		3.5	7	48
BF258	TO-39	250	250	5	200	50	25	30	30 10 6 7	1.0	0.65	0.74*	30	0.34			1		3.5	7	48
BF259	TO-39	300	300	5	250	50	25	30	30 10 6 7	1.0	0.65	0.74*	30	0.34			1		3.5	7	48
BF457	TO-126	100	100	5	100	50	25	30	30 10 6 7	1.0	0.65	0.74*	30	0.34			1		3.5	7	48
BF458	TO-126	250	200	5	200	50	25	30	30 10 6 7	1.0	0.65	0.74*	30	0.34			1		3.5	7	48
BF459	TO-126	300	300	5	250	50	25	30	30 10 6 7	1.0	0.65	0.74*	30	0.34			1		3.5	7	48
BFX13	TO-18	20	15	5	15	50	10	100	2 0.35 50 250	0.2	0.78	1	6	150			10		10	8	66
BFX29	TO-5	20	15	5	50	50	40	150	10 10 50 10 40 1	0.4	1.3	150	12	100			50	150		9	63
BFX30	TO-5	65	65	5	50	50	10	150	0.4 0.4 50 200	0.9	1.3	30	12				290			4	63
BFX37	TO-18	60	60	6	50	20†	100	1	5 5 0.85 0.1 70 300	0.4	1.0	50	6	40			0.5		3	1	62
BFX65	TO-18	45	45	6	40	10*	100	5	5 5 100 0.1 100 5	0.25	0.9	10	6.5						3	1	62

TEST CONDITIONS: (1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub> = I<sub>C</sub> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub> = I<sub>C</sub> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub> = I<sub>C</sub> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub> = I<sub>C</sub> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

T-31-01

Pro Electron Series

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35543 D  
T-31-01

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE0</sub> <sup>*</sup> (V)		V <sub>BE0</sub> (V)		I <sub>CE0</sub> <sup>*</sup> (mA)		H <sub>FE</sub> @ 1 kHz <sup>*</sup>		I <sub>C</sub> & V <sub>CE</sub> (V)		V <sub>CE(SAT)</sub> (V) & V <sub>BE(ON)</sub> <sup>*</sup> (V)		I <sub>C</sub> (mA)		C <sub>ob</sub> (pF)		f <sub>T</sub> (MHz)		t <sub>off</sub> (ns)		NF (dB) Max	Test Conditions	Process No.
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max			
BFX84	TO-39	45	45	6	6	500	100	15	20	1A	10	0.15	1.2	10	12	50	360					9	14	
BFX85	TO-39	45	45	6	6	50	80	15	30	1A	10	0.15	1.2	10	12	50	360					9	14	
BFX86	TO-39	45	45	6	6	50	30	15	30	1A	10	0.15	1.2	10	12	50	360					9	14	
BFX87	TO-5	45	50	6	6	50	40	25	40	500	10	0.4	1.3	150	12	100	150					9	63	
BFX88	TO-5	45	40	6	6	50	30	25	40	500	10	0.4	1.3	150	12	100	150					9	63	
BFY39	TO-18	45	25	5	5	50	30	35	400	10	10	1.0	1.0	10		150	10						23	
BFY39-1	TO-18	45	25	5	5	50	30	35	110	10	10	1.0	1.0	10		150	10						23	
BFY39-2	TO-18	45	25	5	5	50	30	100	200	10	10	1.0	1.0	10		150	10						23	
BFY39-3	TO-18	45	25	5	5	50	30	180	400	10	10	1.0	1.0	10		150	10						23	
BFY50	TO-18	80	35	6	6	500	80	20	30	10	10	0.1	1.2	10	12	60	360					9	14	
BFY51	TO-39	60	30	6	6	500	60	30	40	10	10	0.1	1.2	10	12	60	360					9	14	
BFY52	TO-39	40	20	6	6	500	60	30	60	10	10	0.1	1.2	10	12	60	360					9	14	
BFY56	TO-39	80	45	5	5	50	50	15	20	1	10	0.3	1.5	150	25	40	50						14	

6501130 NATL SEMICOND, (DISCRETE)

28C 35544

D

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V <sub>CE0</sub> <sup>*</sup> (V) Min	V <sub>CE0</sub> <sup>*</sup> (V) Min	V <sub>EB0</sub> (V) Min	I <sub>CB0</sub> <sup>*</sup> (mA) Max	V <sub>CB</sub> (V)	HFE I <sub>re</sub> 1 kHz <sup>*</sup> Min	HFE I <sub>re</sub> 1 kHz <sup>*</sup> Max	I <sub>C</sub> & V <sub>CE</sub> (mA) & (V)	V <sub>CE(SAT)</sub> (V) Max	V <sub>BE(SAT)</sub> & V <sub>BE(ON)</sub> <sup>*</sup> (V) Min	I <sub>C</sub> (mA) Max	C <sub>ob</sub> (pF) Max	f <sub>T</sub> (MHz) Min	f <sub>T</sub> (MHz) Max	t <sub>off</sub> (ns) Max	NF (dB) Max	Test Conditions	Process No.
BFY72	TO-39	50	28	5	40*	20	15	0.1	10	0.25	1.2	150	8	50	50				19
BFY76	TO-18	45	45	6	20	30	30	0.01	5	0.35	1.6	500	6						
BSX21	TO-18		80		500	50	80	0.5	5		0.9	4		60	4				07
BSX45-6	TO-39	80*	40	7	10*	60	40	100	1	1.0	2.0	1A	20	60	50				14
BSX45-10	TO-39	80*	40	7	10*	60	63	160	1	1.0	2.0	1A	20	60	50				14
BSX45-16	TO-39	80*	40	7	10*	60	100	250	1	1.0	2.0	1A	20	60	50				14
BSX46-6	TO-39	100*	60	7	10*	60	40	100	1	1.0	2.0	1A	25	60	50				12
BSX46-10	TO-39	100*	60	7	10*	60	63	160	1	1.0	2.0	1A	25	60	50				12
BSX46-16	TO-39	100*	60	7	10*	60	100	250	1	1.0	2.0	1A	25	60	50				12
BSX48	TO-18	50	25	5	120	50	17	100	1	1.5	1.5	500	6	250	30				19
BSX88	TO-18	40	15	5	25	20	15	0.5	1	0.5	0.72	0.8	6	300	10				21
BSY38	TO-18	20	12	5	100	20	30	60	0.35	0.25	0.7	0.85	5	200	10	45		16	21
BSY39	TO-18	20	12	5	100	20	15	45	1	0.6	1.5	100	5	200	10	45		16	21
BSY51	TO-18	60	35	5	100	30	40	120	0.35	0.25	0.7	0.85	9	130	50				19
BSY52	TO-18	60	25	5	100	30	20	70	1	0.6	1.5	100	9	130	50				19
BSY53	TO-18	75	30	7	10	60	20	0.1	10	0.6	1.3	150	9	150	50				19

T-31-01

TEST CONDITIONS:  
 (1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

5

Pro Electron Series

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35545 D

T-31-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V <sub>CE0</sub> <sup>*</sup> (V)		V <sub>BE0</sub> (V)		I <sub>CE0</sub> <sup>*</sup> (mA)		HFE <sub>hfe</sub> @ 1 kHz <sup>*</sup>		I <sub>C</sub> & VCE (V)		V <sub>CE(SAT)</sub> (V) & V <sub>BE(ON)</sub> <sup>*</sup> (V)		C <sub>ob</sub> (pF)		f <sub>T</sub> (MHz)		t <sub>off</sub> (ns)		Test Conditions	Process No.
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
BSY54	TO-18	30	75	7	60	10	35	0.1	10	0.6	1.3	150	9	150	50						19
							75	10	10												
BSY95A	TO-18	15	20	5	16	50	30	1	0.35	0.35	0.87	10	6	200	10						21
							50	200	10	0.35											

TEST CONDITIONS:

(1) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (2) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 20V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 5 mA. (3) I<sub>C</sub> = 200 μA, V<sub>CE</sub> = 2V, f = 1 kHz. (4) I<sub>C</sub> = 100 mA, V<sub>CE</sub> = 10V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 10 mA. (5) I<sub>C</sub> = 10 mA, V<sub>CE</sub> = 3V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 1 mA. (6) I<sub>C</sub> = 100 μA, V<sub>CE</sub> = 5V, f = 1 kHz. (7) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 10V, f = 200 kHz. (8) I<sub>C</sub> = 1 mA, V<sub>CE</sub> = 5V, f = 1 kHz. (9) I<sub>C</sub> = 150 mA, V<sub>CE</sub> = 6V, I<sub>B</sub><sup>1</sup> = I<sub>B</sub><sup>2</sup> = 15 mA. (10) I<sub>C</sub> = 10 μA, V<sub>CE</sub> = 5V, f = WB.

6501130 NATL SEMICOND, (DISCRETE)

28C 35546

T-31-01

Pro Electron Series

PRO ELECTRON SERIES (JFET)



Type No.	Case Style	BV <sub>GSD</sub> (V) @ I <sub>G</sub> Min	I <sub>GSS</sub> I <sub>DGD</sub> (mA) @ V <sub>GD</sub> Max (V)	V <sub>P</sub> (V) @ V <sub>DS</sub> Min Max (V)	I <sub>D</sub> (nA)	V <sub>GS</sub> (V) @ V <sub>GS</sub> Min Max (V)	I <sub>D</sub> (μA)	I <sub>DSS</sub> (mA) @ V <sub>DS</sub> Min Max (V)	R <sub>e</sub> (V <sub>FS</sub> ) (mmho) @ f Min Max (MHz)	C <sub>iss</sub> (pF) @ V <sub>DS</sub> Typ (V)	V <sub>GS</sub> (V)	C <sub>rss</sub> (pF) @ V <sub>DS</sub> Typ (V)	V <sub>GS</sub> (V)	NF (dB) @ R <sub>G</sub> = 1k f MHz	Process No.	Pkg. No.							
BF244A	TO-92	30	5	.5	8	15	10	2	6.5	15	3	6.5	.001	4	20	-1	1.1	20	-1	1.5	100	50	74
BF244B	TO-92	30	5	.5	8	15	10	6	15	15	3	6.5	.001	4	20	-1	1.1	20	-1	1.5	100	50	74
BF244C	TO-92	30	5	.5	8	15	10	12	25	15	3	6.5	.001	4	20	-1	1.1	20	-1	1.5	100	50	74
BF245A	TO-92	30	5	.5	8	15	10	2	6.5	15	3	6.5	.001	4	20	-1	1.1	20	-1	1.5	100	50	77
BF245B	TO-92	30	5	.5	8	15	10	6	15	15	3	6.5	.001	4	20	-1	1.1	20	-1	1.5	100	50	77
BF245C	TO-92	30	5	.5	8	15	10	12	25	15	3	6.5	.001	4	20	-1	1.1	20	-1	1.5	100	50	77
BF246A	TO-92	25	5	.6	14.5	15	10	30	80	15	8	.001	11	15	0	3.5	15	0				51	74
BF246B	TO-92	25	5	.6	14.5	15	10	60	140	15	8	.001	11	15	0	3.5	15	0				51	74
BF246C	TO-92	25	5	.6	14.5	15	10	110	250	15	8	.001	11	15	0	3.5	15	0				51	74
BF247A	TO-92	25	5	.6	14.5	15	10	30	80	15	8	.001	11	15	0	3.5	15	0				51	77
BF247B	TO-92	25	5	.6	14.5	15	10	60	140	15	8	.001	11	15	0	3.5	15	0				51	77
BF247C	TO-92	25	5	.6	14.5	15	10	110	250	15	8	.001	11	15	0	3.5	15	0				51	77
BF256A	TO-92	30	5	.5	7.5	15	200	3	7	15	4.5	.001				.7	20	-1	7.5	800	50	77	
BF256B	TO-92	30	5	.5	7.5	15	200	6	13	15	4.5	.001				.7	20	-1	7.5	800	50	77	
BF256C	TO-92	30	5	.5	7.5	15	200	11	18	15	4.5	.001				.7	20	-1	7.5	800	50	77	
BC264A	TO-92	30	10	.5	15	10	1000	2	4.5	15	2.5	.001	4.0	15	-1	1.2	15	-1	40*	10*	50	77	
BC264B	TO-92	30	10	.5	15	10	1500	3.5	6.5	15	3.0	.001	4.0	15	-1	1.2	15	-1	40*	10*	50	77	
BC264C	TO-92	30	10	.5	15	10	2500	5.0	8.0	15	3.5	.001	4.0	15	-1	1.2	15	-1	40*	10*	50	77	
BC264D	TO-92	30	10	.5	15	10	3500	7.0	12.0	15	4.0	.001	4.0	15	-1	1.2	15	-1	40*	10*	50	77	

5

This datasheet has been downloaded from:

[www.DatasheetCatalog.com](http://www.DatasheetCatalog.com)

Datasheets for electronic components.

# National Semiconductor was acquired by Texas Instruments.

[http://www.ti.com/corp/docs/investor\\_relations/pr\\_09\\_23\\_2011\\_national\\_semiconductor.html](http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html)

This file is the datasheet for the following electronic components:

BF254 - <http://www.ti.com/product/bf254?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

BF333 - <http://www.ti.com/product/bf333?HQS=TI-null-null-dscatalog-df-pf-null-wwe>



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.