


# BCR3AS

LOW POWER USE

NON-INSULATED TYPE, PLANAR PASSIVATION TYPE


Refer to the page 6 as to the product guaranteed maximum junction temperature 150°C

**BCR3AS**



- $I_T$  (RMS) ..... **3A**
- $V_{DRM}$  ..... **600V**
- IFGT I , IRGT I , IRGT III ..... **15mA (10mA) \*5**

**OUTLINE DRAWING** Dimensions in mm



\* Measurement point of case temperature

① T1 TERMINAL  
② T2 TERMINAL  
③ GATE TERMINAL  
④ T2 TERMINAL

MP-3

## APPLICATION

Hybrid IC, solid state relay, switching mode power supply, light dimmer, electric fan, electric blankets, control of household equipment such as washing machine, other general purpose control applications

## MAXIMUM RATINGS

Symbol	Parameter	Voltage class		Unit
		12	600	
$V_{DRM}$	Repetitive peak off-state voltage *1	600		V
$V_{DSM}$	Non-repetitive peak off-state voltage *1	720		V

Symbol	Parameter	Conditions	Ratings	Unit
$I_T$ (RMS)	RMS on-state current	Commercial frequency, sine full wave 360° conduction, $T_c=108^\circ\text{C}^{*3}$	3	A
$I_{TSM}$	Surge on-state current	60Hz sinewave 1 full cycle, peak value, non-repetitive	30	A
$I^2t$	$I^2t$ for fusing	Value corresponding to 1 cycle of half wave 60Hz, surge on-state current	3.7	$\text{A}^2\text{s}$
PGM	Peak gate power dissipation		3	W
PG (AV)	Average gate power dissipation		0.3	W
VGM	Peak gate voltage		6	V
IGM	Peak gate current		0.3	A
$T_j$	Junction temperature		-40 ~ +125	°C
$T_{stg}$	Storage temperature		-40 ~ +125	°C
—	Weight	Typical value	0.26	g

\*1. Gate open.

**BCR3AS**

Refer to the page 6 as to the product guaranteed maximum junction temperature 150°C

**LOW POWER USE**  
**NON-INSULATED TYPE, PLANAR PASSIVATION TYPE**

**ELECTRICAL CHARACTERISTICS**

Symbol	Parameter	Test conditions	Limits			Unit	
			Min.	Typ.	Max.		
IDRM	Repetitive peak off-state current	T <sub>j</sub> =125°C, V <sub>DRM</sub> applied	—	—	2.0	mA	
V <sub>TM</sub>	On-state voltage	T <sub>c</sub> =25°C, I <sub>TM</sub> =4.5A, Instantaneous measurement	—	—	1.7	V	
V <sub>FGT I</sub>	Gate trigger voltage *2	T <sub>j</sub> =25°C, V <sub>D</sub> =6V, R <sub>L</sub> =6Ω, R <sub>G</sub> =330Ω	I	—	—	1.5	V
V <sub>RGT I</sub>			II	—	—	1.5	V
V <sub>RGT III</sub>			III	—	—	1.5	V
I <sub>FGT I</sub>	Gate trigger current *2	T <sub>j</sub> =25°C, V <sub>D</sub> =6V, R <sub>L</sub> =6Ω, R <sub>G</sub> =330Ω	I	—	—	15*5	mA
I <sub>RGT I</sub>			II	—	—	15*5	mA
I <sub>RGT III</sub>			III	—	—	15*5	mA
V <sub>GD</sub>	Gate non-trigger voltage	T <sub>j</sub> =125°C, V <sub>D</sub> =1/2V <sub>DRM</sub>	0.2	—	—	V	
R <sub>th (j-c)</sub>	Thermal resistance	Junction to case *3	—	—	3.8	°C/W	
(dv/dt) <sub>c</sub>	Critical-rate of rise of off-state commutating voltage *4	T <sub>j</sub> =125°C	5	—	—	V/μs	

\*2. Measurement using the gate trigger characteristics measurement circuit.



\*3. Case temperature is measured on the T2 terminal.

\*4. Test conditions of the critical-rate of rise of off-state commutating voltage is shown in the table below.

\*5. High sensitivity (I<sub>GT</sub>≤10mA) is also available. (IGT item①)

Test conditions	Commutating voltage and current waveforms (inductive load)
1. Junction temperature T <sub>j</sub> =125°C  2. Rate of decay of on-state commutating current (di/dt) <sub>c</sub> =-1.5A/ms  3. Peak off-state voltage V <sub>D</sub> =400V	

**PERFORMANCE CURVES**




# BCR3AS


Refer to the page 6 as to the product guaranteed maximum junction temperature 150°C

LOW POWER USE  
NON-INSULATED TYPE, PLANAR PASSIVATION TYPE


**GATE CHARACTERISTICS (I, II AND III)**




**GATE TRIGGER CURRENT VS. JUNCTION TEMPERATURE**




**GATE TRIGGER VOLTAGE VS. JUNCTION TEMPERATURE**




**MAXIMUM TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (JUNCTION TO CASE)**



**MAXIMUM ON-STATE POWER DISSIPATION**









**ALLOWABLE CASE TEMPERATURE VS. RMS ON-STATE CURRENT**



# BCR3AS

Refer to the page 6 as to the product guaranteed maximum junction temperature 150°C



LOW POWER USE  
NON-INSULATED TYPE, PLANAR PASSIVATION TYPE





# BCR3AS

Refer to the page 6 as to the product guaranteed maximum junction temperature 150°C

LOW POWER USE  
NON-INSULATED TYPE, PLANAR PASSIVATION TYPE



### GATE TRIGGER CHARACTERISTICS TEST CIRCUITS




# BCR3AS

LOW POWER USE

The product guaranteed maximum junction temperature 150°C (See warning.)


NON-INSULATED TYPE, PLANAR PASSIVATION TYPE

**BCR3AS**



- **IT (RMS)** ..... **3A**
- **VDRM** ..... **600V**
- **IFGT I , IRGT I , IRGT III** ..... **15mA (10mA) \*5**

**OUTLINE DRAWING** Dimensions in mm



\* Measurement point of case temperature

① T1 TERMINAL  
② T2 TERMINAL  
③ GATE TERMINAL  
④ T2 TERMINAL

MP-3

## APPLICATION

Hybrid IC, solid state relay, switching mode power supply, light dimmer, electric fan, electric blankets, control of household equipment such as washing machine, other general purpose control applications

(Warning)

1. Refer to the recommended circuit values around the triac before using.
2. Be sure to exchange the specification before using. If not exchanged, general triacs will be supplied.

## MAXIMUM RATINGS

Symbol	Parameter	Voltage class		Unit
		12	600	
VDRM	Repetitive peak off-state voltage *1	600		V
VDSM	Non-repetitive peak off-state voltage *1	720		V

Symbol	Parameter	Conditions	Ratings	Unit
IT (RMS)	RMS on-state current	Commercial frequency, sine full wave 360° conduction, Tc=133°C*3	3	A
ITSM	Surge on-state current	60Hz sinewave 1 full cycle, peak value, non-repetitive	30	A
I <sup>2</sup> t	I <sup>2</sup> t for fusing	Value corresponding to 1 cycle of half wave 60Hz, surge on-state current	3.7	A <sup>2</sup> s
PGM	Peak gate power dissipation		3	W
PG (AV)	Average gate power dissipation		0.3	W
VGM	Peak gate voltage		6	V
IGM	Peak gate current		0.3	A
Tj	Junction temperature		-40 ~ +150	°C
Tstg	Storage temperature		-40 ~ +150	°C
—	Weight	Typical value	0.26	g

\*1. Gate open.

# BCR3AS

The product guaranteed maximum junction temperature 150°C (See warning.)

**LOW POWER USE**  
NON-INSULATED TYPE, PLANAR PASSIVATION TYPE

## ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Test conditions	Limits			Unit	
			Min.	Typ.	Max.		
IDRM	Repetitive peak off-state current	T <sub>j</sub> =150°C, V <sub>DRM</sub> applied	—	—	2.0	mA	
VTM	On-state voltage	T <sub>c</sub> =25°C, I <sub>TM</sub> =4.5A, Instantaneous measurement	—	—	1.7	V	
VFGT I	Gate trigger voltage *2	T <sub>j</sub> =25°C, V <sub>D</sub> =6V, R <sub>L</sub> =6Ω, R <sub>G</sub> =330Ω	I	—	—	1.5	V
VRGT I			II	—	—	1.5	V
VRGT III			III	—	—	1.5	V
IFGT I	Gate trigger current *2	T <sub>j</sub> =25°C, V <sub>D</sub> =6V, R <sub>L</sub> =6Ω, R <sub>G</sub> =330Ω	I	—	—	15*5	mA
IRGT I			II	—	—	15*5	mA
IRGT III			III	—	—	15*5	mA
VGD	Gate non-trigger voltage	T <sub>j</sub> =125°C/150°C, V <sub>D</sub> =1/2V <sub>DRM</sub>	0.2/0.1	—	—	V	
Rth (j-c)	Thermal resistance	Junction to case *3	—	—	3.8	°C/W	
(dv/dt) <sub>c</sub>	Critical-rate of rise of off-state commutating voltage *4	T <sub>j</sub> =125°C/150°C	5/1	—	—	V/μs	

\*2. Measurement using the gate trigger characteristics measurement circuit.



\*3. Case temperature is measured on the T2 terminal.

\*4. Test conditions of the critical-rate of rise of off-state commutating voltage is shown in the table below.

\*5. High sensitivity (I<sub>GT</sub>≤10mA) is also available. (IGT item①)

Test conditions	Commutating voltage and current waveforms (inductive load)
1. Junction temperature T <sub>j</sub> =125°C/150°C  2. Rate of decay of on-state commutating current (di/dt) <sub>c</sub> =-1.5A/ms  3. Peak off-state voltage V <sub>D</sub> =400V	

## PERFORMANCE CURVES




# BCR3AS


The product guaranteed maximum junction temperature 150°C (See warning.)

LOW POWER USE  
NON-INSULATED TYPE, PLANAR PASSIVATION TYPE


**GATE CHARACTERISTICS  
(I, II AND III)**




**GATE TRIGGER CURRENT VS. JUNCTION TEMPERATURE**




**GATE TRIGGER VOLTAGE VS. JUNCTION TEMPERATURE**




**MAXIMUM TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS  
(JUNCTION TO CASE)**



**MAXIMUM ON-STATE POWER DISSIPATION**









**ALLOWABLE CASE TEMPERATURE VS. RMS ON-STATE CURRENT**



# BCR3AS

The product guaranteed maximum junction temperature 150°C (See warning.)





LOW POWER USE  
NON-INSULATED TYPE, PLANAR PASSIVATION TYPE





# BCR3AS

The product guaranteed maximum junction temperature 150°C (See warning.)


LOW POWER USE  
NON-INSULATED TYPE, PLANAR PASSIVATION TYPE



**GATE TRIGGER CHARACTERISTICS TEST CIRCUITS**



**RECOMMENDED CIRCUIT VALUES AROUND THE TRIAC**





LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.