



BCR2PM

LOW POWER USE
INSULATED TYPE, PLANAR PASSIVATION TYPE

BCR2PM



- IT (RMS) 2A
- VDRM 600V
- IRGT I , IRGT III 10mA



APPLICATION

Switching mode power supply, light dimmer, electric flasher unit, control of household equipment such as TV sets · stereo · refrigerator · washing machine · infrared kotatsu · carpet, solenoid drivers, small motor control, copying machine, electric tool, other general purpose control applications

MAXIMUM RATINGS

Symbol	Parameter	Voltage class		Unit
		12	600	
VDRM	Repetitive peak off-state voltage *1	600		V
VDSM	Non-repetitive peak off-state voltage *1	720		V

Symbol	Parameter	Conditions	Ratings	Unit
IT (RMS)	RMS on-state current	Commercial frequency, sine full wave 360° conduction	2	A
ITSM	Surge on-state current	60Hz sinewave 1 full cycle, peak value, non-repetitive	10	A
I ² _t	I ² _t for fusing	Value corresponding to 1 cycle of half wave 60Hz, surge on-state current	0.41	A ² s
PGM	Peak gate power dissipation		1	W
PG (AV)	Average gate power dissipation		0.1	W
VGM	Peak gate voltage		6	V
IGM	Peak gate current		1	A
T _j	Junction temperature		-40 ~ +125	°C
T _{stg}	Storage temperature		-40 ~ +125	°C
—	Weight	Typical value	2.0	g

*1. Gate open.

BCR2PM

LOW POWER USE


INSULATED TYPE, PLANAR PASSIVATION TYPE

ELECTRICAL CHARACTERISTICS



Symbol	Parameter	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
IDRM	Repetitive peak off-state current	T _j =125°C, V _{DRM} applied	—	—	0.5	mA
V _{TM}	On-state voltage	T _a =25°C, I _{TM} =1.5A, Instantaneous measurement	—	—	1.6	V
V _{RGT I}	Gate trigger voltage *2	T _j =25°C, V _D =6V, R _L =6Ω, R _G =330Ω	—	—	2.0	V
V _{RGT III}			—	—	2.0	V
I _{RGT I}	Gate trigger current *2	T _j =25°C, V _D =6V, R _L =6Ω, R _G =330Ω	—	—	10	mA
I _{RGT III}			—	—	10	mA
V _{GD}	Gate non-trigger voltage	T _j =125°C, V _D =1/2V _{DRM}	0.1	—	—	V
R _{th(j-a)}	Thermal resistance	Junction to ambient, Natural convection	—	—	40	°C/W

*2. Measurement using the gate trigger characteristics measurement circuit.

GATE TRIGGER CHARACTERISTICS TEST CIRCUITS




PERFORMANCE CURVES




BCR2PM

LOW POWER USE
INSULATED TYPE, PLANAR PASSIVATION TYPE


GATE CHARACTERISTICS




GATE TRIGGER CURRENT VS. JUNCTION TEMPERATURE




GATE TRIGGER VOLTAGE VS. JUNCTION TEMPERATURE




MAXIMUM TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (JUNCTION TO AMBIENT)



MAXIMUM ON-STATE POWER DISSIPATION









ALLOWABLE AMBIENT TEMPERATURE VS. RMS ON-STATE CURRENT



BCR2PM

LOW POWER USE
INSULATED TYPE, PLANAR PASSIVATION TYPE





LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.