

AN8000/AN8000M Series



3-pin Positive Output Low Dropout Voltage Regulator (50mA Type)

Overview


The AN8000 series is 3-pin low-dropout fixed positive output monolithic voltage regulators. Since their power consumption can be minimized, they are suitable for battery stabilizing power supply and reference voltage. Thirteen types of output voltage are available ; 2V, 2.5V, 3V, 3.5V (TO-92 only) , 4V, 4.5V, 5V, 6V, 7V, 8V, 8.5V, 9V, and 10V.

Features

- Input/output voltage difference : 0.3V (max.)
- Output current of up to 50mA
- Low bias current ; 0.6mA (typ.)
- Output voltage ; 2V, 2.5V, 3V, 3.5V (TO-92 only) , 4V, 4.5V, 5V, 6V, 7V, 8V, 8.5V, 9V, and 10V.
- Over-voltage protective circuit built-in.



Block Diagram



■ Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Rating	Unit
Supply voltage	V_I	20	V
Supply current	I_{CC}	100	mA
Power dissipation	P_D	650 *	mW
Operating ambient temperature	T_{opr}	-30 to+80	°C
Storage temperature	AN8000 Series	-55 to+150	°C
	AN8000M Series	-55 to+125	

* Mounting onto the PCB (20 × 20 × 1.7mm glass epoxy copper foil 1 cm² or more), for AN8000M Series.

■ Electrical Characteristics (Ta=25°C)

• AN8002/AN8002M (2V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	1.92	2	2.08	V
Line regulation	REG_{IN}	$V_I=2.5$ to 8V, $T_j=25^\circ\text{C}$	—	2	40	mV
Load regulation	REG_L	$I_O=1$ to 40mA, $T_j=25^\circ\text{C}$	—	7	20	mV
		$I_O=1$ to 50mA, $T_j=25^\circ\text{C}$	—	10	25	mV
Minimum I/O voltage difference	$V_{DIF (min.)}$	$V_I=1.9\text{V}$, $I_O=20\text{mA}$, $T_j=25^\circ\text{C}$	—	0.06	0.2	V
		$V_I=1.9\text{V}$, $I_O=50\text{mA}$, $T_j=25^\circ\text{C}$	—	0.12	0.3	V
Bias current	I_{bias}	$I_O=0\text{mA}$, $T_j=25^\circ\text{C}$	—	0.6	1	mA
Ripple rejection ratio	RR	$V_I=3$ to 5V, $f=120\text{Hz}$	62	74	—	dB
Output noise voltage	V_{no}	$f=10\text{Hz}$ to 100kHz	—	60	—	μV
Output voltage temperature coefficient	$\Delta V_O/T_a$	$T_j=-30$ to+125°C	—	0.1	—	mV/°C

Note1) The specified condition $T_j=25^\circ\text{C}$ means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, $V_I=3\text{V}$, $I_O=20\text{mA}$, $C_O=10\mu\text{F}$

• AN8025/AN8025M (2.5V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	2.4	2.5	2.6	V
Line regulation	REG_{IN}	$V_I=3$ to 8.5V, $T_j=25^\circ\text{C}$	—	2.5	50	mV
Load regulation	REG_L	$I_O=1$ to 40mA, $T_j=25^\circ\text{C}$	—	8	20	mV
		$I_O=1$ to 50mA, $T_j=25^\circ\text{C}$	—	12.5	25	mV
Minimum I/O voltage difference	$V_{DIF (min.)}$	$V_I=2.4\text{V}$, $I_O=20\text{mA}$, $T_j=25^\circ\text{C}$	—	0.07	0.2	V
		$V_I=2.4\text{V}$, $I_O=50\text{mA}$, $T_j=25^\circ\text{C}$	—	0.12	0.3	V
Bias current	I_{bias}	$I_O=0\text{mA}$, $T_j=25^\circ\text{C}$	—	0.6	1	mA
Ripple rejection ratio	RR	$V_I=3.5$ to 5.5V, $f=120\text{Hz}$	60	72	—	dB
Output noise voltage	V_{no}	$f=10\text{Hz}$ to 100kHz	—	65	—	μV
Output voltage temperature coefficient	$\Delta V_O/T_a$	$T_j=-30$ to+125°C	—	0.13	—	mV/°C

Note1) The specified condition $T_j=25^\circ\text{C}$ means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, $V_I=3.5\text{V}$, $I_O=20\text{mA}$, $C_O=10\mu\text{F}$

■ Electrical Characteristics (Ta=25°C)

• AN8003/AN8003M (3V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	2.88	3	3.12	V
Line regulation	REG_{IN}	$V_I=3.5$ to 9V, $T_j=25^\circ\text{C}$	—	3	50	mV
Load regulation	REG_{L}	$I_O=1$ to 40mA, $T_j=25^\circ\text{C}$	—	9	25	mV
		$I_O=1$ to 50mA, $T_j=25^\circ\text{C}$	—	15	30	mV
Minimum I/O voltage difference	$V_{\text{DIF (min.)}}$	$V_I=2.9\text{V}$, $I_O=20\text{mA}$, $T_j=25^\circ\text{C}$	—	0.07	0.2	V
		$V_I=2.9\text{V}$, $I_O=50\text{mA}$, $T_j=25^\circ\text{C}$	—	0.12	0.3	V
Bias current	I_{bias}	$I_O=0\text{mA}$, $T_j=25^\circ\text{C}$	—	0.6	1	mA
Ripple rejection ratio	RR	$V_I=4$ to 6V, $f=120\text{Hz}$	58	70	—	dB
Output noise voltage	V_{no}	$f=10\text{Hz}$ to 100kHz	—	70	—	μV
Output voltage temperature coefficient	$\Delta V_O/T_a$	$T_j=-30$ to $+125^\circ\text{C}$	—	0.15	—	$\text{mV}/^\circ\text{C}$

Note1) The specified condition $T_j=25^\circ\text{C}$ means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, $V_I=4\text{V}$, $I_O=20\text{mA}$, $C_O=10\mu\text{F}$

• AN8035/AN8035M (3.5V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	3.36	3.5	3.64	V
Line regulation	REG_{IN}	$V_I=4$ to 9.5V, $T_j=25^\circ\text{C}$	—	3.5	50	mV
Load regulation	REG_{L}	$I_O=1$ to 40mA, $T_j=25^\circ\text{C}$	—	10	30	mV
		$I_O=1$ to 50mA, $T_j=25^\circ\text{C}$	—	20	40	mV
Minimum I/O voltage difference	$V_{\text{DIF (min.)}}$	$V_I=3.4\text{V}$, $I_O=20\text{mA}$, $T_j=25^\circ\text{C}$	—	0.07	0.2	V
		$V_I=3.4\text{V}$, $I_O=50\text{mA}$, $T_j=25^\circ\text{C}$	—	0.12	0.3	V
Bias current	I_{bias}	$I_O=0\text{mA}$, $T_j=25^\circ\text{C}$	—	0.6	1	mA
Ripple rejection ratio	RR	$V_I=4.5$ to 6.5V, $f=120\text{Hz}$	57	69	—	dB
Output noise voltage	V_{no}	$f=10\text{Hz}$ to 100kHz	—	75	—	μV
Output voltage temperature coefficient	$\Delta V_O/T_a$	$T_j=-30$ to $+125^\circ\text{C}$	—	0.2	—	$\text{mV}/^\circ\text{C}$

Note1) The specified condition $T_j=25^\circ\text{C}$ means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, $V_I=4.5\text{V}$, $I_O=20\text{mA}$, $C_O=10\mu\text{F}$

• AN8004/AN8004M (4V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	3.84	4	4.16	V
Line regulation	REG_{IN}	$V_I=4.5$ to 10V, $T_j=25^\circ\text{C}$	—	3.5	50	mV
Load regulation	REG_{L}	$I_O=1$ to 40mA, $T_j=25^\circ\text{C}$	—	10	30	mV
		$I_O=1$ to 50mA, $T_j=25^\circ\text{C}$	—	20	40	mV
Minimum I/O voltage difference	$V_{\text{DIF (min.)}}$	$V_I=3.8\text{V}$, $I_O=20\text{mA}$, $T_j=25^\circ\text{C}$	—	0.07	0.2	V
		$V_I=3.8\text{V}$, $I_O=50\text{mA}$, $T_j=25^\circ\text{C}$	—	0.12	0.3	V
Bias current	I_{bias}	$I_O=0\text{mA}$, $T_j=25^\circ\text{C}$	—	0.6	1	mA
Ripple rejection ratio	RR	$V_I=5$ to 7V, $f=120\text{Hz}$	56	67	—	dB
Output noise voltage	V_{no}	$f=10\text{Hz}$ to 100kHz	—	80	—	μV
Output voltage temperature coefficient	$\Delta V_O/T_a$	$T_j=-30$ to $+125^\circ\text{C}$	—	0.2	—	$\text{mV}/^\circ\text{C}$

Note1) The specified condition $T_j=25^\circ\text{C}$ means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, $V_I=5\text{V}$, $I_O=20\text{mA}$, $C_O=10\mu\text{F}$

■ Electrical Characteristics (Ta=25°C)

• AN8045/AN8045M (4.5V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V _O	T _j =25°C	4.32	4.5	4.68	V
Line regulation	REG _{IN}	V _I =5 to 10.5V, T _j =25°C	—	4	50	mV
Load regulation	REG _L	I _O =1 to 40mA, T _j =25°C	—	11	35	mV
		I _O =1 to 50mA, T _j =25°C	—	23	45	mV
Minimum I/O voltage difference	V _{DIF (min.)}	V _I =4.3V, I _O =20mA, T _j =25°C	—	0.07	0.2	V
		V _I =4.3V, I _O =50mA, T _j =25°C	—	0.12	0.3	V
Bias current	I _{bias}	I _O =0mA, T _j =25°C	—	0.7	1	mA
Ripple rejection ratio	RR	V _I =5.5 to 7.5V, f=120Hz	54	66	—	dB
Output noise voltage	V _{no}	f=10Hz to 100kHz	—	85	—	μV
Output voltage temperature coefficient	ΔV _O /Ta	T _j =-30 to +125°C	—	0.23	—	mV/°C

Note1) The specified condition T_j=25°C means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, V_I=5.5V, I_O=20mA, C_O=10μF

• AN8005/AN8005M (5V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V _O	T _j =25°C	4.8	5	5.2	V
Line regulation	REG _{IN}	V _I =5.5 to 11V, T _j =25°C	—	4.5	50	mV
Load regulation	REG _L	I _O =1 to 40mA, T _j =25°C	—	12	40	mV
		I _O =1 to 50mA, T _j =25°C	—	25	50	mV
Minimum I/O voltage difference	V _{DIF (min.)}	V _I =4.8V, I _O =20mA, T _j =25°C	—	0.07	0.2	V
		V _I =4.8V, I _O =50mA, T _j =25°C	—	0.12	0.3	V
Bias current	I _{bias}	I _O =0mA, T _j =25°C	—	0.7	1	mA
Ripple rejection ratio	RR	V _I =6 to 8V, f=120Hz	52	64	—	dB
Output noise voltage	V _{no}	f=10Hz to 100kHz	—	95	—	μV
Output voltage temperature coefficient	ΔV _O /Ta	T _j =-30 to +125°C	—	0.25	—	mV/°C

Note1) The specified condition T_j=25°C means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, V_I=6V, I_O=20mA, C_O=10μF

• AN8006/AN8006M (6V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V _O	T _j =25°C	5.76	6	6.24	V
Line regulation	REG _{IN}	V _I =6.5 to 12V, T _j =25°C	—	5.5	60	mV
Load regulation	REG _L	I _O =1 to 40mA, T _j =25°C	—	13	45	mV
		I _O =1 to 50mA, T _j =25°C	—	28	55	mV
Minimum I/O voltage difference	V _{DIF (min.)}	V _I =5.8V, I _O =20mA, T _j =25°C	—	0.07	0.2	V
		V _I =5.8V, I _O =50mA, T _j =25°C	—	0.13	0.3	V
Bias current	I _{bias}	I _O =0mA, T _j =25°C	—	0.7	1.2	mA
Ripple rejection ratio	RR	V _I =7 to 9V, f=120Hz	51	63	—	dB
Output noise voltage	V _{no}	f=10Hz to 100kHz	—	105	—	μV
Output voltage temperature coefficient	ΔV _O /Ta	T _j =-30 to +125°C	—	0.3	—	mV/°C

Note1) The specified condition T_j=25°C means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, V_I=7V, I_O=20mA, C_O=10μF

■ Electrical Characteristics (Ta=25°C)

• AN8007/AN8007M (7V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	6.72	7	7.28	V
Line regulation	REG_{IN}	$V_I=7.5$ to 13V, $T_j=25^\circ\text{C}$	—	6.5	70	mV
Load regulation	REG_{L}	$I_O=1$ to 40mA, $T_j=25^\circ\text{C}$	—	14	50	mV
		$I_O=1$ to 50mA, $T_j=25^\circ\text{C}$	—	31	60	mV
Minimum I/O voltage difference	$V_{\text{DIF (min.)}}$	$V_I=6.8\text{V}$, $I_O=20\text{mA}$, $T_j=25^\circ\text{C}$	—	0.07	0.2	V
		$V_I=6.8\text{V}$, $I_O=50\text{mA}$, $T_j=25^\circ\text{C}$	—	0.13	0.3	V
Bias current	I_{bias}	$I_O=0\text{mA}$, $T_j=25^\circ\text{C}$	—	0.7	1.3	mA
Ripple rejection ratio	RR	$V_I=8$ to 10V, $f=120\text{Hz}$	50	62	—	dB
Output noise voltage	V_{no}	$f=10\text{Hz}$ to 100kHz	—	120	—	μV
Output voltage temperature coefficient	$\Delta V_O/T_a$	$T_j=-30$ to $+125^\circ\text{C}$	—	0.35	—	$\text{mV}/^\circ\text{C}$

Note1) The specified condition $T_j=25^\circ\text{C}$ means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, $V_I=8\text{V}$, $I_O=20\text{mA}$, $C_O=10\mu\text{F}$

• AN8008/AN8008M (8V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	7.68	8	8.32	V
Line regulation	REG_{IN}	$V_I=8.5$ to 14V, $T_j=25^\circ\text{C}$	—	7.5	80	mV
Load regulation	REG_{L}	$I_O=1$ to 40mA, $T_j=25^\circ\text{C}$	—	15	55	mV
		$I_O=1$ to 50mA, $T_j=25^\circ\text{C}$	—	34	65	mV
Minimum I/O voltage difference	$V_{\text{DIF (min.)}}$	$V_I=7.8\text{V}$, $I_O=20\text{mA}$, $T_j=25^\circ\text{C}$	—	0.07	0.2	V
		$V_I=7.8\text{V}$, $I_O=50\text{mA}$, $T_j=25^\circ\text{C}$	—	0.14	0.3	V
Bias current	I_{bias}	$I_O=0\text{mA}$, $T_j=25^\circ\text{C}$	—	0.7	1.3	mA
Ripple rejection ratio	RR	$V_I=9$ to 11V, $f=120\text{Hz}$	49	61	—	dB
Output noise voltage	V_{no}	$f=10\text{Hz}$ to 100kHz	—	135	—	μV
Output voltage temperature coefficient	$\Delta V_O/T_a$	$T_j=-30$ to $+125^\circ\text{C}$	—	0.4	—	$\text{mV}/^\circ\text{C}$

Note1) The specified condition $T_j=25^\circ\text{C}$ means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, $V_I=9\text{V}$, $I_O=20\text{mA}$, $C_O=10\mu\text{F}$

• AN8085/AN8085M (8.5V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	8.16	8.50	8.84	V
Line regulation	REG_{IN}	$V_I=9$ to 14.5V, $T_j=25^\circ\text{C}$	—	8.3	90	mV
Load regulation	REG_{L}	$I_O=1$ to 40mA, $T_j=25^\circ\text{C}$	—	16	60	mV
		$I_O=1$ to 50mA, $T_j=25^\circ\text{C}$	—	36	70	mV
Minimum I/O voltage difference	$V_{\text{DIF (min.)}}$	$V_I=8.3\text{V}$, $I_O=20\text{mA}$, $T_j=25^\circ\text{C}$	—	0.07	0.2	V
		$V_I=8.3\text{V}$, $I_O=50\text{mA}$, $T_j=25^\circ\text{C}$	—	0.14	0.3	V
Bias current	I_{bias}	$I_O=0\text{mA}$, $T_j=25^\circ\text{C}$	—	0.8	1.4	mA
Ripple rejection ratio	RR	$V_I=9.5$ to 11.5V, $f=120\text{Hz}$	48	60	—	dB
Output noise voltage	V_{no}	$f=10\text{Hz}$ to 100kHz	—	140	—	μV
Output voltage temperature coefficient	$\Delta V_O/T_a$	$T_j=-30$ to $+125^\circ\text{C}$	—	0.43	—	$\text{mV}/^\circ\text{C}$

Note1) The specified condition $T_j=25^\circ\text{C}$ means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, $V_I=9.5\text{V}$, $I_O=20\text{mA}$, $C_O=10\mu\text{F}$

■ Electrical Characteristics (Ta=25°C)

• AN8009/AN8009M (9V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	8.64	9	9.36	V
Line regulation	REG_{IN}	$V_I=9.5$ to 15V , $T_j=25^\circ\text{C}$	—	9	100	mV
Load regulation	REG_{L}	$I_O=1$ to 40mA , $T_j=25^\circ\text{C}$	—	17	70	mV
		$I_O=1$ to 50mA , $T_j=25^\circ\text{C}$	—	37	75	mV
Minimum I/O voltage difference	$V_{\text{DIF (min.)}}$	$V_I=8.8\text{V}$, $I_O=20\text{mA}$, $T_j=25^\circ\text{C}$	—	0.07	0.2	V
		$V_I=8.8\text{V}$, $I_O=50\text{mA}$, $T_j=25^\circ\text{C}$	—	0.14	0.3	V
Bias current	I_{bias}	$I_O=0\text{mA}$, $T_j=25^\circ\text{C}$	—	0.8	1.4	mA
Ripple rejection ratio	RR	$V_I=10$ to 12V , $f=120\text{Hz}$	47	59	—	dB
Output noise voltage	V_{no}	$f=10\text{Hz}$ to 100kHz	—	150	—	μV
Output voltage temperature coefficient	$\Delta V_O/T_a$	$T_j=-30$ to $+125^\circ\text{C}$	—	0.45	—	$\text{mV}/^\circ\text{C}$

Note1) The specified condition $T_j=25^\circ\text{C}$ means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, $V_I=10\text{V}$, $I_O=20\text{mA}$, $C_O=10\mu\text{F}$


• AN8010/AN8010M (10V Type)

Parameter	Symbol	Condition	min	typ	max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	9.6	10	10.4	V
Line regulation	REG_{IN}	$V_I=10.5$ to 16V , $T_j=25^\circ\text{C}$	—	10	100	mV
Load regulation	REG_{L}	$I_O=1$ to 40mA , $T_j=25^\circ\text{C}$	—	18	75	mV
		$I_O=1$ to 50mA , $T_j=25^\circ\text{C}$	—	40	85	mV
Minimum I/O voltage difference	$V_{\text{DIF (min.)}}$	$V_I=9.8\text{V}$, $I_O=20\text{mA}$, $T_j=25^\circ\text{C}$	—	0.07	0.2	V
		$V_I=9.8\text{V}$, $I_O=50\text{mA}$, $T_j=25^\circ\text{C}$	—	0.14	0.3	V
Bias current	I_{bias}	$I_O=0\text{mA}$, $T_j=25^\circ\text{C}$	—	0.8	1.4	mA
Ripple rejection ratio	RR	$V_I=11$ to 13V , $f=120\text{Hz}$	46	58	—	dB
Output noise voltage	V_{no}	$f=10\text{Hz}$ to 100kHz	—	165	—	μV
Output voltage temperature coefficient	$\Delta V_O/T_a$	$T_j=-30$ to $+125^\circ\text{C}$	—	0.5	—	$\text{mV}/^\circ\text{C}$

Note1) The specified condition $T_j=25^\circ\text{C}$ means that the test should be conducted with each test time reduced (within 10ms) so that the drift in characteristic value due to a temperature rise at chip junction can be ignored.

Note2) Unless otherwise specified, $V_I=11\text{V}$, $I_O=20\text{mA}$, $C_O=10\mu\text{F}$


■ Application Circuit




- The AN8000/AN8000M series has IC internal gain increased in order to improve performance. When the power line on the output side is long, use a capacitor of $10\mu\text{F}$.
For the capacitor on the output side, attach it as close to the IC as possible.
- When using at a low temperature, it is recommended to use the capacitors with low internal impedance (for example, tantalum capacitor) for output capacitors.

■ Characteristic Curve


$P_D - T_a$ (AN8000 Series)




$P_D - T_a$ (AN8000M Series)




RR - f




$V_O - V_I$



$V_O - I_O$



$V_O - T_a$





LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.