

THE CONDUCTION LOSSES IN A POWER RECTIFIER


B. Rivet

INTRODUCTION

In spite of the high operating frequency, the conduction losses remain the main cause of the junction's temperature increase in the majority of the applications. Therefore, it is important to accurately estimate these losses. The purpose of this note is to give data to calculate the conduction losses in the diodes.

The forward characteristic of a diode is shown in fig.1

Fig.1 : Forward characteristics of a diodes



We can define two areas :

1) The peak current I_M is lower than $3 I_{F(av)}$:

The forward characteristic of a diode may be assimilated to a straight line defined by V_{to} and r_d (Fig.1).

The forward voltage can be expressed by

$$V_{FM} = V_{to} + r_d I_{FM}$$

V_{to} and r_d are given in the datasheet for each part number. With this model the expression of the conduction losses is :


$$P_{cond} = V_{to} I_{F(av)} + r_d I_{F(RMS)}^2$$

$I_{F(av)}$: average forward current in the diode

$I_{F(RMS)}$: RMS forward current in the diode

Fig.2 shows the average and RMS values for different current wave forms.

Fig.2 : Average and RMS values for different currents wave forms.



APPLICATION NOTE

Example :

With a STTA1206D : $V_{to} = 1.15V$ $r_d = 0.029 \text{ Ohm}$
and a rectangular current : $I_M = 20A$ $\delta = 0.5$
we find :


$$P_{cond} = 17.3W$$

2) The peak current I_M is higher than 3 $I_{F(av)}$:

When the peak current I_M is higher than 3 $I_{F(av)}$, the forward voltage and the conduction losses values calculated with V_{to} and r_d becomes very pessimistic (Fig.1).

A more accurate estimation of the conduction losses can be done with the curve V_{FM} , I_{FM} given in the datasheet (fig.3).

Fig.3 : Forward voltage drop versus forward current of a STTA806D.



In the case of a rectangular current conduction losses can be expressed by :

$$P_{cond} = V_{FM}(I_M) \times I_{F(av)}$$

Where $V_F(I_M)$ is the V_{FM} value when $I_{FM} = I_M$

Example :

With a rectangular current : $I_M = 70A$ $\delta = 0.1$
and a STTA806D $V_{FM}(70A) = 2.75V$ (Fig.3)
 $P_{cond} = V_{FM}(70A) \times \delta \times I_M$
we find :

$$P_{cond} = 19W$$

In these conditions, conduction losses calculated with V_{to} and r_d give : $P_{cond} = 29W$!

Conclusion

This short note provides the designer with the rules to properly estimate the conduction losses in a power diode. It also highlights the limitation of the traditional forward characteristic model $V_F = V_{to} + r_d I_F$, gives a value very pessimistic at high level current.

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1995 SGS-THOMSON Microelectronics - Printed in Italy - All rights reserved.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.