

2SK3262-01MR

FUJI POWER MOS-FET


N-CHANNEL SILICON POWER MOS-FET

Features

- High speed switching
- Low on-resistance
- No secondary breakdown
- Low driving power
- Avalanche-proof

Applications

- Switching regulators
- UPS (Uninterruptible Power Supply)
- DC-DC converters




Maximum ratings and characteristic Absolute maximum ratings

(Tc=25°C unless otherwise specified)

Item	Symbol	Rating	Unit	
Drain-source voltage	V _{DS}	200	V	
Continuous drain current	I _D	±20	A	
Pulsed drain current	I _{D(puls)}	±80	A	
Gate-source voltage	V _{GS}	±20	V	
Maximum Avalanche Energy	E _{AV*1}	355	mJ	
Max. power dissipation	T _a =25°C	P _D	2	W
	T _c =25°C	P _D	45	W
Operating and storage temperature range	T _{ch}	+150	°C	
	T _{stg}	-55 to +150	°C	

*1 L=1.6mH, V_{cc}=24V

Equivalent circuit schematic









Electrical characteristics (Tc =25°C unless otherwise specified)







Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Drain-source breakdown voltage	V _{(BR)DSS}	I _D =1mA V _{GS} =0V	200			V
Gate threshold voltage	V _{GS(th)}	I _D =1mA V _{DS} =V _{GS}	1.0	1.5	2.0	V
Zero gate voltage drain current	I _{DSS}	V _{DS} =200V V _{GS} =0V	T _{ch} =25°C	10	500	μA
			T _{ch} =125°C	0.2	0.5	mA
Gate-source leakage current	I _{GSS}	V _{GS} =±20V V _{DS} =0V		10	100	nA
Drain-source on-state resistance	R _{DS(on)}	I _D =10A V _{GS} =4V		110	150	mΩ
		I _D =10A V _{GS} =10V		85	100	
Forward transconductance	g _{fs}	I _D =10A V _{DS} =25V	9.0	19.0		S
Input capacitance	C _{iss}	V _{DS} =25V		1700	2550	pF
Output capacitance	C _{oss}	V _{GS} =0V		290	435	
Reverse transfer capacitance	C _{rss}	f=1MHz		185	280	
Turn-on time t _{on}	t _{d(on)}	V _{CC} =100V I _D =20A V _{GS} =10V		10	15	ns
			t _r		45	
Turn-off time t _{off}	t _{d(off)}	R _G =10Ω		225	340	
			t _f		120	
Avalanche capability	I _{AV}	L=100μH T _{ch} =25°C	20			A
Diode forward on-voltage	V _{SD}	I _F =20A V _{GS} =0V T _{ch} =25°C		0.93	1.40	V
Reverse recovery time	t _{rr}	I _F =20A V _{GS} =0V		250		ns
Reverse recovery charge	Q _{rr}	-di/dt=100A/μs T _{ch} =25°C		2.90		μC

Thermal characteristics


Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal resistance	R _{th(ch-c)}	channel to case			2.78	°C/W
	R _{th(ch-a)}	channel to ambient			62.5	°C/W

Characteristics






Maximum Avalanche energy vs. starting Tch
 $E_{as} = f(\text{starting Tch}) : V_{cc} = 24V_{AV}, I_{AV} \leq 20A, \text{Non-Repitative}$



Transient Thermal Impedance
 $Z_{th}(ch-c) = f(t) : D = t/T$





LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.