

2SK2339

Silicon N-Channel Power F-MOS

■ Features

- Avalanche energy capability guaranteed
- Low ON-resistance
- No secondary breakdown
- Low-voltage drive


■ Applications

- Non-contact relay
- Solenoid drive
- Motor drive
- Control equipment
- Switching mode regulator


■ Absolute Maximum Ratings (T_c = 25°C)

Parameter	Symbol	Rating	Unit	
Drain-Source breakdown voltage	V _{DSS}	80±10	V	
Gate-Source voltage	V _{GSS}	±15	V	
Drain current	DC	I _D	±10 A	
	Pulse	I _{DP}	±20 A	
Avalanche energy capability	EAS *	62.5	mJ	
Allowable power dissipation	T _c = 25°C	P _D	30	W
	T _a = 25°C		1.3	
Channel temperature	T _{ch}	150	°C	
Storage temperature	T _{stg}	-55 to +150	°C	

* L= 5mH, I_L= 5A, 1 pulse




■ Equivalent Circuit




■ Electrical Characteristics (T_c = 25°C)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Drain-Source cut-off current	I _{DSS}	V _{DS} = 70V, V _{GS} = 0			10	μ A
Gate-Source leakage current	I _{GSS}	V _{DS} = 0, V _{GS} =15V			±10	μ A
Drain-Source breakdown voltage	V _{DSS}	I _D =1mA, V _{GS} = 0	70		90	V
Gate threshold voltage	V _{th}	V _{DS} =10V, I _D =1mA	1		2.5	V
Drain-Source ON-resistance	R _{DS(on)1}	V _{GS} =10V, I _D = 5A		150	230	mΩ
	R _{DS(on)2}	V _{GS} = 4V, I _D = 5A		230	370	mΩ
Forward transadmittance	Y _{fs}	V _{DS} =10V, I _D = 5A	3	5.5		S
Diode forward voltage	V _{DSF}	I _{DR} =10A, V _{GS} = 0			-1.8	V
Reverse recovery time	t _{rr}	L=230μ H, V _{DD} = 30V, V _{GS} = 0		0.55		μ s
Reverse recovery charge	Q _{rr}	I _{DR} =10A, di/dt= 80A/μ s		2.2		μ s
Input capacitance	C _{iss}	V _{DS} =10V, V _{GS} = 0, f= 1MHz		85		pF
Output capacitance	C _{oss}		250	pF		
Feedback capacitance	C _{rss}		20	pF		
Turn-on time	t _{on}			0.5	μ s	
Fall time	t _f	V _{DD} = 30V, I _D = 5A		0.9		μ s
Turn-off time (delay time)	t _{d(off)}	V _{GS} =10V, R _L = 6Ω		1.9		μ s
Channel-Case heat resistance	R _{th(ch-c)}				4.2	°C/W
Channel-Atmosphere heat resistance	R _{th(ch-a)}				96	°C/W


Area of safe operation (ASO)




$P_D - T_a$




IAS - L-load




$I_D - V_{DS}$




$I_D - V_{GS}$




$V_{th} - T_C$




$R_{DS(on)} - I_D$




$R_{DS(on)} - V_{GS}$




$|Y_{fs}| - I_D$




$C_{iss}, C_{oss}, C_{rss} - V_{DS}$




$t_{d(off)}, t_r, t_{on} - I_D$




$V_{DS}, V_{GS} - Q_g$



$I_{SD} - V_{SD}$



$R_{th} - t_p$



Request for your special attention and precautions in using the technical information and semiconductors described in this material

- (1) An export permit needs to be obtained from the competent authorities of the Japanese Government if any of the products or technologies described in this material and controlled under the "Foreign Exchange and Foreign Trade Law" is to be exported or taken out of Japan.
- (2) The technical information described in this material is limited to showing representative characteristics and applied circuit examples of the products. It does not constitute the warranting of industrial property, the granting of relative rights, or the granting of any license.
- (3) The products described in this material are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (4) The products and product specifications described in this material are subject to change without notice for reasons of modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the guaranteed values, in particular those of maximum rating, the range of operating power supply voltage and heat radiation characteristics. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, redundant design is recommended, so that such equipment may not violate relevant laws or regulations because of the function of our products.
- (6) When using products for which dry packing is required, observe the conditions (including shelf life and after-unpacking standby time) agreed upon when specification sheets are individually exchanged.
- (7) No part of this material may be reprinted or reproduced by any means without written permission from our company.

Please read the following notes before using the datasheets

- A. These materials are intended as a reference to assist customers with the selection of Panasonic semiconductor products best suited to their applications.
Due to modification or other reasons, any information contained in this material, such as available product types, technical data, and so on, is subject to change without notice.
Customers are advised to contact our semiconductor sales office and obtain the latest information before starting precise technical research and/or purchasing activities.
- B. Panasonic is endeavoring to continually improve the quality and reliability of these materials but there is always the possibility that further rectifications will be required in the future. Therefore, Panasonic will not assume any liability for any damages arising from any errors etc. that may appear in this material.
- C. These materials are solely intended for a customer's individual use.
Therefore, without the prior written approval of Panasonic, any other use such as reproducing, selling, or distributing this material to a third party, via the Internet or in any other way, is prohibited.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.