

# Medium Power Transistor (50V, 0.5A)

2SD1949 / 2SD1484K / 2SC1741AS

**●Features**

- 1) High current. ( $I_C=5A$ )
- 2) Low saturation voltage, typically  $V_{CE(sat)} = 0.1V$  at  $I_C / I_B = 150mA / 15mA$ .

**●Packaging specifications and hFE**

Type	2SD1949	2SD1484K	2SC1741AS
Package	UMT3	SMT3	SPT
hFE	QR	QR	QR
Marking	Y*	Y*	—
Code	T106	T146	TP
Basic ordering unit (pieces)	3000	3000	5000

\* Denotes hFE

**●Absolute maximum ratings (Ta=25°C)**

Parameter	Symbol	Limits	Unit
Collector-base voltage	$V_{CBO}$	50	V
Collector-emitter voltage	$V_{CEO}$	50	V
Emitter-base voltage	$V_{EBO}$	5	V
Collector current	$I_C$	0.5	A
Collector power dissipation	Pc	0.2	W
		0.3	
Junction temperature	Tj	150	°C
Storage temperature	Tstg	-55~+150	°C

**●Electrical characteristics (Ta=25°C)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	$BV_{CBO}$	50	—	—	V	$I_C=100\mu A$
Collector-emitter breakdown voltage	$BV_{CEO}$	50	—	—	V	$I_C=1mA$
Emitter-base breakdown voltage	$BV_{EBO}$	5	—	—	V	$I_E=100\mu A$
Collector cutoff current	$I_{CBO}$	—	—	0.5	$\mu A$	$V_{CB}=30V$
Emitter cutoff current	$I_{EBO}$	—	—	0.5	$\mu A$	$V_{EB}=4V$
DC current transfer ratio	hFE	120	—	560	—	$V_{CE}/I_C=3V/0.1A$
Collector-emitter saturation voltage	$V_{CE(sat)}$	—	—	0.4	V	$I_C/I_B=150mA/15mA$
Transition frequency	$f_T$	—	250	—	MHz	$V_{CE}=5V, I_E=-20mA, f=100MHz$
Output capacitance	Cob	—	6.5	—	pF	$V_{CB}=10V, I_E=0A, f=1MHz$

(96-678-D15)

# Power Transistor (80V, 0.3A)

2SC3359S

**●Features**

- 1) High breakdown voltage,  $BV_{CEO}=80V$ .
- 2) Low saturation voltage, typically  $V_{CE(sat)} = 0.2V$  at  $I_C / I_B = 0.3A / 0.03A$ .

**●Packaging specifications and hFE**

Type	2SC3359S
Package	SPT
hFE	QR
Code	TP
Basic ordering unit (pieces)	5000

**●Absolute maximum ratings (Ta=25°C)**

Parameter	Symbol	Limits	Unit
Collector-base voltage	$V_{CBO}$	80	V
Collector-emitter voltage	$V_{CEO}$	80	V
Emitter-base voltage	$V_{EBO}$	5	V
Collector current	$I_C$	0.3	A
Collector power dissipation	Pc	0.3	W
Junction temperature	Tj	150	°C
Storage temperature	Tstg	-55~+150	°C

**●Electrical characteristics (Ta=25°C)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-emitter breakdown voltage	$BV_{CEO}$	80	—	—	V	$I_C=1mA$
Collector-base breakdown voltage	$BV_{CBO}$	80	—	—	V	$I_C=50\mu A$
Emitter-base breakdown voltage	$BV_{EBO}$	5	—	—	V	$I_E=50\mu A$
Collector cutoff current	$I_{CBO}$	—	—	0.5	$\mu A$	$V_{CB}=80V$
Emitter cutoff current	$I_{EBO}$	—	—	0.5	$\mu A$	$V_{EB}=4V$
Collector-emitter saturation voltage	$V_{CE(sat)}$	—	0.2	0.5	V	$I_C/I_B=0.3/0.03A$
DC current transfer ratio	hFE	120	—	390	—	$V_{CE}=3V, I_C=0.1A$
Transition frequency	$f_T$	50	150	—	MHz	$V_{CE}=5V, I_E=0.01A, f=100MHz$
Output capacitance	Cob	—	5	8	pF	$V_{CB}=10V, I_E=0A, f=1MHz$

(SPEC-D16)

This datasheet has been downloaded from:

[www.DatasheetCatalog.com](http://www.DatasheetCatalog.com)

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.