

# High-Frequency Amplifier Transistor (11V, 50mA, 3.2GHz)

## 2SC5662 / 2SC4726 / 2SC4083 / 2SC3838K / 2SC4043S

### ●Features

- 1) High transition frequency. (Typ.  $f_T = 1.5\text{GHz}$ )
- 2) Small  $r_{bb'}$ · $C_c$  and high gain. (Typ. 4ps)
- 3) Small NF.

### ● Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Collector-base voltage	$V_{CB0}$	20	V
Collector-emitter voltage	$V_{CE0}$	11	V
Emitter-base voltage	$V_{EB0}$	3	V
Collector current	$I_C$	50	mA
Collector power dissipation	$P_C$	0.15	W
		0.2	
		0.3	
Junction temperature	$T_J$	150	°C
Storage temperature	$T_{stg}$	-55~+150	°C

### ●Packaging specifications and $h_{FE}$

Type	2SC5662	2SC4726	2SC4083	2SC3838K	2SC4043S
Package	VMT3	EMT3	UMT3	SMT3	SPT
$h_{FE}$	NP	NP	NP	NP	P
Marking	AD	AD	1D	AD	-
Code	T2L	TL	T106	T146	TP
Basic ordering unit (pieces)	8000	3000	3000	3000	5000

### ●External dimensions (Units : mm)

<p>2SC5662</p> <p>ROHM : VMT3</p> <p>(1) Base (2) Emitter (3) Collector</p>
<p>2SC4726</p> <p>ROHM : EMT3 EIAJ : SC-75A</p> <p>(1) Emitter (2) Base (3) Collector</p>
<p>2SC4083</p> <p>ROHM : UMT3 EIAJ : SC-70</p> <p>(1) Emitter (2) Base (3) Collector</p> <p>Each lead has same dimensions</p>
<p>2SC3838K</p> <p>ROHM : SMT3 EIAJ : SC-59</p> <p>(1) Emitter (2) Base (3) Collector</p> <p>Each lead has same dimensions</p>
<p>2SC4043S</p> <p>ROHM : SPT EIAJ : SC-72</p> <p>(1) Emitter (2) Collector (3) Base</p> <p>Taping specifications</p>

2SC5662 / 2SC4726 / 2SC4083 /  
2SC3838K / 2SC4043S

Transistors

● Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	
Collector-base breakdown voltage	BV <sub>CB0</sub>	20	–	–	V	I <sub>c</sub> = 10μA	
Collector-emitter breakdown voltage	BV <sub>CE0</sub>	11	–	–	V	I <sub>c</sub> = 1mA	
Emitter-base breakdown voltage	BV <sub>EB0</sub>	3	–	–	V	I <sub>E</sub> = 10μA	
Collector cutoff current	I <sub>CB0</sub>	–	–	0.5	μA	V <sub>CB</sub> = 10V	
Emitter cutoff current	I <sub>EB0</sub>	–	–	0.5	μA	V <sub>EB</sub> = 2V	
Collector-emitter saturation voltage	V <sub>CE(sat)</sub>	–	–	0.5	V	I <sub>c</sub> /I <sub>E</sub> = 10mA/5mA	
DC current transfer ratio	2SC5662, 2SC4726, 2SC4083, 2SC3838K	h <sub>FE</sub>	56	–	180	–	V <sub>CE</sub> /I <sub>c</sub> = 10V/5mA
	2SC4043S		82	–	180		
Transition frequency	f <sub>T</sub>	1.4	3.2	–	GHz	V <sub>CE</sub> = 10V, I <sub>E</sub> = 10mA, f = 500MHz	
Output capacitance	C <sub>ob</sub>	–	0.8	1.5	pF	V <sub>CB</sub> = 10V, I <sub>E</sub> = 0A, f = 1MHz	
Collector-base time constant	τ <sub>cb</sub> -C <sub>c</sub>	–	4	12	ps	V <sub>CB</sub> = 10V, I <sub>c</sub> = 10mA, f = 31.8MHz	
Noise factor	NF	–	3.5	–	dB	V <sub>CE</sub> = 6V, I <sub>c</sub> = 2mA, f = 500MHz, R <sub>g</sub> = 50Ω	

This datasheet has been downloaded from:

[www.DatasheetCatalog.com](http://www.DatasheetCatalog.com)

Datasheets for electronic components.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.