


N-CHANNEL ENHANCEMENT MODE VERTICAL DMOS FET

2N7000P

ISSUE 2 – MARCH 94

FEATURES

- * 60 Volt V_{CEO}
- * $R_{DS(on)} = 5 \Omega$



E-Line
TO92 Compatible

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Drain-Source Voltage	V_{DS}	60	V
Continuous Drain Current at $T_{amb}=25^{\circ}C$	I_D	200	mA
Pulsed Drain Current	I_{DM}	500	mA
Gate-Source Voltage	V_{GS}	± 40	V
Power Dissipation at $T_{amb}=25^{\circ}C$	P_{tot}	400	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^{\circ}C$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Drain-Source Breakdown Voltage	BV_{DSS}	60		V	$I_D=10\mu A, V_{GS}=0V$
Gate-Source Threshold Voltage	$V_{GS(th)}$	0.8	3	V	$I_D=1mA, V_{DS}=V_{GS}$
Gate-Body Leakage	I_{GSS}		10	nA	$V_{GS}=\pm 15V, V_{DS}=0V$
Zero Gate Voltage Drain Current	I_{DSS}		1 1	μA mA	$V_{DS}=48V, V_{GS}=0$ $V_{DS}=48V, V_{GS}=0V, T=125^{\circ}C(2)$
On-State Drain Current(1)	$I_{D(on)}$	75		mA	$V_{DS}=10V, V_{GS}=4.5V$
Static Drain-Source On-State Voltage (1)	$V_{DS(on)}$		2.5 0.4	V V	$V_{GS}=10V, I_D=500mA$ $V_{GS}=4.5V, I_D=75mA$
Static Drain-Source On-State Resistance (1)	$R_{DS(on)}$		5	Ω	$V_{GS}=10V, I_D=500mA$
Forward Transconductance(1)(2)	g_{fs}	100		mS	$V_{DS}=10V, I_D=200mA$
Input Capacitance (2)	C_{iss}		60	pF	$V_{DS}=25V, V_{GS}=0V, f=1MHz$
Common Source Output Capacitance (2)	C_{oss}		25	pF	
Reverse Transfer Capacitance (2)	C_{rss}		5	pF	
Turn-On Time (2)(3)	$t_{(on)}$		10	ns	$V_{DD}=15V, I_D=500mA$ $R_g=25\Omega, R_L=25\Omega$
Turn-Off Time (2)(3)	$t_{(off)}$		10	ns	

- (1) Measured under pulsed conditions. Width=300 μs . Duty cycle $\leq 2\%$ (2) Sample test.
 (3) Switching times measured with 50 Ω source impedance and <5ns rise time on a pulse generator



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.