

2N 5368 through 2N 5375

COMPLEMENTARY SILICON GENERAL PURPOSE AMPLIFIERS AND SWITCHES

THE ABOVE TYPES ARE SILICON PLANAR EPITAXIAL TRANSISTORS FOR GENERAL PURPOSE AMPLIFIERS AND MEDIUM SPEED SWITCHING APPLICATIONS.

CASE TO-92F



ABSOLUTE MAXIMUM RATINGS

	2N5368 (NPN)	2N5372 (PNP)	2N5371 (NPN)
Collector-Base Voltage	60V	60V	40V
Collector-Emitter Voltage	30V	30V	30V
Emitter-Base Voltage	5V	5V	5V
Collector Current	500mA	500mA	500mA
Total Power Dissipation ($T_A \leq 25^\circ\text{C}$)	500mW **		
	derate 4mW/°C above 25°C		

Operating Junction & Storage Temperature T_j, T_{stg} -55 to 150°C

** 360mW in JEDEC registration.

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	TEST CONDITIONS
Collector-Base Breakdown Voltage	BV_{CBO}	↑ Note 1 ↓			V	$I_C=0.01\text{mA}$ $I_E=0$
Collector-Emitter Breakdown Voltage	$LV_{CEO} *$				V	$I_C=10\text{mA}$ $I_B=0$
Emitter-Base Breakdown Voltage	BV_{EBO}				V	$I_E=0.01\text{mA}$ $I_C=0$
Collector Cutoff Current	I_{CBO}				nA	$V_{CB}=40\text{V}$ $I_E=0$
				50	nA	$V_{CB}=40\text{V}$ $I_E=0$
				50	nA	$V_{CB}=30\text{V}$ $I_E=0$
Emitter Cutoff Current	I_{EBO}			50	nA	$V_{EB}=3\text{V}$ $I_C=0$
Collector-Emitter Saturation Voltage	$V_{CE(sat)} *$		0.18	0.3	V	$I_C=150\text{mA}$ $I_B=15\text{mA}$
Base-Emitter Saturation Voltage	$V_{BE(sat)} *$		0.84	1.3	V	$I_C=150\text{mA}$ $I_B=15\text{mA}$
Base-Emitter Voltage	$V_{BE} *$		0.8	1.2	V	$I_C=150\text{mA}$ $V_{CE}=10\text{V}$
Current Gain-Bandwidth Product	f_T				MHz	$I_C=20\text{mA}$ $V_{CE}=10\text{V}$
		250	370		MHz	$I_C=20\text{mA}$ $V_{CE}=10\text{V}$
		150	270			
Collector-Base Capacitance	C_{cb}				pF	$V_{CB}=10\text{V}$ $I_E=0$
				8	pF	$f=1\text{MHz}$
				10	pF	

Note 1 : Equal to the values of absolute maximum ratings.

* Pulse Test : Pulse Width=0.3ms, Duty Cycle=1%

For p-n-p devices, voltage and current values are negative.

MICRO ELECTRONICS LTD.

38 HUNG TO ROAD, KWUN TONG, HONG KONG. TELEX 43510
KWUN TONG P. O. BOX 69477 CABLE ADDRESS "MICROTRON"
TELEPHONE:- 3-430181-6 3-898363, 3-892423

FAX: 3-410321



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.