

High-Power NPN Silicon Transistor

... for use in power amplifier and switching circuits applications.

- Low Collector–Emitter Saturation Voltage –
 $V_{CE(sat)} = 0.75 \text{ Vdc (Max) @ } I_C = 10 \text{ Adc}$

*MAXIMUM RATINGS

Rating	Symbol	2N5302	Unit
Collector–Emitter Voltage	V_{CEO}	60	Vdc
Collector–Base Voltage	V_{CB}	60	Vdc
Collector Current – Continuous	I_C	30	Adc
Base Current	I_B	7.5	Adc
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	200 1.14	Watts W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-65 to +200	$^\circ\text{C}$


THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	θ_{JC}	0.875	$^\circ\text{C/W}$
Thermal Resistance, Case to Ambient	θ_{CA}	34	$^\circ\text{C/W}$

*Indicates JEDEC Registered Data.

2N5302

**30 AMPERE
POWER TRANSISTOR
NPN SILICON
60 VOLTS
200 WATTS**



**CASE 1-07
TO-204AA
(TO-3)**




Figure 1. Power Temperature Derating Curve

2N5302

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
*OFF CHARACTERISTICS				
Collector–Emitter Sustaining Voltage (Note 1) (I _C = 200 mA _{dc} , I _B = 0)	V _{CEO(sus)}	60	–	V _{dc}
Collector Cutoff Current (V _{CE} = 60 V _{dc} , I _B = 0)	I _{CEO}	–	5.0	mA _{dc}
Collector Cutoff Current (V _{CE} = 60 V _{dc} , V _{EB(off)} = 1.5 V _{dc})	I _{CEX}	–	1.0	mA _{dc}
Collector Cutoff Current (V _{CE} = 60 V _{dc} , V _{EB(off)} = 1.5 V _{dc} , T _C = 150°C)	I _{CEX}	–	10	mA _{dc}
Collector Cutoff Current (V _{CB} = 80 V _{dc} , I _E = 0)	I _{CBO}	–	1.0	mA _{dc}
Emitter Cutoff Current (V _{BE} = 5.0 V _{dc} , I _C = 0)	I _{EBO}	–	5.0	mA _{dc}

ON CHARACTERISTICS

DC Current Gain (Note 1) *(I _C = 1.0 A _{dc} , V _{CE} = 2.0 V _{dc}) *(I _C = 15 A _{dc} , V _{CE} = 2.0 V _{dc}) (I _C = 30 A _{dc} , V _{CE} = 4.0 V _{dc})	h _{FE}	40 15 5.0	– 60 –	–
*Collector–Emitter Saturation Voltage (Note 1) (I _C = 10 A _{dc} , I _B = 1.0 A _{dc}) (I _C = 20 A _{dc} , I _B = 2.0 A _{dc}) (I _C = 30 A _{dc} , I _B = 6.0 A _{dc})	V _{CE(sat)}	– – –	0.75 2.0 3.0	V _{dc}
*Base Emitter Saturation Voltage (Note 1) (I _C = 10 A _{dc} , I _B = 1.0 A _{dc}) (I _C = 15 A _{dc} , I _B = 1.5 A _{dc}) (I _C = 20 A _{dc} , I _B = 2.0 A _{dc})	V _{BE(sat)}	– – –	1.7 1.8 2.5	V _{dc}
*Base–Emitter On Voltage (Note 1) (I _C = 15 A _{dc} , V _{CE} = 2.0 V _{dc}) (I _C = 30 A _{dc} , V _{CE} = 4.0 V _{dc})	V _{BE(on)}	– –	1.7 3.0	V _{dc}

*DYNAMIC CHARACTERISTICS

Current–Gain – Bandwidth Product (I _C = 1.0 A _{dc} , V _{CE} = 10 V _{dc} , f = 1.0 MHz)	f _T	2.0	–	MHz
Small–Signal Current Gain (I _C = 1.0 A _{dc} , V _{CE} = 10 V _{dc} , f = 1.0 kHz)	h _{fe}	40	–	–

*SWITCHING CHARACTERISTICS

Rise Time	(V _{CC} = 30 V _{dc} , I _C = 10 A _{dc} , I _{B1} = I _{B2} = 1.0 A _{dc})	t _r	–	1.0	μs
Storage Time		t _s	–	2.0	μs
Fall Time		t _f	–	1.0	μs

*Indicates JEDEC Registered Data.

Note 1: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.

SWITCHING TIME EQUIVALENT TEST CIRCUITS




Figure 2. Turn–On time




Figure 3. Turn–Off time




Figure 4. Thermal Response




Figure 5. Active-Region Safe Operating Area




Figure 6. Capacitance versus Voltage




Figure 7. Turn-On Time




Figure 8. Turn-Off Time




Figure 9. DC Current Gain




Figure 10. Collector Saturation Region




Figure 11. Effects of Base-Emitter Resistance




Figure 12. "On" Voltages




Figure 13. Collector Cut-Off Region






Figure 14. Temperature Coefficients

2N5302

PACKAGE DIMENSIONS

TO-204 (TO-3) CASE 1-07 ISSUE Z



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. ALL RULES AND NOTES ASSOCIATED WITH REFERENCED TO-204AA OUTLINE SHALL APPLY.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	1.550 REF		39.37 REF	
B	---	1.050	---	26.67
C	0.250	0.335	6.35	8.51
D	0.038	0.043	0.97	1.09
E	0.055	0.070	1.40	1.77
G	0.430 BSC		10.92 BSC	
H	0.215 BSC		5.46 BSC	
K	0.440	0.480	11.18	12.19
L	0.665 BSC		16.89 BSC	
N	---	0.830	---	21.08
Q	0.151	0.165	3.84	4.19
U	1.187 BSC		30.15 BSC	
V	0.131	0.188	3.33	4.77

Notes

Notes

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

NORTH AMERICA Literature Fulfillment:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com
Fax Response Line: 303-675-2167 or 800-344-3810 Toll Free USA/Canada

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

EUROPE: LDC for ON Semiconductor – European Support

German Phone: (+1) 303-308-7140 (Mon-Fri 2:30pm to 7:00pm CET)
Email: ONlit-german@hibbertco.com
French Phone: (+1) 303-308-7141 (Mon-Fri 2:00pm to 7:00pm CET)
Email: ONlit-french@hibbertco.com
English Phone: (+1) 303-308-7142 (Mon-Fri 12:00pm to 5:00pm GMT)
Email: ONlit@hibbertco.com

EUROPEAN TOLL-FREE ACCESS*: 00-800-4422-3781

*Available from Germany, France, Italy, UK, Ireland

CENTRAL/SOUTH AMERICA:

Spanish Phone: 303-308-7143 (Mon-Fri 8:00am to 5:00pm MST)
Email: ONlit-spanish@hibbertco.com
Toll-Free from Mexico: Dial 01-800-288-2872 for Access –
then Dial 866-297-9322

ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support

Phone: 1-303-675-2121 (Tue-Fri 9:00am to 1:00pm, Hong Kong Time)
Toll Free from Hong Kong & Singapore:
001-800-4422-3781
Email: ONlit-asia@hibbertco.com

JAPAN: ON Semiconductor, Japan Customer Focus Center

4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031
Phone: 81-3-5740-2700
Email: r14525@onsemi.com

ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local Sales Representative.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.