



BSX 19

BSX 20

NPN SILICON PLANAR EPITAXIAL TRANSISTORS

MICRO ELECTRONICS

CASE T0-18

THE BSX19 AND BSX20 ARE NPN SILICON PLANAR EPITAXIAL TRANSISTORS DESIGNED FOR VERY HIGH SPEED SATURATED SWITCHING APPLICATIONS.



CBE

ABSOLUTE MAXIMUM RATINGS

Collector-Base Voltage	VCBO	40V
Collector-Emitter Voltage ($V_{BE}=0$)	VCES	40V
Collector-Emitter Voltage ($I_B=0$)	VCEO	15V
Emitter-Base Voltage	VEBO	4.5V
Collector Peak Current	ICM	500mA
Total Power Dissipation @ $T_A=25^\circ\text{C}$	P_{tot}	360mW
Operating Junction & Storage Temperature	T_j, T_{stg}	-65 to 200°C

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	BSX19		BSX20		UNIT	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
Collector-Emitter Breakdown Voltage	BVCEO	15		15		V	$I_C=10\text{mA}$ $I_B=0$
Collector-Emitter Breakdown Voltage	BVCER	20		20		V	$I_C=10\text{mA}$ $R_{BE}=10\Omega$
Collector Cutoff Current	ICBO	400		400		nA	$V_{CB}=20\text{V}$ $I_E=0$
		30		30		μA	$V_{CB}=20\text{V}$ $I_E=0$ $T_j=150^\circ\text{C}$
Collector Cutoff Current	ICES	0.4		0.4		μA	$V_{CE}=15\text{V}$ $V_{BE}=0$ $T_j=55^\circ\text{C}$
		1		1		μA	$V_{CE}=40\text{V}$ $V_{BE}=0$
Collector Cutoff Current	ICEV	0.6		0.6		μA	$V_{CE}=15\text{V}$ $V_{BE}=-3\text{V}$ $T_j=55^\circ\text{C}$
Emitter Cutoff Current	IEBO	10		10		μA	$V_{EB}=4.5\text{V}$ $I_C=0$
Collector-Emitter Saturation Voltage	VCE(sat)	0.25		0.25		V	$I_C=10\text{mA}$ $I_B=1\text{mA}$
		0.3				V	$I_C=10\text{mA}$ $I_B=0.6\text{mA}$
				0.3		V	$I_C=10\text{mA}$ $I_B=0.3\text{mA}$
		0.6		0.6		V	$I_C=100\text{mA}$ $I_B=10\text{mA}$

MICRO ELECTRONICS LTD.

38 HUNG TO ROAD, KWUN TONG, HONG KONG. TELEX 43510
 KWUN TONG P. O. BOX 69477 CABLE ADDRESS "MICROTRON"
 TELEPHONE: 3-430181-6 3-8933663 3-892423

FAX: 3-410321

1-2-BMP

- - - Continued - - -

PARAMETER	SYMBOL	BSX19		BSX20		UNIT	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
Base-Emitter Saturation Voltage	V _{BE(sat)}	0.7	0.85	0.7	0.85	V	I _C =10mA I _B =1mA
			1.5		1.5	V	I _C =100mA I _B =10mA
Base-Emitter Voltage	V _{BE}	0.35		0.35		V	I _C =30μA V _{CE} =20V T _j =100°C
D.C. Current Gain	H _{FE}	20	60	40	120		I _C =10mA V _{CE} =1V
		10		20			I _C =10mA V _{CE} =1V
		10		20			T _j =-55°C I _C =100mA V _{CE} =2V
Current Gain-Bandwidth Product	f _T	400		500		MHz	I _C =10mA V _{CE} =10V
Collector-Base Capacitance	C _{cb}		4		4	pF	V _{CB} =5V I _E =0 f=1MHz
Emitter-Base Capacitance	C _{eb}		4.5		4.5	pF	V _{EB} =1V I _C =0 f=1MHz
Turn-On Time	t _{on}		12		12	nS	I _C =10mA V _{CC} =3V I _{B1} =3mA
			7		7	nS	I _C =100mA V _{CC} =6V I _{B1} =40mA
Turn-Off Time	t _{off}		15		18	nS	I _C =10mA V _{CC} =3V I _{B1} =3mA -I _{B2} =1.5mA
			18		21	nS	I _C =100mA I _{B1} =40mA -I _{B2} =20mA
Storage Time	t _s		10		13	nS	I _C =10mA V _{CC} =10V I _{B1} =-I _{B2} =10mA



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.