

STANDARD RECOVERY DIODES

Stud Version

Features

- Wide current range
- High surge current capabilities
- Stud cathode and stud anode version
- Standard JEDEC types


400A

Typical Applications

- Converters
- Power supplies
- Machine tool controls
- High power drives

Major Ratings and Characteristics

| Parameters | 400U/R | Units |
|------------------|-------------|-------------------|
| $I_{F(AV)}$ | 400 | A |
| @ T_C | 120 | °C |
| $I_{F(RMS)}$ | 630 | A |
| I_{FSM} @ 50Hz | 8250 | A |
| @ 60Hz | 8640 | A |
| I^2t @ 50Hz | 340 | KA ² s |
| @ 60Hz | 311 | KA ² s |
| V_{RRM} range | 800 to 1600 | V |
| T_J | - 40 to 200 | °C |



400U(R) Series

Bulletin I2059 rev. C 03/03

International
IR Rectifier

ELECTRICAL SPECIFICATIONS

Voltage Ratings

| Type number | Voltage Code | V_{RRM} , maximum repetitive peak reverse voltage V | V_{RSM} , maximum non-repetitive peak rev. voltage V | I_{RRM} max. @ $T_J = T_J$ max. mA |
|-------------|--------------|--|---|--|
| 400U(R) | 80 | 800 | 900 | 15 |
| | 120 | 1200 | 1300 | |
| | 160 | 1600 | 1700 | |

Forward Conduction

| Parameter | 400U(R) | Units | Conditions |
|--|---------|--------------------|--|
| $I_{F(AV)}$ Max. average forward current @ Case temperature | 400 | A | 180° conduction, half sine wave |
| | 120 | °C | |
| $I_{F(RMS)}$ Max. RMS forward current | 630 | A | DC @ 110°C case temperature |
| I_{FSM} Max. peak, one-cycle forward, non-repetitive surge current | 8250 | A | t = 10ms No voltage |
| | 8640 | | t = 8.3ms reapplied |
| | 6940 | | t = 10ms 100% V_{RRM} |
| | 7270 | | t = 8.3ms reapplied |
| I^2t Maximum I^2t for fusing | 340 | KA ² s | t = 10ms No voltage |
| | 311 | | t = 8.3ms reapplied |
| | 241 | | t = 10ms 100% V_{RRM} |
| | 220 | | t = 8.3ms reapplied |
| $I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing | 3400 | KA ² √s | t = 0.1 to 10ms, no voltage reapplied |
| | | | |
| $V_{F(TO)1}$ Low level value of threshold voltage | 0.77 | V | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, $T_J = T_J$ max. |
| $V_{F(TO)2}$ High level value of threshold voltage | 0.85 | | $(I > \pi \times I_{F(AV)})$, $T_J = T_J$ max. |
| r_{f1} Low level value of forward slope resistance | 0.49 | mΩ | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, $T_J = T_J$ max. |
| r_{f2} High level value of forward slope resistance | 0.49 | | $(I > \pi \times I_{F(AV)})$, $T_J = T_J$ max. |
| V_{FM} Max. forward voltage drop | 1.62 | V | $I_{pk} = 1500A$, $T_J = T_J$ max, $t_p = 10ms$ sinusoidal wave |

Thermal and Mechanical Specifications

| Parameter | 400U(R) | Units | Conditions |
|--|-----------------|-------|--|
| T_J Max. junction operating temperature range | -40 to 200 | °C | |
| T_{stg} Max. storage temperature range | -40 to 200 | | |
| R_{thJC} Max. thermal resistance, junction to case | 0.15 | K/W | DC operation |
| R_{thCS} Max. thermal resistance, case to heatsink | 0.04 | | Mounting surface, smooth, flat and greased |
| T Max. allowed mounting torque ±10% | 27 | Nm | Not lubricated threads |
| wt Approximate weight | 250 | g | |
| Case style | DO-205AB (DO-9) | | See Outline Table |

ΔR_{thJC} Conduction

(The following table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC)

| Conduction angle | Sinusoidal conduction | Rectangular conduction | Units | Conditions |
|------------------|-----------------------|------------------------|-------|----------------------------|
| 180° | 0.020 | 0.013 | K/W | $T_J = T_{J \text{ max.}}$ |
| 120° | 0.023 | 0.023 | | |
| 90° | 0.029 | 0.031 | | |
| 60° | 0.042 | 0.044 | | |
| 30° | 0.073 | 0.074 | | |

Ordering Information Table


Device Code

| | | | | | |
|-----------|----------|----------|----------|------------|----------|
| 40 | 0 | U | R | 160 | D |
| 1 | 2 | 3 | 4 | 5 | 6 |

- 1** - 40 = Essential Part Number
- 2** - 0 = Standard Recovery Device
- 3** - U = Stud Normal Polarity (Cathode to Stud)
- 4** - None = Stud Normal Polarity (Cathode to Stud)
R = Stud Reverse Polarity (Anode to Stud)
- 5** - Voltage code: Code x 10 = V_{RRM} (See Voltage Ratings table)
- 6** - Diffused diode

NOTE: For Metric device M16 x 1.5 Contact Factory

Outline Table



400U(R) Series

Bulletin I2059 rev. C 03/03




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - Forward Power Loss Characteristics




Fig. 4 - Forward Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - Forward Voltage Drop Characteristics




Fig. 8 - Thermal Impedance Z_{thJC} Characteristic

400U(R) Series

Bulletin I2059 rev. C 03/03

International
IR Rectifier

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 03/03



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.