

PNP POWER TRANSISTOR SILICON AMPLIFIER

Qualified per MIL-PRF-19500/582

Devices

2N5679

2N5680

Qualified Level

JAN
JANTX
JANTXV

MAXIMUM RATINGS ($T_A = 25^{\circ}\text{C}$ unless otherwise noted)


Ratings	Symbol	2N5679	2N5680	Unit
Collector-Emitter Voltage	V_{CEO}	100	120	Vdc
Collector-Base Voltage	V_{CBO}	100	120	Vdc
Emitter-Base Voltage	V_{EBO}	4.0	4.0	Vdc
Collector Current	I_C	1.0	1.0	Adc
Base Current	I_B	0.5	0.5	Adc
Total Power Dissipation	P_T	@ $T_A = +25^{\circ}\text{C}^{(1)}$	1.0	W
		@ $T_C = +25^{\circ}\text{C}^{(2)}$	10	W
Operating & Storage Temperature Range	T_{op}, T_{stg}	-65 to +200	-65 to +200	$^{\circ}\text{C}$

THERMAL CHARACTERISTICS

Characteristics	Symbol	Max.	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	17.5	$^{\circ}\text{C}$

1) Derate linearly $5.7 \text{ mW}/^{\circ}\text{C}$ for $T_A > +25^{\circ}\text{C}$

2) Derate linearly $57 \text{ mW}/^{\circ}\text{C}$ for $T_C > +25^{\circ}\text{C}$



TO-39*
(TO-205AD)

*See appendix A for package outline

ELECTRICAL CHARACTERISTICS ($T_A = 25^{\circ}\text{C}$ unless otherwise noted)

Characteristics	Symbol	Min.	Max.	Unit
-----------------	--------	------	------	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage $I_C = 10 \text{ mAdc}$	$V_{(BR)CEO}$	100 120		Vdc
Emitter-Base Cutoff Current $V_{EB} = 4.0 \text{ Vdc}$	I_{EBO}		1.0	μAdc
Collector-Emitter Cutoff Current $V_{CE} = 70 \text{ Vdc}$ $V_{CE} = 80 \text{ Vdc}$	I_{CEO}		10	μAdc
Collector-Emitter Cutoff Current $V_{BE} = 1.5 \text{ Vdc}$ $V_{CE} = 100 \text{ Vdc}$ $V_{CE} = 120 \text{ Vdc}$	I_{CEX}		100	nAdc

2N5679, 2N5680 JAN SERIES

ELECTRICAL CHARACTERISTICS (con't)

Characteristics	Symbol	Min.	Max.	Unit
-----------------	--------	------	------	------

ON CHARACTERISTICS

Forward Current Transfer Ratio I _C = 250 mA _{dc} , V _{CE} = 2.0 V _{dc} I _C = 500 mA _{dc} , V _{CE} = 2.0 V _{dc} I _C = 1.0 A _{dc} , V _{CE} = 2.0 V _{dc}	h _{FE}	40 20 5	150	
Collector-Emitter Saturation Voltage I _C = 250 mA _{dc} , I _B = 25 mA _{dc} I _C = 500 mA _{dc} , I _B = 50 mA _{dc}	V _{CE(sat)}		0.6 1.0	V _{dc}
Base-Emitter Saturation Voltage I _C = 250 mA _{dc} , I _B = 25 mA _{dc} I _C = 500 mA _{dc} , I _B = 50 mA _{dc}	V _{BE(sat)}		1.1 1.3	V _{dc}

DYNAMIC CHARACTERISTICS

Magnitude of Common Emitter Small-Signal Short Circuit Forward-Current Transfer Ratio I _C = 0.1 A _{dc} , V _{CE} = 10 V _{dc} , f = 10 kHz	h _{fe}	3.0		
Small Signal Short Circuit Forward-Current Transfer Ratio I _C = 0.2 A _{dc} , V _{CE} = 1.5 V _{dc} , f = 1.0 kHz	h _{fe}	40		
Output Capacitance V _{CB} = 20 V _{dc} , I _E = 0, f = 1 MHz	C _{obo}		50	pF

SAFE OPERATING AREA

<p>DC Tests T_C = +25°C, 1 Cycle, t ≥ 0.5 s</p> <p>Test 1 V_{CE} = 2 V_{dc}, I_C = 1.0 A_{dc}</p> <p>Test 2 V_{CE} = 10 V_{dc}, I_C = 1.0 A_{dc}</p> <p>Test 3 V_{CE} = 90 V_{dc}, I_C = 50 mA_{dc}</p>



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.