


MICRO ELECTRONICS

2SA928
PNP
SILICON
TRANSISTOR

DESCRIPTION

2SA928 is PNP silicon planar transistor dedesigned for audio power amplifier.

TO-92B



ECB

ABSOLUTE MAXIMUM RATINGS

Collector-Base Voltage	VCBO	30V
Collector-Emitter Voltage	VCEO	30V
Emitter-Base Voltage	VEBO	5V
Collector Current	IC	2A
Continuous Power Dissipation	Pd	1W
Operating & Storage Junction Temperature	Tj, Tstg	-55 to +150°C

ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	CONDITIONS
Collector-Base Breakdown Voltage	BVCBO	30				IC=100μA IE=0
Collector-Emitter Breakdown Voltage	BVCEO	30			V	IC=10mA IB=0
Emitter-Base Breakdown Voltage	BVEBO	5			V	IE=1mA IC=0
Collector Cutoff Current	ICBO			100	nA	VCB=30V IE=0
Emitter Cutoff Current	IEBO			100	nA	VEB=5V IC=0
D.C. Current Gain	HFE	100		320		IC=500mA VCE=2V
	GROUP -O	100		200		IC=500mA VCE=2V
	GORUP -Y	160		320		IC=500mA VCE=2V
Base-Emitter Voltage	VBE			1.0	V	IC=500mA VCE=2V
Collector-Emitter Saturation Voltage	VCE(sat)			2.0	V	IC=1.5A IB=0.03A
Output Capacitance	Cob		48		pF	VCB=10V f=1MHz
Current Gain Bandwidth Product	fT		120		MHz	IC=500mA VCE=2V



MICRO ELECTRONICS LTD. 美科有限公司

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.
Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex: 43510 Micro Hx. Tel: 2343 0181-5

1-2. 0-9



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.