

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

2N5629 2N5630 NPN
2N6029 2N6030 PNP

COMPLEMENTARY SILICON POWER
TRANSISTORS

JEDEC TO-3 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N5629 2N6029 series types are complementary silicon power transistors manufactured by the epitaxial base process, mounted in a hermetically sealed metal case designed for high voltage and high power amplifier applications.

MAXIMUM RATINGS ($T_C=25^\circ\text{C}$ unless otherwise noted)

	SYMBOL	2N5629 2N6029	2N5630 2N6030	UNIT
Collector-Emitter Voltage	V_{CE0}	100	120	V
Collector-Base Voltage	V_{CB0}	100	120	V
Emitter-Base Voltage	V_{EBO}		7.0	V
Collector Current	I_C		16	A
Collector Current-PEAK	I_{CM}		20	A
Base Current	I_B		5.0	A
Power Dissipation	P_D		200	W
Operating and Storage Junction Temperature	T_J, T_{STG}	-60 to +200		$^\circ\text{C}$
Thermal Resistance	θ_{JC}	0.875		$^\circ\text{C}/\text{W}$

ELECTRICAL CHARACTERISTICS ($T_C=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
I_{CEV}	$V_{CE}=\text{Rated } V_{CB}, V_{EB}(\text{OFF})=1.5\text{V}$		1.0	mA
I_{CEV}	$V_{CE}=\text{Rated } V_{CB}, V_{EB}(\text{OFF})=1.5\text{V}, T_C=150^\circ\text{C}$		5.0	mA
I_{CEO}	$V_{CE}=\frac{1}{2} \text{ Rated } V_{CE0}$		1.0	mA
I_{CBO}	$V_{CB}=\text{Rated } V_{CBO}$		1.0	mA
I_{EBO}	$V_{BE}=7.0\text{V}$		1.0	mA
BV_{CE0}	$I_C=200\text{mA}$ (2N5629, 2N6029)	100		V
BV_{CE0}	$I_C=200\text{mA}$ (2N5630, 2N6030)	120		V
$V_{CE}(\text{SAT})$	$I_C=10\text{A}, I_B=1.0\text{A}$		1.0	V
$V_{CE}(\text{SAT})$	$I_C=16\text{A}, I_B=4.0\text{A}$		2.0	V
$V_{BE}(\text{SAT})$	$I_C=10\text{A}, I_B=1.0\text{A}$		1.8	V
$V_{BE}(\text{ON})$	$V_{CE}=2.0\text{V}, I_C=8.0\text{A}$		1.5	V
h_{FE}	$V_{CE}=2.0\text{V}, I_C=8.0\text{A}$ (2N5629, 2N6029)	25	100	
h_{FE}	$V_{CE}=2.0\text{V}, I_C=8.0\text{A}$ (2N5630, 2N6030)	20	80	
h_{FE}	$V_{CE}=2.0\text{V}, I_C=16\text{A}$	4.0	-	
h_{fe}	$V_{CE}=10\text{V}, I_C=4.0\text{A}, f=10\text{kHz}$	15	-	
f_T	$V_{CE}=20\text{V}, I_C=1.0\text{A}, f=0.5\text{MHz}$	1.0	-	MHz
C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=0.1\text{MHz}$		500	pF
C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=0.1\text{MHz}$		1000	pF



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.