

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

CSSD2003

SILICON SWITCHING DIODE

JEDEC DO-35 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR CSSD2003 is a high speed Silicon Switching Diode designed for computer and general purpose applications requiring a high breakdown voltage.

MAXIMUM RATINGS ($T_A=25^\circ\text{C}$)

	SYMBOL		UNIT
Peak Repetitive Reverse Voltage	V_{RRM}	250	V
Peak Working Reverse Voltage	V_{RWM}	250	V
Average Forward Current	I_O	250	mA
Forward Steady-State Current	I_F	400	mA
Peak Forward Surge Current (1.0s pulse)	I_{FSM}	1.0	A
Power Dissipation	P_D	500	mW
Operating and Storage Junction Temperature	T_J, T_{STG}	-65 TO +200	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
BV_R	$I_R=100\mu\text{A}$	250		V
I_R	$V_R=150\text{V}$		100	nA
I_R	$V_R=150\text{V}, T_A=150^\circ\text{C}$		100	μA
V_F	$I_F=100\text{mA}$		1.0	V
C_T	$V_R=0, f=1.0\text{MHz}$		5.0	pF
t_{rr}	$I_F=I_R=30\text{mA}, \text{Recov to } 3.0\text{mA}, R_L=100\Omega$		50	ns



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.