


# GI820 THRU GI828

## FAST SWITCHING PLASTIC RECTIFIER

*Reverse Voltage - 50 to 800 Volts      Forward Current - 5.0 Amperes*

### Case Style P600



Dimensions in inches and (millimeters)

### FEATURES

- ◆ Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- ◆ High surge current capability
- ◆ High forward current operation
- ◆ Fast switching for high efficiency
- ◆ Construction utilizes void-free molded plastic technique
- ◆ Uniform molded body
- ◆ High temperature soldering guaranteed: 250°C/10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension



### MECHANICAL DATA

**Case:** Void-free molded plastic body

**Terminals:** Plated axial leads, solderable per MIL-STD-750, Method 2026

**Polarity:** Color band denotes cathode end

**Mounting Position:** Any

**Weight:** 0.07 ounce, 2.1grams

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

	SYMBOLS	GI820	GI821	GI822	GI824	GI826	GI828	UNITS
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	Volts
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	Volts
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	Volts
Maximum non-repetitive peak reverse voltage	$V_{RSM}$	75	150	250	450	650	880	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length at $T_A=55^\circ\text{C}$	$I_{(AV)}$	5.0						Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	300.0						Amps
Maximum instantaneous forward voltage at 5.0A $T_J=25^\circ\text{C}$ at 15.7A $T_J=150^\circ\text{C}$	$V_F$	1.10 1.05						Volts
Maximum reverse current at rated DC blocking voltage $T_A=25^\circ\text{C}$ $T_A=100^\circ\text{C}$	$I_R$	10.0 1.0						$\mu\text{A}$ mA
Typical junction capacitance (NOTE 1)	$C_J$	300.0						pF
Maximum reverse recovery time (NOTE 2)	$t_{rr}$	200.0						ns
Maximum reverse recovery current (NOTE 2)	$I_{RM(REC)}$	2.0						Amps
Typical thermal resistance (NOTE 3)	$R_{\theta JA}$	10.0						$^\circ\text{C}/\text{W}$
Operating junction and storage temperature range	$T_J, T_{STG}$	-50 to +150						$^\circ\text{C}$

### NOTES:

(1) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts

(2) Reverse recovery test conditions:  $I_F=1.0\text{A}$ ,  $V_R=30\text{V}$ ,  $di/dt=50\text{A}/\mu\text{s}$ , and  $I_{rr}=10\% I_{RM}$  for measurement of  $t_{rr}$

(3) Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, with both leads equally to heat sink

# RATINGS AND CHARACTERISTIC CURVES G1820 THRU G1828

FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - FORWARD CURRENT DERATING CURVE




FIG. 3 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 4 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 5 - TYPICAL REVERSE CHARACTERISTICS





FIG. 6 - TYPICAL THERMAL RESISTANCE





LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.