

6367254 MOTOROLA SC (XSTRS/R F)

96D 82066 D

T-31-15

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	V _{CEO}	20	Vdc
Collector-Base Voltage	V _{CBO}	20	Vdc
Emitter-Base Voltage	V _{EBO}	3.0	Vdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR-5 Board,* T _A = 25°C Derate above 25°C	P _D	225	mW
Thermal Resistance Junction to Ambient	R _{θJA}	556	°C/mW
Total Device Dissipation Alumina Substrate,** T _A = 25°C Derate above 25°C	P _D	300	mW
Thermal Resistance Junction to Ambient	R _{θJA}	417	°C/mW
Junction and Storage Temperature	T _J , T _{stg}	150	°C


*FR-5 = 1.0 x 0.75 x 0.62 in.

**Alumina = 0.4 x 0.3 x 0.024 in. 99.5% alumina.

DEVICE MARKING

MMBTH81 = 3D

MMBTH81

CASE 318-02/03, STYLE 6
SOT-23 (TO-236AA/AB)

UHF/VHF TRANSISTOR

PNP SILICON

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted.)


Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector-Emitter Breakdown Voltage (I _C = 1.0 mA _{dc} , I _B = 0)	V _{(BR)CEO}	20	—	—	Vdc
Collector-Base Breakdown Voltage (I _C = 10 μA _{dc} , I _E = 0)	V _{(BR)CBO}	20	—	—	Vdc
Emitter-Base Breakdown Voltage (I _E = 10 μA _{dc} , I _C = 0)	V _{(BR)EBO}	3.0	—	—	Vdc
Collector Cutoff Current (V _{CB} = 10 Vdc, I _E = 0)	I _{CBO}	—	—	100	nA _{dc}
Emitter Cutoff Current (V _{BE} = 2.0 Vdc, I _C = 0)	I _{EBO}	—	—	100	nA _{dc}
ON CHARACTERISTICS					
DC Current Gain (I _C = 5.0 mA _{dc} , V _{CE} = 10 Vdc)	h _{FE}	60	—	—	—
Collector-Emitter Saturation Voltage (I _C = 5.0 mA _{dc} , I _B = 0.5 mA _{dc})	V _{CE(sat)}	—	—	0.5	Vdc
Base-Emitter On Voltage (I _C = 5.0 mA _{dc} , V _{CE} = 10 Vdc)	V _{BE(on)}	—	—	0.9	Vdc
SMALL-SIGNAL CHARACTERISTICS					
Current-Gain — Bandwidth Product (I _C = 5.0 mA _{dc} , V _{CE} = 10 Vdc, f = 100 MHz)	f _T	600	—	—	MHz
Collector-Base Capacitance (V _{CB} = 10 Vdc, I _E = 0, f = 1.0 MHz)	C _{cb}	—	—	0.85	pF
Collector-Emitter Capacitance (I _B = 0, V _{CB} = 10 Vdc, f = 1.0 MHz)	C _{ce}	—	—	0.65	pF

6367254 MOTOROLA SC (XSTRS/R F)

96D 82146 D

T-29-19
2N2945
2N2946

CASE 26-03, STYLE 1
 TO-46 (TO-206AB)



TRANSISTOR
 PNP SILICON

Refer to 2N2944A for graphs.

MAXIMUM RATINGS

Rating	Symbol	2N2945	2N2946	Unit
Emitter-Collector Voltage	V_{ECO}	20	35	Vdc
Collector-Base Voltage	V_{CBO}	25	40	Vdc
Emitter-Base Voltage	V_{EBO}	25	40	Vdc
Collector Current — Continuous	I_C	100		Adc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above 25°C	P_D	400	2.3	mW mW/°C
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	2.0	11.43	Watts mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-65 to +200		°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	87.5	°C/W
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	435	°C/W

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector Cutoff Current ($V_{CB} = 25 \text{ Vdc}, I_E = 0$) ($V_{CB} = 40 \text{ Vdc}, I_E = 0$)	I_{CBO}	—	—	0.2 0.5	nAdc
Emitter Cutoff Current ($V_{EB} = 25 \text{ Vdc}, I_C = 0$) ($V_{EB} = 40 \text{ Vdc}, I_C = 0$)	I_{EBO}	—	—	0.2 0.5	nAdc
ON CHARACTERISTICS					
DC Current Gain ($I_C = 1.0 \text{ mAdc}, V_{CE} = 0.5 \text{ Vdc}$)	h_{FE}	40 30	160 130	—	—
*DC Current Gain (Inverted Connection) ($I_B = 200 \mu\text{Adc}, V_{EC} = 0.5 \text{ Vdc}$)	$h_{FE(inv)}$	4.0 3.0	17 15	—	—
Offset Voltage ($I_B = 200 \mu\text{Adc}, I_E = 0$)	$V_{EC(ofs)}$	—	0.23 0.27	0.5 0.8	mVdc
($I_B = 1.0 \text{ mAdc}, I_E = 0$)		—	0.5 0.6	1.0 2.0	
($I_B = 2.0 \text{ mAdc}, I_E = 0$)		—	0.9 1.0	1.6 2.5	
SMALL-SIGNAL CHARACTERISTICS					
Current-Gain — Bandwidth Product ($I_C = 1.0 \text{ mAdc}, V_{CE} = 6.0 \text{ Vdc}, f = 1.0 \text{ MHz}$)	f_T	5.0 3.0	13 12	—	MHz
Output Capacitance ($V_{CB} = 6.0 \text{ Vdc}, I_E = 0, f = 500 \text{ kHz}$)	C_{obo}	—	3.2	10	pF
Input Capacitance ($V_{EB} = 6.0 \text{ Vdc}, I_C = 0, f = 500 \text{ kHz}$)	C_{ibo}	—	1.9	6.0	pF
"ON" Series Resistance ($I_B = 1.0 \text{ mAdc}, I_E = 0, I_C = 100 \mu\text{Arms}, f = 1.0 \text{ kHz}$)	r_{ec}	—	4.5 5.0	35 45	Ohms

*Indicates Data in addition to JEDEC Requirements.

6367254 MOTOROLA SC (XSTRS/R F)

96D 82220 D
T-35-17


MAXIMUM RATINGS

Rating	Symbol	2N3734	2N3735 2N3737	Unit
Collector-Emitter Voltage	V _{CEO}	30	50	V _{dc}
Collector-Base Voltage	V _{CBO}	50	75	V _{dc}
Emitter-Base Voltage	V _{EBO}	5.0		V _{dc}
Collector Current — Continuous	I _C	1.5		A _{dc}
		TO-39 2N3734 2N3735	TO-46 2N3737	
Total Device Dissipation @ T _A = 25°C Derate above 25°C	P _D	1.0 5.71	0.5 2.86	Watt mW/°C
Total Device Dissipation @ T _C = 26°C Derate above 25°C	P _D	4.0 22.8	2.0 11.4	Watts mW/°C
Operating and Storage Junction Temperature Range	T _J , T _{stg}	-65 to +200		°C


THERMAL CHARACTERISTICS

Characteristic	Symbol	2N3734	2N3735 2N3737	Unit
Thermal Resistance, Junction to Case	R _{θJC}	0.044	0.088	°C/mW
Thermal Resistance, Junction to Ambient	R _{θJA}	0.175	0.35	°C/mW

2N3734
2N3735
CASE 79-02, STYLE 1
TO-39 (TO-205AD)



2N3737
CASE 26-03, STYLE 1
TO-46 (TO-206AD)



GENERAL PURPOSE
TRANSISTOR

NPN SILICON

Refer to 2N3725 for graphs.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector-Emitter Breakdown Voltage(1) (I _C = 10 mA _{dc} , I _B = 0)	V _{(BR)CEO}	30 50	—	V _{dc}
Collector-Base Breakdown Voltage (I _C = 10 μA _{dc} , I _E = 0)	V _{(BR)CBO}	50 75	—	V _{dc}
Emitter-Base Breakdown Voltage (I _E = 10 μA _{dc} , I _C = 0)	V _{(BR)EBO}	5.0	—	V _{dc}
Collector Cutoff Current (V _{CE} = 25 V _{dc} , V _{EB} = 2 V _{dc} , T _A = 100°C) (V _{CE} = 25 V _{dc} , V _{EB} = 2 V _{dc} , T _A = 100°C) (V _{CE} = 40 V _{dc} , V _{EB} = 2 V _{dc}) (V _{CE} = 40 V _{dc} , V _{EB} = 2 V _{dc} , T _A = 100°C)	I _{CEX}	—	0.20 20 0.20 20	μA _{dc}
Base Cutoff Current (V _{CE} = 25 V _{dc} , V _{EB} = 2 V _{dc}) (V _{CE} = 40 V _{dc} , V _{EB} = 2 V _{dc})	I _{BL}	—	0.3 0.3	μA _{dc}
ON CHARACTERISTICS				
DC Current Gain(1) (I _C = 10 mA _{dc} , V _{CE} = 1 V _{dc}) (I _C = 150 mA _{dc} , V _{CE} = 1 V _{dc}) (I _C = 500 mA _{dc} , V _{CE} = 1 V _{dc}) (I _C = 1 A _{dc} , V _{CE} = 1.5 V _{dc}) (I _C = 1.5 A _{dc} , V _{CE} = 5 V _{dc})	h _{FE}	35 40 35 30 20	— — — 120 80	—
Collector-Emitter Saturation Voltage(1) (I _C = 10 mA _{dc} , I _B = 1 mA _{dc}) (I _C = 150 mA _{dc} , I _B = 15 mA _{dc}) (I _C = 500 mA _{dc} , I _B = 50 mA _{dc}) (I _C = 1 A _{dc} , I _B = 100 mA _{dc})	V _{CE(sat)}	—	0.2 0.3 0.5 0.9	V _{dc}
Base-Emitter Saturation Voltage(1) (I _C = 10 mA _{dc} , I _B = 1 mA _{dc}) (I _C = 150 mA _{dc} , I _B = 15 mA _{dc}) (I _C = 500 mA _{dc} , I _B = 50 mA _{dc}) (I _C = 1 A _{dc} , I _B = 100 mA _{dc})	V _{BE(sat)}	—	0.8 1.0 1.2 1.4	V _{dc}

6367254 MOTOROLA SC (XSTRS/R F)

96D 82221 D

2N3737

T-35-17

ELECTRICAL CHARACTERISTICS (continued) ($T_A = 25^\circ\text{C}$ unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
SMALL-SIGNAL CHARACTERISTICS				
Output Capacitance ($V_{CB} = 10\text{ Vdc}$, $I_E = 0$, $f = 100\text{ kHz}$)	C_{obo}	—	9.0	pF
Input Capacitance ($V_{BE} = 0.5\text{ Vdc}$, $I_C = 0$, $f = 100\text{ kHz}$)	C_{ibo}	—	80	pF
Small-Signal Current Gain ($I_C = 50\text{ mAdc}$, $V_{CE} = 10\text{ Vdc}$, $f = 100\text{ MHz}$)	h_{fe}	2.5	—	—
SWITCHING CHARACTERISTICS				
Turn-On Time ($V_{CC} = 30\text{ V}$, $V_{BE(off)} = 2.0\text{ V}$, $I_C = 1.0\text{ Amp}$, $I_{B1} = 100\text{ mA}$)	t_{on}	—	40	ns
Turn-Off Time ($V_{CC} = 30\text{ V}$, $V_{BE(off)} = 2.0\text{ V}$, $I_C = 1.0\text{ Amp}$, $I_{B1} = 100\text{ mA}$)	t_{off}	—	60	ns
Total Control Charge ($I_C = 1\text{ Amp}$, $I_B = 100\text{ mA}$, $V_{CC} = 30\text{ V}$)	Q_T	—	10	NC

(1) Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2.0\%$.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.