

N-CHANNEL J-FET

Qualified per MIL-PRF-19500/431

Devices

2N4091

2N4092

2N4093


Qualified Level

JANTX
JANTXV

ABSOLUTE MAXIMUM RATINGS ($T_A = +25^{\circ}\text{C}$ unless otherwise noted)

Parameters / Test Conditions	Symbol	Value	Units
Gate-Source Voltage	V_{GS}	-40	V
Drain-Source Voltage	V_{DS}	40	V
Drain-Gate Voltage	V_{DG}	40	V
Gate Current	I_G	10	mAdc
Power Dissipation ⁽¹⁾	P_T	0.36	W
$T_A = +25^{\circ}\text{C}$			
Operating Junction	T_j	-65 to +175	$^{\circ}\text{C}$
Operating Storage Temperature Range	T_{stg}	-65 to +200	$^{\circ}\text{C}$

(1) Derate linearly 2.4 mW/ $^{\circ}\text{C}$ for $T_A > 25^{\circ}\text{C}$.



*See appendix A for package outline

ELECTRICAL CHARACTERISTICS ($T_C = +25^{\circ}\text{C}$ unless otherwise noted)

PARAMETERS / TEST CONDITIONS	Symbol	Min.	Max.	Units
Gate-Source Breakdown Voltage $V_{DS} = 0, I_G = -1.0 \mu\text{Adc}$	$V_{(BR)GSS}$	-40		Vdc
Gate Reverse Current $V_{DS} = 0, V_{GS} = -20 \text{Vdc}$	I_{GSS}		-0.1	ηA
Drain Current $V_{GS} = -12, V_{DS} = 20 \text{Vdc}$ 2N4091 $V_{GS} = -8.0, V_{DS} = 20 \text{Vdc}$ 2N4092 $V_{GS} = -6.0, V_{DS} = 20 \text{Vdc}$ 2N4093	$I_{D(off)}$		0.1	ηA
Drain Current $V_{GS} = 0, V_{DS} = 20 \text{Vdc}$ 2N4091 2N4092 2N4093	I_{DSS}	30 15 8.0		mA

2N4091, 2N4092, 2N4093 JAN SERIES

ELECTRICAL CHARACTERISTICS ($T_C = 25^{\circ}C$ unless otherwise noted) (con't)

PARAMETERS / TEST CONDITIONS		Symbol	Min.	Max.	Units	
Static Drain - Source On-State Resistance $V_{GS} = 0, I_D = 1.0 \text{ mAdc}$		$r_{DS(on)}$		30	Ω	
2N4091			50			
2N4092 2N4093			80			
Drain - Source On-State Voltage $V_{GS} = 0, I_D = 6.6 \text{ mAdc}$ $V_{GS} = 0, I_D = 4.0 \text{ mAdc}$ $V_{GS} = 0, I_D = 2.5 \text{ mAdc}$		$V_{DS(on)}$		0.2	Vdc	
2N4091			0.2			
2N4092 2N4093			0.2			
Small-Signal, Common-Source Reverse Transfer Capacitance $V_{GS} = 20 \text{ Vdc}, V_{DS} = 0, f = 1.0 \text{ MHz}$		C_{rss}		5.0	pF	
Small-Signal, Common-Source Short-Circuit Input Capacitance $V_{GS} = 0, V_{DS} = 20 \text{ Vdc}, f = 1.0 \text{ MHz}$		C_{iss}		16	pF	
Turn-On Delay Time	2N4091 2N4092 2N4093	See Figure 3 of MIL-PRF- 19500/431	$t_{d_{on}}$	15	ηs	
Rise Time	2N4091 2N4092 2N4093			t_r		10
Turn-Off Delay Time	2N4091 2N4092 2N4093					$t_{d_{off}}$
		60				
		80				



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.