



Rectifiers, General Purpose (Continued)

I_O (AMPS)	12	16	20	40
@ T_C (°C)	150	150	150	150
I_{FSM} (AMPS)	300	325	350	800
CASE	 DO-4*		 DO-5*	
V_{RRM} (VOLTS)				
100	CR12-010	CR16-010	CR20-010	CR40-010
200	CR12-020	CR16-020	CR20-020	CR40-020
400	CR12-040	CR16-040	CR20-040	CR40-040
600	CR12-060	CR16-060	CR20-060	CR40-060
800	CR12-080	CR16-080	CR20-080	CR40-080
1000	CR12-100	CR16-100	CR20-100	CR40-100
1200	CR12-120	CR16-120	CR20-120	CR40-120

V_F MAX @ $I_F = I_O$	1.1V	1.1V	1.1V	1.1V
-------------------------	------	------	------	------

I_R MAX @ V_{RRM}	10 μ A	10 μ A	10 μ A	100 μ A
-----------------------	------------	------------	------------	-------------

* Standard polarity is cathode to case. For reverse polarity add "R" suffix to part number.



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.