

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

2N3668
2N3669
2N3670
2N4103

SILICON CONTROLLED RECTIFIER
16 AMPS
220 THRU 800 VOLTS
JEDEC TO-3 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N3668, 2N3669, 2N3670, 2N4103 types are hermetically sealed silicon SCR's designed for sensing circuit applications and control systems. Higher voltage devices and electrical selections are available on special order.

MAXIMUM RATINGS (T_C=25° unless otherwise noted)

	SYMBOL	2N3668	2N3669	2N3670	2N4103	UNIT
Peak Repetitive Off-State Voltage	V _{RRM}	100	200	400	600	V
Peak Repetitive Off-State Voltage	V _{DRM}	200	400	600	800	V
RMS On-State Current (T _C =90°C)	I _T (RMS)			16		A
Peak One Cycle Surge (60Hz, T _C =80°C)	I _{TSM}			200		A
Peak Gate Current	I _{GM}			4.0		A
Average Gate Power Dissipation	P _G (AV)			0.5		W
Operating and Storage Junction Temperature	T _J , T _{STG}		-40 TO +125			°C
Thermal Resistance	θ _{JC}			1.7		°C/W

ELECTRICAL CHARACTERISTICS (T_C=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
I _{RRM}	V _R =Rated V _{RRM} , T _C =100°C			1.0	mA
I _{DRM}	V _D =Rated V _{DRM} , T _C =100°C			2.0	mA
V _{TM}	I _T =25A			1.8	V
I _{GT}	V _D =7.0V	1.0		40	mA
V _{GT}	V _D =7.0V			2.0	V
I _H	R _G =1.0kΩ	0.5		50	mA
dv/dt	V _D =.67 x V _{DRM} , R _G =1.0kΩ, T _C =100°C	10	400		V/μs
t _{gd}	I _G =125mA, di _G /dt=1.25A/μs			500	ns
t _q	V _D =.67 x V _{DRM} , V _R =35V, I _T =10A, T _C =90°C			50	μs



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.