

INTERNATIONAL RECTIFIER



2N681 & 2N5204 SERIES

25 and 35 Amp RMS SCRs

Major Ratings and Characteristics



	2N681-92	2N5204-07	Units
I_T (RMS)	25	35	A
I_T (AV)	16*	22*	A
@ T_C	-65 to 65*	-40 to 40	°C
I_{TSM}	@ 50 Hz	145	A
	@ 60 Hz	150*	
		300*	
i^2t	@ 50 Hz	103	A ² s
	@ 60 Hz	94	
		375	
I_{GT}	40	40	mA
dv/dt	—	100*	V/ μ s
di/dt	75–100	100	A/ μ s
T_J	-65 to 125*	-40 to 125*	°C
V_{RRM}, V_{DRM} range	25–800	600–1200	V

*JEDEC registered value.

Description/Features

- General purpose stud mounted
- Broad forward and reverse voltage range – through 1200 volts
- Can be supplied to meet stringent military, aerospace and other high-reliability requirements

CASE STYLE AND DIMENSIONS



Conforms to JEDEC Outline TO-208AA (TO-48)
Dimensions in Millimeters and (Inches)

VOLTAGE RATINGS (Applied gate voltage zero or negative)

Part Numbers	V_{RRM} , V_{DRM} - Max. Repetitive Peak Reverse and Off-State Voltage (V)	V_{RSM} Max. Non Repetitive Peak Reverse Voltage $t_p < 5$ ms (V)
	$T_J = -65^{\circ}\text{C}$ to 125°C	$T_J = -65^{\circ}\text{C}$ to 125°C
2N681	25*	35*
2N682	50*	75*
2N683	100*	150*
2N685	200*	300*
2N687	300*	400*
2N688	400*	500*
2N689	500*	600*
2N690	600*	720*
2N691	700*	840*
2N692	800*	960*
	$T_J = -40^{\circ}\text{C}$ to 125°C	$T_J = -40^{\circ}\text{C}$ to 125°C
2N5204	600	720
2N5205	800	960
2N5206	1000	1200
2N5207	1200	1440

ELECTRICAL SPECIFICATIONS

		2N681-92	2N5204-07	Units	Conditions
ON-STATE					
$I_T(\text{RMS})$	Max. RMS on-state current	25	35	A	
$I_T(\text{AV})$	Max. average on-state current	16*	22*	A	
	@ $T_C =$	-65 to 65*	-40 to 40*	$^{\circ}\text{C}$	180° half sine wave conduction
I_{TSM}	Max. peak one cycle, non-repetitive surge current	145	285	A	50 Hz half cycle sine wave or 6 ms rectangular pulse
		150*	300*		60 Hz half cycle sine wave or 5 ms rectangular pulse
		170	340		50 Hz half cycle sine wave or 6 ms rectangular pulse
		180	355		60 Hz half cycle sine wave or 5 ms rectangular pulse
					Following any rated load condition, and with rated V_{RRM} applied following surge.
					Same conditions as above except with V_{RRM} applied following surge = 0.
I^2t	Max. I^2t capability, for fusing	103	410	A^2s	$t = 10$ ms
		94	375		$t = 8.3$ ms
I^2t	Max. I^2t capability, for individual device fusing	145	580	A^2s	$t = 10$ ms
		135	530		$t = 8.3$ ms
$I^2\sqrt{t}$	Max. $I^2\sqrt{t}$ capability, for individual device fusing $\text{\textcircled{1}}$	1450	5800	$\text{A}^2\sqrt{\text{s}}$	$t = 0.1$ to 10 ms initial $T_J \leq 125^{\circ}\text{C}$ V_{RRM} following surge = 0.
V_{TM}	Max. peak on-state voltage	2*	2.3*	V	$T_J = 25^{\circ}\text{C}$, $I_T(\text{AV}) = 16\text{A}$ (50A peak) 2N681, $I_T(\text{AV}) = 22\text{A}$ (70A peak) 2N5204
I_H	Max. holding current	20 @ 25°C \dagger	200* @ -40°C	mA	Anode supply = 24V, initial $I_T = 1.0\text{A}$.
BLOCKING					
dv/dt	Min. critical rate-of-rise of off-state voltage	100 \dagger	100*	V/ μs	$T_J = 125^{\circ}\text{C}$. Exponential to 100% rated V_{DRM}
		250 \dagger	250		$T_J = 125^{\circ}\text{C}$. Exponential to 67% rated V_{DRM}
					Gate open circuited.

*JEDEC Registered value.

 $\text{\textcircled{1}}$ I^2t for time $t_x = I^2\sqrt{t} \cdot \sqrt{t_x}$. \dagger Typical

ELECTRICAL SPECIFICATIONS (Continued)

		2N681-92	2N5204-07	Units	Conditions
BLOCKING (Continued)					
$I_{R(-)}$ & $I_{D(-)}$ Max. reverse and off-state current V_{RRM} & $V_{DRM} =$	5V	$I_{R(AV)}$ & $I_{D(AV)}$ (Average Values)	I_{RM} & I_{DM} (Peak Values)	mA	$T_J = 125^\circ\text{C}$, gate open circuited.
	25 to 150V	6.5*	—		
	200 & 250V	6.0*	—		
	300V	5.0*	—		
	400V	4.0*	—		
	500V	3.0*	—		
	600V	2.5*	3.3*		
	700V	2.25*	—		
	800V	2.0*	2.5*		
	1000V	—	2.0*		
1200V	—	1.7*			
SWITCHING					
t_d	Typical delay time	1	1	μs	$T_C = 25^\circ\text{C}$, $V_{DM} = \text{rated } V_{DRM}$, $I_{TM} = 10\text{A}$ dc resistive circuit. Gate pulse: 10V, 40 Ω source, $t_p = 6 \mu\text{s}$, $t_r = 0.1 \mu\text{s}$.
di/dt	Max. non-repetitive rate of rise of turned-on current $V_{DM} = 25$ to 600V	100	—	A/ μs	$T_C = 125^\circ\text{C}$, $V_{DM} = \text{rated } V_{DRM}$, $I_{TM} = 2 \times di/dt$. Gate pulse: 20V, 15 Ω , $t_p = 6 \mu\text{s}$, $t_r = 0.1 \mu\text{s}$ max. Per JEDEC standard RS-397, 5.2.2.6.
		= 700 to 800V	75		
		—	100		$T_C = 125^\circ\text{C}$, $V_{DM} = 600\text{V}$, $I_{TM} = 200\text{A}$ @ 400 Hz, max., Gate pulse: 20V, 15 Ω , $t_p = 6 \mu\text{s}$, $t_r = 0.1 \mu\text{s}$ max. Per JEDEC standard RS-397, 5.2.2.6.
TRIGGERING					
P_{GM}	Max. peak gate power	5*	60*	W	$t_p \leq 5$ ms for 2N681 series; $t_p \leq 500 \mu\text{s}$ for 2N5204 series.
$P_{G(AV)}$	Max. average gate power	0.5*	0.5*	W	
$+I_{GM}$	Max. peak positive gate current	2*	2	A	
$+V_{GM}$	Max. peak positive gate voltage	10*	—	V	
$-V_{GM}$	Max. peak negative gate voltage	5*	5*	V	
I_{GT}	Max. required DC gate current to trigger	80*	80*	mA	$T_C = \text{min. rated value}$. Max. required gate trigger current is the lowest value which will trigger all units with +6V anode-to-cathode.
		40	40		$T_C = 25^\circ\text{C}$
		18.5	20		$T_C = 125^\circ\text{C}$
	Typical DC gate current to trigger	30	30	$T_C = 25^\circ\text{C}$ +6V anode-to-cathode	
V_{GT}	Max. required DC gate voltage to trigger	3*	3*	V	$T_C = -65^\circ\text{C}$. Max. required gate trigger voltage is the lowest value which will trigger all units with +6V anode-to-cathode.
		2	2		$T_C = 25^\circ\text{C}$
	Typical DC gate voltage to trigger	1.5	1.5	$T_C = 25^\circ\text{C}$ +6V anode-to-cathode	
V_{GD}	Max. DC gate voltage not to trigger	0.25*	0.25*	V	$T_C = 125^\circ\text{C}$. Max. gate voltage not to trigger is the maximum value which will not trigger any unit with rated V_{DRM} anode-to-cathode.

THERMAL-MECHANICAL SPECIFICATIONS

		2N681-82	2N5204-07	Units	Conditions
T_J	Operating junction temperature range	-65° to 125°	-40° to 125°	°C	
T_{stg}	Storage temperature range	-65° to 125°	-40° to 125°	°C	
R_{thJC}	Max. internal thermal resistance, junction to case	1.5	1.5*	deg. C/W	DC operation
R_{thCS}	Thermal resistance, case to sink	0.35	0.35	deg. C/W	Mounting surface smooth, flat and greased.
	Mounting torque to nut ±10%	20,(27.5)		lbf · in.	Lubricated threads (non-lubricated threads).
		0.23(.32)		kgf · m	
	to device	2.3(3.1)		N·m	Lubricated threads.
		25		lbf · in.	
		0.29		kgf · m	
		2.8		N·m	
wt	Approximate weight	14(0.49)	14 (0.5)	g (oz.)	
	Case Style	TO-208AA (TO-48)			

*JEDEC Registered value.

2N681 Series




Fig. 1 – Maximum Allowable Case Temperature Vs. Average On-State Current, 2N681 Series




Fig. 2 – Maximum On-State Voltage Vs. Current, 2N681 Series

2N681 Series




Fig. 3 — Maximum Low Level On-State Power Loss Vs. Current (Sinusoidal Current Waveform), 2N681 Series




Fig. 4 — Maximum High Level On-State Power Loss Vs. Current (Sinusoidal Current Waveform), 2N681 Series




Fig. 5 — Gate Characteristics, 2N681 Series




Fig. 5A — Area of All Possible Triggering Points Vs. Temperature 2N681 Series

2N681 Series




Fig. 6 – Maximum Transient Thermal Impedance, Junction to Case, Vs. Pulse Duration, 2N681 Series




Fig. 7 – Maximum Non-Repetitive Surge Current, Vs. Number of Current Pulses, 2N681 Series

2N5204 Series




Fig. 8 – Maximum Allowable Case Temperature Vs. Average On-State Current (Sinusoidal Current Waveform), 2N5204 Series




Fig. 9 – Maximum Allowable Case Temperature Vs. Average On-State Current (Rectangular Current Waveform), 2N5204 Series

2N5204 Series




Fig. 10 — Maximum Low-Level On-State Power Loss Vs. Average On-State Current (Sinusoidal Current Waveform), 2N5204 Series




Fig. 11 — Maximum High-Level On-State Power Loss Vs. Average On-State Current (Sinusoidal Current Waveform), 2N5204 Series




Fig. 12 — Maximum Low-Level On-State Power Loss Vs. Average On-State Current (Rectangular Current Waveform), 2N5204 Series




Fig. 13 — Maximum High-Level On-State Power Loss Vs. Average On-State Current (Rectangular Current Waveform), 2N5204 Series




Fig. 14 — Maximum Instantaneous On-State Voltage Vs. Instantaneous On-State Current, 2N5204 Series




Fig. 15 — Maximum Transient Thermal Resistance, Junction to Case, Vs. Pulse Duration, 2N5204 Series



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.