


# Schottky PowerMod

## CPT50035 — CPT50050



Dim.	Inches		Millimeters		Notes
	Min.	Max.	Min.	Max.	
A	---	3.630	---	92.20	
B	0.700	0.800	17.78	20.32	
C	---	0.680	---	17.28	
E	0.120	0.130	3.05	3.30	
F	0.490	0.510	12.45	12.95	
G	1.375 BSC		34.92 BSC		
H	0.010	---	0.25	---	
N	---	---	---	---	1/4-20
Q	0.275	0.290	6.99	7.37	Dia.
R	3.150 BSC		80.01 BSC		
U	0.600	---	15.24	---	
V	0.312	0.340	7.92	8.64	
W	0.180	0.195	4.57	4.95	Dia.

Microsemi Catalog Number	Working Peak Reverse Voltage	Repetitive Peak Reverse Voltage
CPT50035*	35V	35V
CPT50040*	40V	40V
CPT50045*	45V	45V
CPT50050*	50V	50V

\*Add Suffix A for Common Anode, D for Doubler

- Schottky Barrier Rectifier
- Guard Ring Protection
- 500 Amperes/35 to 50 Volts
- 175°C Junction Temperature
- Reverse Energy Tested

### Electrical Characteristics

Average forward current per pkg	I <sub>F(AV)</sub> 500 Amps	T <sub>C</sub> = 134°C, Square wave, R <sub>θJC</sub> = 0.12°C/W
Average forward current per leg	I <sub>F(AV)</sub> 250 Amps	T <sub>C</sub> = 134°C, Square wave, R <sub>θJC</sub> = 0.24°C/W
Maximum surge current per leg	I <sub>FSM</sub> 5000 Amps	8.3ms, half sine, T <sub>J</sub> = 175°C
Maximum repetitive reverse current per leg	I <sub>R(OV)</sub> 2 Amps	f = 1 KHZ, 25°C, 1 μsec square wave
Max peak forward voltage per leg	V <sub>FM</sub> 0.70 Volts	I <sub>FM</sub> = 250A: T <sub>J</sub> = 25°C
Max peak forward voltage per leg	V <sub>FM</sub> 0.55 Volts	I <sub>FM</sub> = 250A: T <sub>J</sub> = 175°C
Max peak reverse current per leg	I <sub>RM</sub> 200 mA	V <sub>R</sub> = 5.0V, T <sub>C</sub> = 25°C
Max peak reverse current per leg	I <sub>RM</sub> 8.0 mA	V <sub>RRM</sub> , T <sub>J</sub> = 125°C*
Typical junction capacitance per leg	C <sub>J</sub> 9800 pF	V <sub>RRM</sub> , T <sub>J</sub> = 25°C

\*Pulse test: Pulse width 300 μsec, Duty cycle 2%

### Thermal and Mechanical Characteristics

Storage temp range	T <sub>STG</sub>	-55°C to 175°C
Operating junction temp range	T <sub>J</sub>	-55°C to 175°C
Max thermal resistance per leg	R <sub>θJC</sub>	0.24°C/W Junction to case
Max thermal resistance per pkg	R <sub>θJC</sub>	0.12°C/W Junction to case
Typical thermal resistance (greased)	R <sub>θCS</sub>	0.08°C/W Case to sink
Terminal Torque		35-50 inch pounds
Mounting Base Torque (outside holes)		30-40 inch pounds
Mounting Base Torque (center hole) center hole must be torqued first		8-10 inch pounds
Weight		2.8 ounces (78 grams) typical

# CPT50035 — CPT50050

Figure 1  
Typical Forward Characteristics — Per Leg




Figure 3  
Typical Junction Capacitance — Per Leg




Figure 4  
Forward Current Derating — Per Leg




Figure 2  
Typical Reverse Characteristics — Per Leg





Figure 5  
Maximum Forward Power Dissipation — Per Leg





LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.