



MILITARY DATA SHEET

MN54F138-X REV 1A0

Original Creation Date: 03/14/96
 Last Update Date: 07/30/96
 Last Major Revision Date: 03/14/96

1-OF-8 DECODER/DEMULTIPLEXER

General Description

The F138 is a high-speed 1-of-8 decoder/demultiplexer. This device is ideally suited for high-speed bipolar memory chip select address decoding. The multiple input enables allow parallel expansion to a 1-of-24 decoder using just three F138 devices or a 1-of-32 decoder using four F138 devices and one inverter.

Industry Part Number

54F138

NS Part Numbers

54F138DMQB
 54F138FMQB
 54F138LMQB

Prime Die

M138

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

Features

- FAST Process for High Speed
- Demultiplexing Capability
- Multiple input Enable for Easy Expansion
- Active LOW Mutually Exclusive Outputs

(Absolute Maximum Ratings)

(Note 1)

Storage Temperature	-65 C to +150 C
Ambient Temperature under Bias	-55 C to +125 C
Junction Temperature under Bias	-55 C to +175 C
Vcc Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30 mA to +5.0mA
Voltage Applied to Output in HIGH State (with Vcc=0V)	
Standard Output	-0.5V to Vcc
TRI-STATE Output	-0.5V to +5.5V
Current Applied to Output in LOW State (Max)	twice the rated Iol(mA)
ESD Last Passing Voltage (Min)	4000V

Note 1: Absolute maximum ratings are those values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature	
Commercial	0 C to +70 C
Military	-55 C to +125 C
Supply Voltage	
Military	+4.5V to +5.5V
Commercial	+4.5V to +5.5V

Electrical Characteristics

DC PARAMETER

(The following conditions apply to all the following parameters, unless otherwise specified.)
DC: VCC 4.5V to 5.5V, Temp range: -55C to 125C

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	Input High Current	VCC=5.5V, VM=2.7V, VINH=5.5V	1, 3	INPUTS		20	uA	1, 2, 3
IBVI	Input High Current	VCC=5.5V, VM=7.0V, VINH=5.5V	1, 3	INPUTS		100	uA	1, 2, 3
IIL	Input LOW Current	VCC=5.5V, VM=0.5V, VINH=5.5V	1, 3	INPUTS		-0.6	mA	1, 2, 3
VOL	Output LOW Voltage	VCC=4.5V, VIL=0.8V, IOL=20mA, VIH=2.0V	1, 3	OUTPUTS		0.5	V	1, 2, 3
VOH	Output HIGH Voltage	VCC=4.5V, VIL=0.8V, IOH=-1.0mA, VINH=5.5V, VIH=2.0V, VINL=0.0V	1, 3	OUTPUTS	2.5		V	1, 2, 3
IOS	Short Circuit Current	VCC=5.5V, VINL=0.0V, VM=0.0V, VINH=5.5V	1, 3	OUTPUTS	-60	-150	mA	1, 2, 3
VCD	Input Clamp Diode Voltage	VCC=4.5V, IM=-18mA	1, 3	INPUTS		-1.2	V	1, 2, 3
ICC	Supply Current	VCC=5.5V, VINL=0.0V, VINH=5.5V	1, 3	VCC		20	mA	1, 2, 3
ICEX	Output HIGH Leakage Current	VCC=5.5V, VINL=0.0V, VINH=5.5V, VM=5.5V	1, 3	OUTPUTS		250	uA	1, 2, 3

Electrical Characteristics

AC PARAMETER

(The following conditions apply to all the following parameters, unless otherwise specified.)
 AC: CL=50pf, RL=500 OHMS, TR=2.5ns, TF=2.5ns SEE AC FIGS

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpLH(1)	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	An to $\bar{O}n$	3.0	7.5	ns	9
			2, 4	An to $\bar{O}n$	3.0	12.0	ns	10, 11
tpHL(1)	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	An to $\bar{O}n$	4.0	8.0	ns	9
			2, 4	An to $\bar{O}n$	4.0	9.5	ns	10, 11
tpLH(2)	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	E1/2 to $\bar{O}n$	3.0	7.0	ns	9
			2, 4	E1/2 to $\bar{O}n$	3.0	11.0	ns	10, 11
tpHL(2)	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	E1/2 to $\bar{O}n$	3.0	7.0	ns	9
			2, 4	E1/2 to $\bar{O}n$	3.0	8.0	ns	10, 11
tpLH(3)	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	E3 to $\bar{O}n$	3.5	8.0	ns	9
			2, 4	E3 to $\bar{O}n$	3.5	12.5	ns	10, 11
tpHL(3)	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	E3 to $\bar{O}n$	3.5	7.5	ns	9
			2, 4	E3 to $\bar{O}n$	3.5	8.5	ns	10, 11

Note 1: Screen tested 100% on each device at +25C, +125C, & -55C temperature, subgroups A1, 2, 3, 7 & 8.

Note 2: Screen tested 100% on each device at +25C temperature only, subgroup A9.

Note 3: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C, +125C & -55C temperature, subgroups A1, 2, 3, 7 & 8.

Note 4: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C subgroup A9, and periodically at +125C & -55C temperature, subgroups 10 & 11.

National Semiconductor was acquired by Texas Instruments.

http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html

This file is the datasheet for the following electronic components:

JM38510/33701BEA - <http://www.ti.com/product/jm38510/33701bea?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F138LMQB - <http://www.ti.com/product/54f138lmb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F138FMQB - <http://www.ti.com/product/54f138fmb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

54F138DMQB - <http://www.ti.com/product/54f138dmb?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/33701BFA - <http://www.ti.com/product/jm38510/33701bfa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/33701SEA - <http://www.ti.com/product/jm38510/33701sea?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/33701B2A - <http://www.ti.com/product/jm38510/33701b2a?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

JM38510/33701SFA - <http://www.ti.com/product/jm38510/33701sfa?HQS=TI-null-null-dscatalog-df-pf-null-wwe>



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

LittleDiode.com

Looking forward to providing you with the best possible service.