



**MILITARY DATA SHEET**

**MN54F379-X REV 1A0**

Original Creation Date: 04/29/96  
 Last Update Date: 07/30/96  
 Last Major Revision Date: 04/29/96

**QUAD PARALLEL REGISTER WITH ENABLE**

**General Description**

The F379 is a 4-bit register with a buffered common Enable. This device is similar to the F175, but with common Enable rather than common Master Reset.

**Industry Part Number**

54F379

**NS Part Numbers**

54F379DMQB  
 54F379FMQB  
 54F379LMQB

**Prime Die**

M379

**Processing**

MIL-STD-883, Method 5004

**Quality Conformance Inspection**

MIL-STD-883, Method 5005

Subgrp	Description	Temp ( °C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

**Features**

- Edge-Triggered D-type inputs
- Buffered Positive Edge-Triggered Clock
- Buffered Common Enable Input
- True and Complement Outputs

**(Absolute Maximum Ratings)**

(Note 1)

Storage Temperature	-65 C to +150 C
Ambient Temperature under Bias	-55 C to +125 C
Junction Temperature under Bias	-55 C to +175 C
Vcc Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30mA to +5.0mA
Voltage Applied to Output in HIGH State (with Vcc=0V)	
Standard Output	-0.5V to Vcc
TRI-STATE Output	-0.5V to +5.5V
Current Applied to Output in LOW State (Max)	twice the rated Iol(mA)
ESD Last Passing Voltage (Min)	4000V

Note 1: Absolute Maximum ratings are those values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

**Recommended Operating Conditions**

Free Air Ambient Temperature	
Commercial	0 C to +70 C
Military	-55 C to +125 C
Supply Voltage	
Military	+4.5V to +5.5V
Commercial	+4.5V to +5.5V

## Electrical Characteristics

### DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)  
DC: VCC 4.5V to 5.5V, Temp range: -55C to 125C

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	Input High Current	VCC=5.5V, VM=2.7V, VINH=5.5V, VINL=0.0V	1, 3	INPUTS		20	uA	1, 2, 3
IBVI	Input High Current	VCC=5.5V, VM=7.0V, VINH=5.5, VINL=0.0V	1, 3	INPUTS		100	uA	1, 2, 3
IIL	Input LOW Current	VCC=5.5V, VM=0.5V, VINH=5.5V, VINL=0.0V	1, 3	INPUTS		-0.6	mA	1, 2, 3
VOL	Output LOW Voltage	VCC=4.5V, VIL=0.8V, IOL=20mA, VINH=5.5V, VINL=0.0V, VIH=2.0V	1, 3	OUTPUTS		0.5	V	1, 2, 3
VOH	Output HIGH Voltage	VCC= 4.5V, VIH=2.0V, IOH=-1.0mA, VIL=0.8V, VINL=0.0V, VINH=5.5V	1, 3	OUTPUTS	2.5		V	1, 2, 3
IOS	Short Circuit Current	VCC=5.5V, VINH=5.5V, VINL=0.0V, VM=0.0V	1, 3	OUTPUTS	-60	-150	mA	1, 2, 3
VCD	Input Clamp Diode Voltage	VCC=4.5V, IM=-18mA, VINH=5.5V	1, 3	INPUTS		-1.2	V	1, 2, 3
ICC	Supply Current	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 3	VCC		40	mA	1, 2, 3
ICEX	Output HIGH Leakage Current	VCC=5.5V, VINH=5.5V, VINL=0.0V, VM=5.5V	1, 3	OUTPUTS		250	uA	1, 2, 3

## Electrical Characteristics

### AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)  
 AC: CL=50pf, RL=500 OHMS, TR=2.5ns, TF=2.5ns SEE AC FIGS

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpLH	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	CP to Qn or Qn	4.0	6.5	ns	9
			2, 4	CP to Qn or Qn	3.0	8.5	ns	10, 11
tpHL	Propagation Delay	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	2, 4	CP to Qn or Qn	5.0	8.5	ns	9
			2, 4	CP to Qn or Qn	4.0	10.0	ns	10, 11
ts(H/L)(1)	Setup Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	5	Dn to CP	3.0		ns	9
			5	Dn to CP	4.0		ns	10, 11
th(H/L)(1)	Hold Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	5	Dn to CP	1.0		ns	9
			5	Dn to CP	2.0		ns	10, 11
ts(H/L)(2)	Setup Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	5	$\bar{E}$ to CP	6.0		ns	9
			5	$\bar{E}$ to CP	8.0		ns	10, 11
th(H/L)(2)	Hold Time	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C	5	$\bar{E}$ to CP	0		ns	9, 10, 11
tw(H)	Pulse Width	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C TR/TF=1.0ns	5	CP	4.0		ns	9
			5	CP	5.0		ns	10, 11
tw(L)	Pulse Width	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C TR/TF=1.0ns	5	CP	5.0		ns	9
			5	CP	7.0		ns	10, 11
fMAX	Maximum Clock Frequency	VCC=5.0V @25C, VCC=4.5V & 5.5V @-55/125C TR/TF=1.0ns	5		100		MHZ	9
			5		75		MHZ	10, 11

Note 1: Screen tested 100% on each device at +25C, +125C & -55C temperature, subgroups A1, 2, 3, 7 & 8.

Note 2: Screen tested 100% on each device at +25C temperature only, subgroup A9.

Note 3: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C, +125C & -55C temperature, subgroups A1, 2, 3, 7 & 8.

Note 4: Sample tested (Method 5005, Table 1) on each MFG. lot at +25C subgroup A9, and periodically at +125C & -55C temperature, subgroups 10 & 11.

# National Semiconductor was acquired by Texas Instruments.

[http://www.ti.com/corp/docs/investor\\_relations/pr\\_09\\_23\\_2011\\_national\\_semiconductor.html](http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html)

This file is the datasheet for the following electronic components:

54F379DMQB - <http://www.ti.com/product/54f379dmqb?HQS=TI-null-null-dscatalog-df-pf-null-ww>

54F379LMQB - <http://www.ti.com/product/54f379lmqb?HQS=TI-null-null-dscatalog-df-pf-null-ww>



LittleDiode supplies new, hard to find or obsolete electronic components and semiconductors all over the world.

With over two million different components listed you are sure to find the part you need.

Feel free to visit us today at our online store:

[LittleDiode.com](http://LittleDiode.com)

Looking forward to providing you with the best possible service.